


SI4642D

Hob, Aesthetics: Universal, Induction, 60 cm, Built-in: Ultra-low profile or Fully Flushed

































TYPE

Product Family: Hob • Dimensions: 60 cm • Type: Induction • Built-in: Ultra-low profile or Fully Flushed • Power supply: Electric • EAN code: 8017709287092

AESTHETICS

Colour: Black • Finishing: Glass • Aesthetics: Universal • Material: Glass • Glass Type: Ceramic • Type of control setting: VTC controls • Control knobs position: Front • Slider: Yes • Slider: Red • Glass edge: Straight edge • Serigraphy colour: Grey

PROGRAMME / FUNCTIONS

Total no. of cook zones: 4 • No. of induction cook zones: 4 • Time-setting options: Automatic switch-off • No. of cooking zones with booster: 4 • Main on/off switch: Yes • Power levels: 9

OPTIONS

Standard cut out: 478-482x555-560 mm • End cooking timer: 1 • Pause option: Yes • Minute minder: 1 • End of cooking acoustic alarm: Yes • Residual time indicator: Yes • Limited Power Consumption Mode: Yes advance • Limited Power Consumption Mode in W: 2400, 2800, 3500, 4000, 4500, 5000, 5500, 6000, 7400 W • Control Lock / Child Safety: Yes • Keep warm automatic function: Yes • Rapid level selection: Yes

COOKING ZONES

1st zone position: Front left • 2nd zone position: Rear left • 3rd zone position: Rear right • 4th zone position: Front right • 1st zone type: Induction - single • 2nd zone type: Induction - single • 3rd zone type: Induction - single • 4th zone tipe: Induction - single • 1st zone dimensions: Ø 21.0 cm • 2nd zone dimensions: Ø 16.0 cm • 3rd zone dimensions: Ø 21.0 cm • 4th zone dimensions: Ø 16.0 cm • 1st zone power: 2.30 kW • 2nd zone power: 1.85 kW • 3rd zone power: 2.30 kW • 4th zone power: 1.85 kW • 1st zone booster power: 2.10 kW • 3rd zone booster power: 3.00 kW • 4th zone booster power: 2.10 kW

TECHNICAL FEATURES

Automatic setting according to pan dimension: Yes • Permanent Automatic Pot Detection with indication of the relative control:
Yes • Automatic pan detection: Yes, min 7 cm • Minimum pan diameter indication: Yes • Automatic switch off when overheat: Yes
• Residual heat indicator: Yes • Protection against accidental start up: Yes

PERFORMANCE / ENERGY LABEL

2nd zone energy consumption: 190 Wh/Kg • Energy consumption zone 3: 193 Wh/Kg • Energy consumption zone 4: 190 Wh/Kg

ELECTRICAL CONNECTION

Nominal power (W): 7400 W • Voltage (V): 220-240 V • Frequency (Hz): 50/60 Hz • Type of electric cable: Single and Double phase • Power supply cable length: 120 cm

LOGISTIC INFORMATION

Dimensions of the product (mm): 56x600x510 • Depth (mm): 510 mm • Width (mm): 600 mm • Product Height (mm): 56 mm

