Belly pan

for: Triumph Speed Twin 1200 Triumph Thruxton 1200 / R / RS Triumph Street Twin

Part number: RMC-010300

Instruction Manual

Version: 3 Date: 12.09.2021

Read and save this manual for future reference. Before attempting to assemble, install, operate the products, please ensure a complete understanding of the instructions and any other documents related to the products, including but not limited to a provided disclaimer. Failure to comply with instructions in this manual could result in serious injury, death and/or property damage. This manual is subject to change without notice.



Important note

Products of Rennstall Moto or any of its affiliates (collectively, "Rennstall") are sold "AS IS" without any express or implied warranties. To the fullest extent permitted by law, Rennstall disclaims any and all warranties. Installation or usage of Rennstall's products may affect warranties of utilized vehicles, such as motorcycles.

ANY BUYER OR USER OF PRODUCTS OF RENNSTALL EXPRESSLY AND VOLUNTARILY ASSUMES ANY AND ALL RISKS INCLUDING, BUT NOT LIMITED TO, DEATH, DISABILITY, AND/OR SERIOUS PHYSICAL INJURY, RELATED TO THE INSTALLATION OR USAGE OF SUCH PRODUCTS BY BUYER, USER OR ANY THIRD PARTY.

Under no circumstances are Rennstall's products to be used on public roads or any other streets, highways, or off-road areas. Rennstall's products are solely intended for use on vehicles operated on closed-course facilities, show events or racetracks, each with appropriate supervision of qualified individuals to ensure safety of all involved parties.

Always use caution when installing or using Rennstall's products, adhere to all instructions, only utilize provided hardware or tools, and do not modify or otherwise alter the products.

Prior to any usage of Rennstall's products, a buyer or user shall inspect and verify the integrity of the entire vehicle upon which such products are mounted, installed, or otherwise attached. Vehicles are to be inspected before each use for evidence of damage, defect, or wear to ensure the vehicle is fit and ready for operation. Without limiting the generality of the foregoing, buyer or user shall specifically inspect all bolts after each usage in excess of Two Hundred (200) kilometers or One Hundred Twenty-Five (125) miles.

Under no circumstances and under no legal theory whether in tort, contract, or otherwise shall Rennstall or its employees, agents, representatives, successors, or assigns, be liable to a buyer, user or any other person for any direct, indirect, special, incidental, or consequential damages of any kind arising out of or relating to the installation or usage of the products, even if Rennstall has been informed of the possibility of such damages, or for any claim by any other party.

Belly Pan

Part Number: RMC-010300



Time:

<1h

Preparation:

None

Steps:

- Mount the two spacers to the latches on the bottom of the frame using the two tin nuts (do not yet tighten since some fine adjustment might be needed). → Fig.1
- Place the two large M6 washers between the belly pan and the spacers mounted to the frame. → Fig.1
 (Recommendation: Fixate the washers with some sealant or modeling clay).
- Loosen the top radiator mount. Do not remove the bolt completely! → Fig.2

 Push the radiator upwards about 5mm (3/16") until you get a gap between the radiator and its bottom mounting points on the frame (blue arrow). → Fig.3
- Mount the two stainless steel brackets to the bottom radiator mounts on the frame by sliding them in the created gap and pushing them outwards from the inside. You might need to turn them slightly. → Fig.4
 - Slide the radiator down and keep pushing it down while tightening the top radiator mount. Torque down to 10Nm (7.4 ft·lb).
- Put belly pan into place and insert the bottom two TX M6 bolts plus countersunk washers. Do not yet tighten.

Insert the two TX M6 bolts plus countersunk washers at the top and thread them into the tin nuts. Torque down to 8Nm (5.9 ft·lb).

Now torque down the bottom two bolts to 8Nm (5.9 ft·lb).




Fig.1



Fig.2



Fig.3



Fig.4