














#### Features:

- Efficacy Of Up To 151lm/W\*
- Resistant To Marine Enviroments
- Minimum Lumen Maintenance: 50 000h (L80B20)

Power Supply:	220-240V AC   50 - 60Hz		- 1			
Colour Rendering Index:	CRI 80+					
Colour Consistency:	3-Step MacAdam					
Colour Temperature: (Kelvin / CCT)	<b>○</b> 3000K					
Installation Type:	Surface Mounted					
Ingress Protection:	IP65					
IK Rating:	IK10					
Luminaire Colour:	■ Grey					
Material:	Housing - Powder coated die-cast aluminium Diffuser - Polycarbonate matt					
	Dimensions	Wattage (System)	CRI	Kelvin	Luminous Flux (Effective)	
	201mm x 150mm x 150mm	15W	80+	3000K	7236Lm*	
	650mm x 150mm x 150mm	15W	80+	3000K	10134Lm*	
	1000mm x 150mm x 150mm	15W	80+	3000K	13788Lm*	

#### **Dimensions:**



<sup>\*</sup>E & O.E (Errors And Omissions Excepted)

 $<sup>^* \</sup>textit{Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above}\\$ are subject to change without prior notice.

 $<sup>{}^{\</sup>star}\text{All lumen outputs stated above are based a nominal output that included a 10\% light loss, this can vary depending on the optic used.}$ 



# Contact

# **Cape Town**

1B Hansen Close, Richmond Park, Cape Town T. +27 21 555 0570

## Durban

Unit L, Nandi Park, 34 Brickworks Way Briardene T. +27 31 001 2964

## Namibia - Windhoek

Unit 2, Tesoro Building, 31 TV More Street Windhoek T. +264 61 40 0339

# Johann esburg

17 Galaxy Road, Unit 5A Galaxy Park, Linbro Park T. +27 11 262 5179

## Port Elizabeth

216 Main Road, Walmer Port Elizabeth T. +27 41 451 4359