

LED UNIVERSE





Features:

- Constant Current
- Output Voltage Of 10-300V
- SANS1464-22 Compliant
- Self-Testing
- Built In Driver
- Remote Box Supplied

Power Supply:	220-240V AC 50 - 60Hz
Emergency Duration:	1 Hour 20% Output
Battery Type:	7.2V Lithium-Ion
Ingress Protection:	IP20
Dimensions:	Inverter: 170mm x 45mm x 35mm Battery: 170mm x 45mm x 35mm
Remote Box Dimensions:	400mm x 50mm x 45mm

*For detailed luminaire compatibility, please contact your Rubicon Lighting representative.

*Please note this unit is used in situations where LED light source makes use of a built in driver.



*E & O.E (Errors And Omissions Excepted)

*Subject to change without prior notice.

Contact

Cape Town

1B Hansen Close,
Richmond Park,
Cape Town
T. +27 21 555 0570

Durban

Unit L, Nandi Park,
34 Brickworks Way
Briardene
T. +27 31 001 2964

Namibia – Windhoek

Unit 2, Tesoro Building,
31 TV More Street
Windhoek
T. +264 61 40 0339

Johannesburg

17 Galaxy Road,
Unit 5A Galaxy Park,
Linbro Park
T. +27 11 262 5179

Port Elizabeth

216 Main Road,
Walmer
Port Elizabeth
T. +27 41 451 4359