

















- Inox AISI 316 Stainless Steel
- Coastal Quality
- Adjustable Beam Tilt
- Minimum Lumen Maintenance: 50 000h (L70B30)




Power Supply:	24V DC		
LED-Module	RGB		
Installation Type:	Recessed, Ground		
Beam Angle:	16° _ 34° Diffuser Filter		
Ingress Protection:	IP67		
IK Rating:	IK10		
Dimensions:	Ø180mm x 90mm		
Material:	Body - Stainless Steel & Aluminium Diffuser - Tempered Glass		
	Dimensions	Wattage (System)	Luminous Flux (Effective)
	Ø180mm x 90mm	11W	490Lm*

*RGB control unit required, please see next page.

Includes:



Dimensions:



^{*}E & O.E (Errors And Omissions Excepted)

^{*}Due to the rapid development in LED technology the performance values, power consumption and lumen output levels statedæbove subject to change without prior notice.

^{*}All lumen outputs stated above are based a nominal output that included a 10% light loss, this can vary depending on the option



MASTER RGB




Features:

- Multi-Voltage Electronic Gear Included
- Colour Selection Remote Control Included



Dimensions:



150W

SLAVE RGB




Features:

- Multi-Voltage Electronic Gear Included
- Colour Selection Remote Control Included



Dimensions:



150W

^{*}E & O.E (Errors And Omissions Excepted)

^{*}Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.

^{*}All lumen outputs stated above are based a nominal output that included a 10% light loss, this can vary depending on the optic used.



Contact

Cape Town

1B Hansen Close, Richmond Park, Cape Town T. +27 21 555 0570

Durban

Unit L, Nandi Park, 34 Brickworks Way Briardene T. +27 31 001 2964

Namibia - Windhoek

Unit 2, Tesoro Building, 31 TV More Street Windhoek T. +264 61 40 0339

Johann esburg

17 Galaxy Road, Unit 5A Galaxy Park, Linbro Park T. +27 11 262 5179

Port Elizabeth

216 Main Road, Walmer Port Elizabeth T. +27 41 451 4359