















Features:

- Inox AISI 316 Stainless Steel
- Coastal Quality
- Adjustable Beam Tilt
- Minimum Lumen Maintenance: 50 000h (L70B30)




Power Supply:	24V DC		
LED-Module	RGB		
Installation Type:	Recessed, Ground		
Beam Angle:	16° _ 34° Diffuser Filter		
Ingress Protection:	IP67		
IK Rating:	IK10		
Dimensions:	120mm x 120mm x 95mm		
Material:	Body - Stainless Steel & Aluminium Diffuser - Tempered Glass		
	Dimensions	Wattage (System)	Luminous Flux (Effective)
	120mm x 120mm x 95mm	6W	240Lm*

*RGB control unit required, please see next page.

Includes:



Dimensions:



^{*}E & O.E (Errors And Omissions Excepted)

^{*}Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.

^{*}All lumen outputs stated above are based a nominal output that included a 10% light loss, this can vary depending on the optic used.



MASTER RGB




Features:

Multi-Voltage Electronic Gear Included Colour Selection Remote Control Included



Dimensions:



150W

SLAVE RGB




Features:

Multi-Voltage Electronic Gear Included Colour Selection Remote Control Included



Dimensions:



150W

^{*}E & O.E (Errors And Omissions Excepted)

^{*}Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.



Contact

Cape Town

1B Hansen Close, Richmond Park, Cape Town T. +27 21 555 0570

Durban

Unit L, Nandi Park, 34 Brickworks Way Briardene T. +27 31 001 2964

Namibia - Windhoek

Unit 2, Tesoro Building, 31 TV More Street Windhoek T. +264 61 40 0339

Johannesburg

17 Galaxy Road, Unit 5A Galaxy Park, Linbro Park T. +27 11 262 5179

Port Elizabeth

216 Main Road, Walmer Port Elizabeth T. +27 41 451 4359