

Luminous Flux

(Effective)

573Lm*











Features:

- Efficacy Of Up To 47lm/W*
- Resistant To Marine Enviroments
- Minimum Lumen Maintenance: 50 000h (L80B20)

Power Supply:	220-240V AC 50 - 60Hz	
Diffuser Options:	• Clear • Matt	
Colour Rendering Index:	CRI 80+	
Colour Consistency:	3-Step MacAdam	
Colour Temperature: (Kelvin / CCT)	○ 3000К	
Beam Angle:	86°	
Installation Type:	Surface Mounted	
Ingress Protection:	IP65	
IK Rating:	IK08	
Luminaire Colour:	Grey	

Housing - Powder Coated Aluminium

Diffuser - Polycarbonate


Dimensions

Ø160mm x 800mm



Light Distribution:

Material:




Dimensions:

Wattage

(System)

12W



CRI

+08

Kelvin

3000K

^{*}E & O.E (Errors And Omissions Excepted)

^{*}Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.

^{*}All lumen outputs stated above are based a nominal output that included a 10% light loss, this can vary depending on the optic used.



Contact

Cape Town

1B Hansen Close, Richmond Park, Cape Town T. +27 21 555 0570

Durban

Unit L, Nandi Park, 34 Brickworks Way Briardene T. +27 31 001 2964

Namibia - Windhoek

Unit 2, Tesoro Building, 31 TV More Street Windhoek T. +264 61 40 0339

Johann esburg

17 Galaxy Road, Unit 5A Galaxy Park, Linbro Park T. +27 11 262 5179

Port Elizabeth

216 Main Road, Walmer Port Elizabeth T. +27 41 451 4359