

RUBICON
LIGHTING

SAXA TRI-PROOF






Features:

- Efficacy Of Up To 120lm/W*
- Easy Replacement And Installation
- Can Be Used As Either Side Or Back Cable Entry
- Minimum Lumen Maintenance: 50 000h (L80B10)



Power Supply:	220 - 240V AC 50 - 60Hz				
Operating Temperature Range: (Ta - Ambient)	-36°C to + 45°C				
Colour Rendering Index:	CRI 83+				
Colour Consistency:	3-Step MacAdam				
Colour Temperature: (Kelvin / CCT)	● 2700K ● 4000K ● 6500K ● 3000K ● 5000K				
Beam Angle:	110°				
Installation Type:	Surface Mounted				
Ingress Protection:	IP65				
IK Rating:	IK10				
Luminaire Colour:	<input type="radio"/> White				
Material:	Housing - Aluminium Diffuser - Shock & Pressure Proof Polycarbonate				
	Dimensions	Wattage (System)	CRI	Kelvin	Luminous Flux (Effective)
	613mm x 74mm x 64mm	18W	83+	4000K	2160Lm*
	1175mm x 74mm x 64mm	36W	83+	4000K	4320Lm*
	1456mm x 74mm x 64mm	54W	83+	4000K	6480Lm*

Dimensions:



*E & O.E (Errors And Omissions Excepted)

*Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.

*All lumen outputs stated above are based a nominal output that included a 10% light loss, this can vary depending on the optic used.

Contact

Cape Town

1B Hansen Close,
Richmond Park,
Cape Town
T. +27 21 555 0570

Durban

Unit L, Nandi Park,
34 Brickworks Way
Briardene
T. +27 31 001 2964

Namibia – Windhoek

Unit 2, Tesoro Building,
31 TV More Street
Windhoek
T. +264 61 40 0339

Johannesburg

17 Galaxy Road,
Unit 5A Galaxy Park,
Linbro Park
T. +27 11 262 5179

Port Elizabeth

216 Main Road,
Walmer
Port Elizabeth
T. +27 41 451 4359