









#### Features:

- Non-Maintained Operation
- SABS Approved
- High Level Emergency Illumination
- DALI Optional
- Self Contained
- Minimum Lumen Maintenance: 50 000h (L80B10)



Power Supply:	220-240V AC   50 - 60Hz		
Emergency Duration:	1 Hour 100% Output		
Legend Height:	150mm		
Battery Type:	5x 2Ahr Nickel-Cadmium		
Colour Temperature: (Kelvin / CCT)	<b>○</b> 4000K		
Installation Type:	Surface Mounted		
Ingress Protection:	IP20		
	Dimensions	Wattage (System)	Luminous Flux (Effective)
	430mm x 215mm x 45mm	3W	240Lm*

#### **Dimensions:**



<sup>\*</sup>E & O.E (Errors And Omissions Excepted)

 $<sup>^* \</sup>textit{Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are}\\$ subject to change without prior notice.

<sup>\*</sup>All lumen outputs stated above are based a nominal output that included a 10% light loss, this can vary depending on the optic used.



# Contact

# **Cape Town**

1B Hansen Close, Richmond Park, Cape Town T. +27 21 555 0570

## Durban

Unit L, Nandi Park, 34 Brickworks Way Briardene T. +27 31 001 2964

## Namibia - Windhoek

Unit 2, Tesoro Building, 31 TV More Street Windhoek T. +264 61 40 0339

# Johann esburg

17 Galaxy Road, Unit 5A Galaxy Park, Linbro Park T. +27 11 262 5179

## Port Elizabeth

216 Main Road, Walmer Port Elizabeth T. +27 41 451 4359