














Features:

- Locally Manufactured
- Passive Cooling
- Multi-Bank Connector For Up To 7 Fittings
- Minimum Lumen Maintenance: 50 000h (L70B10)



Power Supply:	220-240V AC 50 - 60Hz				
Operating Temperature Range: (Ta - Ambient)	- 20°C to 35°C				
Dimming:	Dali_(On Request)				
Colour Rendering Index:	CRI 80+				
Colour Consistency:	3-Step MacAdam				
Colour Temperature: (Kelvin / CCT)	○ 3000K ○ 4000K				
Beam Angle:	15° _ 67°				
Installation Type:	Recessed, Ceiling Mounted Luminaire				
Ingress Protection:	IP20				
Luminaire Colour:	○ White ● Black				
Material:	Body - Powder Coated Aluminium				
	Dimensions	Wattage (System)	CRI	Kelvin	Luminous Flux (Effective)
	Ø46mm x 35mm (Ø40mm Cut-Out)	1.9W	80+	3000K	95Lm*
	Ø46mm x 35mm (Ø40mm Cut-Out)	1.9W	80+	4000K	102Lm*

Dimensions:



^{*}E & O.E (Errors And Omissions Excepted)

 $^{^* \}textit{Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are}\\$ subject to change without prior notice.

^{*}All lumen outputs stated above are based a nominal output that included a 10% light loss, this can vary depending on the optic used.



Contact

Cape Town

1B Hansen Close, Richmond Park, Cape Town T. +27 21 555 0570

Durban

Unit L, Nandi Park, 34 Brickworks Way Briardene T. +27 31 001 2964

Namibia - Windhoek

Unit 2, Tesoro Building, 31 TV More Street Windhoek T. +264 61 40 0339

Johannesburg

17 Galaxy Road, Unit 5A Galaxy Park, Linbro Park T. +27 11 262 5179

Port Elizabeth

216 Main Road, Walmer Port Elizabeth T. +27 41 451 4359