











Features:

- Non-Maintained Operation
- Super Compact Plug & Play LED
- Optimised Lenses For Different Applications
- Manual, Self-Test Or Addressable Monitoring
- Self Contained Power Supply
- Dali Control (On Request)
- Minimum Lumen Maintenance: 50 000h (L90B10)



Power Supply:	220-240V AC 50 - 60Hz				
Emergency Duration:	3 Hours 100% Output				
Battery:	Lithium-Ion Phosphate				
Colour Rendering Index:	CRI 80+				
Colour Temperature: (Kelvin / CCT)	○ 6500K				
Lens Options:	• Anti Panic • Spot • Escape Route				
Installation Type:	Recessed				
Ingress Protection:	IP20				
IK Rating:	IK03				
Luminaire Colour:	White				
	Dimensions	Wattage (System)	CRI	Kelvin	Luminous Flux (Effective)
	Ø51mm x 94mm (Ø40mm Cut-Out)	2.5W	80+	6500K	200Lm*

^{*}Lumen Output Is Based On Emergency Operation.

Lens Options:






Escape Route (ER)



Dimensions:



^{*}E & O.E (Errors And Omissions Excepted)

^{*}Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.

^{*}All lumen outputs stated above are based a nominal output that included a 10% light loss, this can vary depending on the optic used.



Contact

Cape Town

1B Hansen Close, Richmond Park, Cape Town T. +27 21 555 0570

Durban

Unit L, Nandi Park, 34 Brickworks Way Briardene T. +27 31 001 2964

Namibia - Windhoek

Unit 2, Tesoro Building, 31 TV More Street Windhoek T. +264 61 40 0339

Johann esburg

17 Galaxy Road, Unit 5A Galaxy Park, Linbro Park T. +27 11 262 5179

Port Elizabeth

216 Main Road, Walmer Port Elizabeth T. +27 41 451 4359