

**PROSenPSS1**



FEATURES:

- Max 25 x 3 m
- IP20
- 10 - 1000 lux
- 10 - 1092 min
- Ideal 2,5 - 3,5 m


Ordering example: Product Name (e.g. PROSenPSS1)

Type	Radial	Detection angle	Angle of aperture	Optimum mounting height 2,8 m	Sensor Technology	HF-system
Presence detector	25 x 3 m (75 m <sup>2</sup> )	360 °	140 °	2,8 m	Sensor Technology	5,8 GHz


DETAIL:

KNX bus  
Indoors  
Ceiling  
Surface wiring

DETECTION AREA:



DIMENSIONS:



**PROSenPSS2**



FEATURES:

- High frequency sensor 360°
- Movement Ø 15 m
- Presence Ø 15 m
- True Presence Ø 9m
- Brightness
- Air humidity


Ordering example: Product Name (e.g. PROSenPSS2)

Type	Radial	Detection angle	Angle of aperture	Optimum mounting height 2,8 m	HF-system
Presence detector	Ø 15 m (177 m <sup>2</sup> )	360 °	160 °	2,8 m	7,2 GHz


DETAIL:

KNX bus  
Indoors  
Ceiling  
Concealed wiring

DETECTION AREA:



DIMENSIONS:



[Return to Contents Page](#)