SCC-1

25" Standard Controller Cabinet

The SCC-1 Standard Controller Cabinet is the smaller version of the modular electrical and wire management enclosure system for the TrolMaster HCS-2 and NFS-2 Control system.

The cabinet is designed to allow TrolMaster's HCS-2 and NFS-2 controllers to be installed in a clean and professional manner. A pre-cut opening allows the TrolMaster's main controller Hydro-X Pro (HCS-2) or Agua-X Pro (NFS-2) to be easily installed and provides a



professional and clean installation for your control system. All device stations can be mounted inside the IP56 rated electrical cabinet to keep the device stations clean and dry. Users can safely mount and neatly organize the power supplies, modules, and RJ12 cables with ease.

*Note: In order to achieve the IP56 standard, you must use the provided "controller rubber gasket" and perfectly fit the gasket between the controller and cabinet door.

Specifications

SCC-1

Power Input

Voltage	120V	
Max Amps	15A	

Working Environments

Ingress Protection	IP56
Temperature	32°F - 104°F / 0°C - 40°C

Cabinet Dimension and

6.26" / 159.1mm (L) x 18" / 457.2mm (W) x 25" / 635mm (H)

30.49 lbs / 13.83kg

Weight Size

Weight

Size

Packaging Dimensions and G.W.

10.43" / 265mm (L) x 21.65" / 550mm (W) x 28.35" / 720mm (H)


Weight 37.15 lbs / 16.85kg


Package Content

Controller Cabinet	1 pc
Controller Rubber Gasket	1 pc
Short RJ-12 Cables	16 pcs
Power Cables (for OA6 modules)	4 pcs
OA6-24 Screw Set	10 pcs
Installation Manual	1 pc

Cabinet Capacity

Splitter Board Group #1	10 ports (Top)
Splitter Board Group #2	6 ports (Top)
Splitter Board Group #3	17 ports (Top)
Splitter Board Group #4	2 x 4 ports (Detachable Splitter Bars) 2 ports (Device) 6 ports (Bottom)
Power Outlet	4+1+6





Email: support@trolmaster.com

Phone: 877-420-9876