



DANGER

May be corrossive to metals. Causes serious eye irritation. May damage fertility or the unborn child.

Obtain special instructions before use. Don not handle until all safety precautions have been read and understood. Keep only in original container. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses. if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention.

Absorb spillage to prevent material damage. Store in corrosive resistant container with a resistant inner liner.

▲ WARNING: This product can expose you to Ethylene Oxide, which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NFPA® RATINGS

Health: 2; Flammability: 1; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5; Organic acid salt mixture/HMIRA Registration Number 9207: Monocarbamide Dihydrogen Sulphate/21351-39-3; Linear Alcohol Ethoxylate/34398-01-1; Glycerin/56-81-5

For industrial and commercial use only.
For additional information, see Safety Data Sheet.



INDUSTRIAL CLEANERS and DEGREASERS

D.P.C

Acid Replacement with Acid Perfomance

•REPLACES HYDROFLOURIC AND SULPHURIC ACIDS

•CLEANS AND BRIGHTENS CORRODED AND OXIDIZED ALUMINIUM

•REMOVES DUST, GREASE, AND OXIDATION FROM COILS

DOT NON-REGULATED

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

DESCRIPTION: This heavy-duty acid replacement product has the performance of hydrofluoric and sulfuric acids, but is non-corrosive to skin, making it far safer to users. It is DOT non-regulated, and no EPCRA risk management plan filing is required. Contains no phosphorous.

As aluminium cleaner and brighter, it has outstanding calcium, limescale and silicate-deposit removal properties. It quickly removes corrosion and oxidation, leaving surfaces bright and clean it is ideal for use on aluminium trailer bodies, boats, building materials and most other exterior aluminium surfaces.

As a coil cleaner, it removes dust, dirt, grime, grease and oxidation from aluminium or copper coils as well as fans of cooling units and air conditioners. use it regularly to clean coils for more effient operation and lower power consumption.

DIRECTIONS: ALWAYS TEST IN AN INCONSPICUOUS AREA BEFORE USING THIS PRODUCT. Wear rubber gloves and googles when handling. Use full strength for heavy duty cleaning. May be diluted with up to 5 parts water for maintenance or light cleaning and brightening. Brush, spray, or swab onto the surface to be cleaned, allow to penetrate soils, then rinse thoroughly with clean water. Use with care on painted surfaces.

Use palstic pails for diluting and dispose of excess solution immediately after use.

Do not use on anodized aluminum.

DISPOSAL:

Dispose of contents/container to comply with local/regional/national/international regulations.



ycle. 0104.091621