

Graffiti X

Safety Data Sheet

SECTION 1: Product and company identification

Product name : Graffiti X
Use of the substance/mixture : Graffiti remover
Product code : 8307
Company : Metropolitan Compounds
3343 N University Drive
Hollywood, FL 33024 - USA
T (855) 474-6781
Emergency number : Chemtec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Gas 1 H220
Flam. Aerosol 1 H222
Skin Irrit. 2 H315
Eye Irrit. 2A H319
Repr. 2 H361
STOT SE 3 H336
STOT RE 2 H373
Asp. Tox. 1 H304

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Extremely flammable gas
Extremely flammable aerosol
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
May cause drowsiness or dizziness
Suspected of damaging fertility or the unborn child
May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Keep away from heat, hot surfaces, open flames, sparks. - No smoking
Do not spray on an open flame or other ignition source
Pressurized container: Do not pierce or burn, even after use
Do not breathe gas
Avoid breathing gas
Wash thoroughly after handling
Use only outdoors or in a well-ventilated area
Wear protective gloves, protective clothing, eye protection, face protection
If swallowed: Immediately call a doctor, a POISON CENTER
If on skin: Wash with plenty of water
If inhaled: Remove person to fresh air and keep comfortable for breathing
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If exposed or concerned: Get medical advice/attention
Call a doctor, a POISON CENTER if you feel unwell
Get medical advice/attention if you feel unwell
Specific treatment (see first aid on this label)
Do NOT induce vomiting
If skin irritation occurs: Get medical advice/attention
If eye irritation persists: Get medical advice/attention
Take off contaminated clothing and wash it before reuse
Leaking gas fire: Do not extinguish, unless leak can be stopped safely
Eliminate all ignition sources if safe to do so
Store in a well-ventilated place
Store in a well-ventilated place. Keep container tightly closed

Graffiti X

Safety Data Sheet

Store locked up
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	GHS-US classification
toluene	(CAS No) 108-88-3	20 - 40	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
butane	(CAS No) 106-97-8	2.5 - 10	Flam. Gas 1, H220 Compressed gas, H280
propane	(CAS No) 74-98-6	2.5 - 10	Flam. Gas 1, H220 Compressed gas, H280
Glycol Ether EB	(CAS No) 111-76-2	2.5 - 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Asp. Tox. 1, H304
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	(CAS No) 112-34-5	2.5 - 10	Eye Irrit. 2A, H319
acetone, propan-2-one, propanone	(CAS No) 67-64-1	2.5 - 10	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
OLEIC ACID	(CAS No) 112-80-1	1 - 2.5	Not classified
sodium hydroxide	(CAS No) 1310-73-2	0.1 - 1	Met. Corr. 1, H290 Skin Corr. 1A, H314

A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If breathing is difficult, give oxygen. Get immediate medical attention. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. show this sheet where possible. Keep watching the victim. Keep victim warm and rested.
- First-aid measures after inhalation : Remove the victim into fresh air. Artificial respiration and/or oxygen if necessary. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : Wash with water and soap. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse with water. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth with water. Get medical attention immediately if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause drowsiness or dizziness. Headache. nausea, vomiting. Irritation to throat. Irritation of the nasal mucous membranes. Aspiration may cause pulmonary edema and pneumonitis. Causes serious eye irritation. Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Keep watching the victim. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : May liberate toxic gases. Extremely flammable aerosol.
- Explosion hazard : Contents under pressure. Contains gas under pressure; may explode if heated.
- Reactivity : Reacts violently with strong acids. This product may react with oxidizing agents.

Graffiti X

Safety Data Sheet

5.3. Advice for firefighters

Firefighting instructions : In case of fire and/or explosion do not breathe fumes. Move containers away from the fire area if this can be done without risk. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Cool tanks/drums with water spray/remove them into safety.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Special attention should be given to low areas/pits where flammable vapors can accumulate. Stay upwind/keep distance from source.

6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment.
Emergency procedures : Ventilate spillage area. DO NOT touch spilled material. Advice local authorities if considered necessary.

6.1.2. For emergency responders

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Do not allow to enter drains or water courses. Prevent entry to sewers and public waters. Avoid release to the environment. Advice local authorities if considered necessary.

6.3. Methods and material for containment and cleaning up

For containment : Eliminate every possible source of ignition. NO open flames, NO sparks, and NO smoking. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if safe to do so. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent the product from entering drains or confined areas.
Methods for cleaning up : Clean contaminated surfaces with a soap solution. Take up liquid spill into absorbent material. Dispose as hazardous waste.

6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection. For further information refer to section 8 Exposure controls/personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective.
Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not spray on a naked flame or any incandescent material. Do not smoke while handling product. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. . Ground/bond container and receiving equipment. Do not breathe gas. Do not eat, drink or smoke when using this product. Avoid prolonged and repeated contact with skin. Wear recommended personal protective equipment. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling.
Hygiene measures : Use good personal hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pressurized container. Do not puncture, incinerate or crush. Take precautionary measures against static discharge. Must not come into contact with food or be consumed.
Storage conditions : Store locked up. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Refrigerate.
Incompatible products : acids. Strong oxidizing agents. Oxidizing agent. Nitrates. fluorine. Chlorine.
Incompatible materials : Heat sources. Open flame. Keep away from any possible contact with water, because of violent reaction and possible flash fire.
Storage area : Aerosol 2.
Special rules on packaging : meet the legal requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butane (106-97-8)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
ACGIH	ACGIH STEL (ppm)	1000 ppm

Graffiti X

Safety Data Sheet

propane (74-98-6)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
toluene (108-88-3)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Visual impair; female repro;
OSHA	Remark (OSHA)	(2) See Table Z-2.
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether (112-34-5)		
ACGIH	ACGIH TWA (ppm)	10 ppm
Glycol Ether EB (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
acetone, propan-2-one, propanone (67-64-1)		
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI
OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. . If exposure limits have not been established, maintain airborne levels to an acceptable level.
- Personal protective equipment : Use appropriate personal protective equipment when risk assessment indicates this is necessary. Protective goggles. Gloves. Protective clothing. apron.



- Hand protection : Gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear chemical protective equipment that is specifically recommended by the manufacturer. Use of an impervious apron is recommended. It may provide little or no thermal protection.
- Respiratory protection : If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
- Thermal hazard protection : Use appropriate personal protective equipment when risk assessment indicates this is necessary.
- Consumer exposure controls : Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Avoid contact with eyes, skin and clothing. Keep away from food and drink. When using do not smoke. Use good personal hygiene practices. Take off contaminated clothing and wash it before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Gas
- Appearance : Aerosol. Tan.
- Odor : Solvent-like odor
- Odor threshold : No data available
- pH : 12.5 - 13.4
- Melting point : No data available
- Freezing point : No data available

Graffiti X

Safety Data Sheet

Boiling point	: 193.64 °F Estimated
Flash point	: -156 °F Estimated
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.765 g/ml Estimated
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts violently with strong acids. This product may react with oxidizing agents.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

Heat. No flames, No sparks. Eliminate all sources of ignition. Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point.

10.5. Incompatible materials

Do not mix with other chemicals. Strong oxidizing agents. Nitrates. Fluorine. Caustic products. Chlorine.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Glycol Ether EB (111-76-2)	
LD50 oral rat	1300 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE CLP (oral)	1300.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h

sodium hydroxide (1310-73-2)	
LD50 oral rat	>= ml/kg

Skin corrosion/irritation : Causes skin irritation.
pH: 12.5 - 13.4

Serious eye damage/irritation : Causes serious eye irritation.
pH: 12.5 - 13.4

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

toluene (108-88-3)	
IARC group	3 - Not Classifiable

Graffiti X

Safety Data Sheet

Glycol Ether EB (111-76-2)	
IARC group	3 - Not Classifiable

Reproductive toxicity : Suspected of damaging fertility or the unborn child.
 Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.
 Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.

Glycol Ether EB (111-76-2)	
NOAEL (oral,rat,90 days)	see comments
NOAEL (dermal,rat/rabbit,90 days)	see comments

Aspiration hazard : May be fatal if swallowed and enters airways.
 Likely routes of exposure : Skin and eyes contact;Inhalation;Ingestion

SECTION 12: Ecological information

12.1. Toxicity

Glycol Ether EB (111-76-2)	
LC50 fish 1	1474 mg/l Oncorhynchus mykiss
EC50 Daphnia 1	100 mg/l Water flea
ErC50 (algae)	1840 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	> 100 mg/l
NOEC chronic crustacea	100 mg/l daphnid

12.2. Persistence and degradability

sodium hydroxide (1310-73-2)	
Persistence and degradability	Biodegradability: not applicable. No test data on mobility of the components available.

12.3. Bioaccumulative potential

sodium hydroxide (1310-73-2)	
Bioaccumulative potential	Does not contain bioaccumulative component(s).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container to comply with local/regional/national/international regulations.
 Additional information : Do not re-use empty containers. Handle unclean empty containers as full ones.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1
 UN-No.(DOT) : UN1950
 Proper Shipping Name (DOT) : Aerosols
 flammable, (each not exceeding 1 L capacity)
 Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
 Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None
 DOT Packaging Bulk (49 CFR 173.xxx) : None
 DOT Special Provisions (49 CFR 172.102) : N82
 DOT Packaging Exceptions (49 CFR 173.xxx) : 306
 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
 DOT Vessel Stowage Location : A

Graffiti X

Safety Data Sheet

DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.306.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : UN1950
 Proper Shipping Name (IMDG) : Aerosols
 Class (IMDG) : 2.1 - Flammable gases

Air transport

UN-No. (IATA) : UN1950
 Proper Shipping Name (IATA) : Aerosols, flammable, containing substances in Division 6.1, Packing Group III
 Class (IATA) : 2.1 - Gases : Flammable

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Toluene	CAS No 108-88-3	20 - 40%
Glycol Ether EB	CAS No 111-76-2	2.5 - 10%
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether butane (106-97-8)	CAS No 112-34-5	2.5 - 10%
Not listed on SARA Section 313 (Specific toxic chemical listings)		
propane (74-98-6)		
Not listed on SARA Section 313 (Specific toxic chemical listings)		
toluene (108-88-3)		
Listed on SARA Section 313 (Specific toxic chemical listings)		
CERCLA RQ	1000 lb	
sodium hydroxide (1310-73-2)		
Not listed on SARA Section 313 (Specific toxic chemical listings)		
CERCLA RQ	1000 lb	
acetone, propan-2-one, propanone (67-64-1)		
Not listed on SARA Section 313 (Specific toxic chemical listings)		
CERCLA RQ	5000 lb	

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H290	May be corrosive to metals
H302	Harmful if swallowed

Graffiti X


Safety Data Sheet

H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.