



DESCRIPTION

This heavy duty drain opener contains caustic granules activated by aluminum needles that release substantially more intense heat and turbulence than our regular strength drain opener.

The heat and movement liquefy, dissolve and remove a variety of clogging material such as hair, paper, animal and vegetable fats and oils, as well as other organic matter that clog drains and sewer lines.

Keep away from open flames. - No smoking. Keep/Store away from clothing, combustible materials. Take any precaution to avoid mixing with acids, reducing agents, water. Product will generate large amounts of heat when wetted. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Do not breathe dust. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves. Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a doctor, POISON CENTER if you feel unwell.

In case of fire: Use foam, dry extinguishing powder, carbon dioxide (CO₂) to extinguish.

WARNING: This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

RED HOT

Heavy Duty Activated Alkaline Drain Opener

DANGER

May intensify fire; oxidizer.

Causes severe skin burns and eye damage.

May cause respiratory irritation.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: □25 lbs. □55 lbs.

Reorder From:



DIRECTIONS

For Municipal Sewer Lines:

Pour or shovel 20 pounds of product into strategic manholes. If sewer system is dry, flush product with plenty of water.

For Industrial Drains:

Pour 1-2 pounds of product down drain. Where the accumulations of grease and organic matter are high, pour 3-5 pounds of product down drain.

**BE AWARE

- Generates heat that may cause hazardous liquids to erupt.
- Place a deep container over treated drain.
- Never use a plunger with this product.
- Never look directly into a treated drain.
- Never use with or immediately after acid-type drain openers.
- Never enter treated sewers until thoroughly flushed with water.

DISPOSAL

Dispose of contents/container to comply with local/regional/national/international regulations.

NFPA® RATINGS

Health: 3; Flammability: 0; Reactivity: 2; Special: ~~W~~

CONTAINS/CAS NUMBER:

Sodium Hydroxide/1310-73-2; Sodium Nitrate/7631-99-4; Aluminum Metal/7429-90-5; Sodium Chloride/7647-14-5; Dye/Mixture.



Please Recycle.

0618.012715