

# SLICKSTER

Saves production, maintenance, and repair time. Protects and preserves equipment. Spray on, let set and the fast-acting, penetrating formula goes to work. It loosens the rust or corrosion, making it easy to separate the surfaces. For use on refrigerator equipment, automobiles, work-shops. Free nuts and bolts. Lubricates locks, hinges, moving parts. Stops and retards corrosion. Stops corrosion on battery terminals.

LOOSENS UP RUSTED NUTS & BOLTS

PREVENT FUTURE RUST & CORROSION

SAFE FOR ALL METAL & ELECTRICAL  
COMPONENTS

## DIRECTIONS

Remove cap and point valve opening toward surface to be sprayed. Hold can 4-8 inches away, push button and spray. For stubborn cases, repeat the spray and allow to set for a few minutes.

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

**FIRST AID:IF SWALLOWED:** Immediately call a poison center/doctor. Do NOT induce vomiting.

**IF ON SKIN:** Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

**IF IN EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

**IF INHALED:** Move to fresh air. Call a physician if symptoms



**METROPOLITAN COMPOUNDS**