

AEV®

ZOLL®



Ventilation
Made Easy

Ventilation Made Easy

Full Patient Range

For patients from infant (≥ 5 kg) through adult

Smart Help™ Display

Guides operator through on-screen commands when responding to alarms

Calculates Oxygen Usage

Calculates oxygen use in liters per minute to help manage the logistics of patient transportation

Intuitive Design

User-friendly, straight-forward interface

Unprecedented Battery Run-Time

No additional battery back-up needed thanks to 10-hour battery run-time. Battery recharges to 90% in 2 hours.

Rugged, All-Weather Device

Under 10 lbs (4.5 kg) yet rugged. Originally designed for the unique needs of the military to handle austere environments.

ZOLL Medical Corporation
Worldwide Headquarters
269 Mill Road
Chelmsford, MA 01824
978-421-9655
800-804-4356

For subsidiary addresses and fax numbers, as well as other global locations, please go to www.zoll.com/contacts.

AEV® Specifications

Clinical Specifications

Product Family: Part of the 731 Series

Operating Modes: AC, CPAP NPPV with or without pressure support

Breath Target: Volume and pressure

Flow Rate: 0 to 100 LPM @ 40 cm H₂O (3922 Pa)

Breath Rate: 1 to 60 BPM

Tidal Volume: 50 to 1500 ml ATPD +/- 10% of setting

Inspiratory Time: 0.3 to 3.0 seconds

I:E Ratio: 1:1 to 1:99.9

FiO₂: 21 to 100% +/- 3% of full scale +/- 10% of setting

PEEP: 0 to 25 cm H₂O (0 to 2451 Pa)

Peak Inspiratory Pressure (PIP): 10 to 80 cm H₂O (980 to 7845 Pa)

Trigger Sensitivity: -0.5 to -6.0 cm H₂O (-49 to -588 Pa)

Oxygen Input Pressure: 55 psig (-25%; + 20%) (379170 Pa)

Environmental

Operating Voltages: 100 to 240 VAC (50/60 Hz) or 12.5 to 28.0 VDC

Operating Time: Internal Battery 10 hours

Temperature Ranges:

Operating: -25° to 49°C (-13 to 120°F) with battery charging, battery discharge and AC power operation

Battery Charging: 0° to 45°C (32° to 113°F)

Long-Term Storage: -15° to 21°C (5° to 71°F) Optimal storage conditions

Altitude Compensation:

-2,000 to 25,000 ft. (609.6 to 7,620 meters)

Safety Specifications

Airway Pressure High Limit: 20 to 100 cm H₂O values (1961 to 9806 Pa)

Airway Pressure Low Limit: Off, 3 to 35 cm H₂O (294 to 3432 Pa)

BPM High Alarm Limit: Off, 2 to 60

BPM Low Alarm Limit: 2 to 40

LED Status/Alarm Indicator: Red, yellow, and green

General

Size: 8.0" wide x 12.5" high x 4.5" deep (20.3 cm wide x 31.8 cm high x 11.4 cm deep)

Weight: 9.7 lbs (4.4 kg)

