## MPACT® MODEL 73X SPECIFICATIONS

**OPERATING MODES** 

OXYGEN: Control, Assist/Control COMPRESSOR: Control, Assist/Control

FLOW RATE: 30 LPM, constant flow

BREATHING RATE: Adjustable, 10, 12, 14, 16, 18, 20 BPM

TIDAL VOLUME: 300 to 1000 ml, ATPD

INSPIRATORY TIME: Variable based on selected BREATHING RATE and TIDAL VOLUME

FiO<sub>2</sub>: 21% using ambient air or 100% with external oxygen source

O<sub>2</sub> Input Pressure: 55 PSI (-25%; + 20%)

AIRWAY PRESSURE LIMIT: Adjustable, 15 to 80 cmH<sub>2</sub>O

MAXIMUM AIRWAY PRESSURE: 80 cm H<sub>2</sub>O using AIRWAY PRESSURE LIMIT/ALARM, 100 cm H<sub>2</sub>O

mechanical backup

BREATH TRIGGER: -2.0 cmH<sub>2</sub>O

LED BAR GRAPH: Pressure Range: -2 to 90 cmH<sub>2</sub>O

**Battery Capacity Range: Green/Yellow/Red** 

LED ALARM INDICATORS: Ext Power Low/Fail, Low Battery, Low Oxygen, Vt Setting,

**Patient Disconnect, High Airway Pressure and System Failure** 

ALARM MUTE: Yes, 30-seconds

ALARM VOLUME: 85 dBA @ 1 ft

NOISE LEVEL: Less than 75 dBA when measured @ 1-meter (compressor

modes)

OPERATING VOLTAGE: 12 VDC (nominal)

**OPERATING TIME** 

INTERNAL BATTERIES: Compressor: approximately 6 hours @ average adult settings

Oxygen: approximately 12 hours @ average adult settings Continuous (from AC-DC converter or automotive power source)

**TEMPERATURE RANGES** 

**EXTERNAL 12 V:** 

OPERATING: -25° C to 49° C (-13° F to 120° F)
CHARGING: 0° C to 40° C (32° F to 104° F)
LONG TERM STORAGE: 10° C to 30° C (50° F to 86° F)

**ENCLOSURE:** Polycarbonate with clear door

**Battery compartment accessible without tools** 

**SIZE** 

**VENTILATION SYSTEM:** 8.87" Wide x 11.5" High x 4.5" Deep

22.55 cm Wide x 29.21 cm High x 11.43 cm Deep

AC POWER SUPPLY (supplied): 2.38" Wide x 5.23" High x 1.60" Deep

6.05 cm Wide x 13.28 cm High x 4.06 cm Deep

<u>WEIGHT</u>

VENTILATOR: 11 lbs

4.54 Kg

COMPLETE KIT: 13.2 lbs

5.99 Kg

KIT CONTENTS: Ventilator, AC-DC Power Supply, 12 VDC Automotive Power

Cable, Ventilator Circuit, Padded Case, (2) Fuses, 6' Oxygen Hose,

Operation Manual (on CD), Fresh Gas/Emergency Air Intake

Filter, AC Power Cord

WARRANTY: Limited, 1-year (see LIMITED WARRANTY statement)

<u>Note:</u> Impact Instrumentation, Inc. reserves the right to change these specifications without prior notification.

p/n 929-073x-00 Rev A Updated 10/11