

MATERIAL SAFETY DATA SHEET



PROSOCO, Inc.

I PRODUCT IDENTIFICATION

MANUFACTURER'S NAME AND ADDRESS: PROSOCO, Inc.
3741 Greenway Circle
Lawrence, KS 66046

EMERGENCY TELEPHONE NUMBERS:
8:00 AM – 5:00 PM CST Monday-Friday: 785/865-4200
NON-BUSINESS HOURS (INFOTRAC): 800/535-5053

PRODUCT TRADE NAME: Stand Off® Color Enhancer WB

HMIS Profile: Health 1 Flammability: 0 Reactivity: 0

II HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS NO.	ACGIH TLV/TWA	OSHA PEL/TWA
Not classified as a hazardous chemical as defined in OSHA 1910.1200 Appendix A.	*	NE	NE

III TYPICAL PHYSICAL DATA

	SPECIFIC GRAVITY	SOLUBILITY IN WATER	APPEARANCE AND ODOR
Color Enhancer WB	1.00	Yes	Milky white liquid, slight odor

IV FIRE AND EXPLOSION HAZARD DATA

EMERGENCY OVERVIEW

Stand Off® Color Enhancer WB is a milky white liquid. Contact with the eyes or prolonged contact with skin may result in reversible irritation. Mist inhalation may cause irritation. Always wear appropriate personal protective equipment when using this product.

FLASH POINT (METHOD): >212°F (ASTM D 3278)

FLAMMABLE LIMITS: Not determined

EXTINGUISHING MEDIA: Use dry chemical, foam or water spray.

SPECIAL FIRE FIGHTING PROCEDURES: None.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None. Burning may produce toxic vapors, carbon dioxide, carbon monoxide and nitrous oxides.

V HEALTH HAZARD DATA

PRIMARY ROUTES OF EXPOSURE: Skin, eyes, ingestion, inhalation.

CARCINOGEN INFORMATION: Not listed (OSHA, IARC, NTP).

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: No applicable information found.

EFFECTS OF OVEREXPOSURE: Irritation of the eyes or skin.

EYE CONTACT: Direct contact may cause moderate irritation.

SKIN CONTACT: Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis.

INHALATION: Exposure to high vapor concentrations may cause eye and respiratory tract irritation, headache, dizziness, nausea, drowsiness and loss of consciousness.

INGESTION: Although ingestion is unlikely, liquid would irritate upper digestive tract if swallowed.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: If in eyes, flush with large amounts of water for 15 minutes, holding eyelids apart to ensure flushing of the entire eye surface. Get medical attention.

SKIN CONTACT: Wash exposed area with soap and water. Remove contaminated clothing. If persistent irritation occurs, get medical attention. Launder contaminated clothing before reuse.

INHALATION: No respiratory effects anticipated. Remove to fresh air. Get medical attention if ill effects persist.

INGESTION: Get immediate medical attention. If vomiting occurs, keep head below hips to prevent liquid from entering lungs. Never give anything by mouth to an unconscious person.

VI REACTIVITY DATA

STABILITY: Stable.

CONDITIONS TO AVOID: None.

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with strong oxidizing agents and acids. Aluminum at high temperatures.

HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS: Combustion may produce CO₂, CO and nitrous oxides.

VII SPILL OR LEAK PROCEDURES

SPILL, LEAK, WASTE DISPOSAL PROCEDURES: Wear appropriate protective safety equipment. Floors may be slippery; care should be exercised to avoid falls. Contain and keep from sewers and surface waters.

WASTE DISPOSAL METHODS: Dispose of in accordance with federal, state and district regulations. This material as supplied is not classified as a hazardous waste by USEPA RECRA criteria. Federal regulation prohibits disposal of liquid materials of any kind in a sanitary landfill. Solidify cleanup residuals before disposal. As local and state regulations may vary, consult with appropriate state and local regulatory agencies or the sanitary landfill operator to ascertain proper disposal procedures.

Empty containers must not be reused. Drain all liquid possible from the container before disposal in a sanitary landfill.

VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear a NIOSH approved dust/mist respirator as necessary to avoid unnecessary inhalation of wind drift during application. Ventilate interior spaces during curing as minute quantities of ethanol may be evolved.

VENTILATION: No special ventilation required.

PROTECTIVE CLOTHING: Wear protective clothing such as long sleeved work shirt and pants, work boots, and rubber gloves as needed to avoid prolonged skin contact. Do not allow clothing to become saturated with product. If work practices cannot be adjusted to avoid excess clothing saturation, splash resistant or Tyvek clothing and boots may be required.

PROTECTIVE GLOVES: Chemically resistant gloves such as nitrile, rubber, or PVC may be used to avoid prolonged skin contact..

EYE PROTECTION: Safety glasses with side shields are recommended. Splash resistant goggles or a face shield should be used prevent eye contact where wind-drift and excess atomization can pose a risk

OTHER PROTECTIVE EQUIPMENT: Access to a fixed or portable eyewash is recommended.

IX SPECIAL PRECAUTIONS

WORK PRACTICES: Proper work practices and planning should be utilized to avoid contact with workers, passersby, and non-masonry surfaces. Do not atomize during application. Beware of wind drift. See the Product Data sheet and label for specific precautions to be taken during use. Wash hands before breaks and at the end of a shift.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Store in a cool, dry, well-ventilated place. Keep containers tightly closed when not dispensing product. **Keep from freezing.** Use care around spilled material because it will be slippery.

OTHER PRECAUTIONS: None known.

X REGULATORY INFORMATION

SHIPPING: This product is not regulated for domestic or international shipment.

SARA 313 REPORTABLE:

CHEMICAL NAME	CAS	UPPERBOUND CONCENTRATION % BY WEIGHT
NA	NA	NA

CALIFORNIA PROPOSITION 65: No listed materials are known to be present in this product.

HMIS: 1,0,0,X

XI OTHER

MSDS Status: **Date of Revision:** May 1, 2007
For Product Manufactured After: May 1, 2007
Changes: New Product
Item #: 55108
Approved By: Regulatory Department

DISCLAIMER:

The information contained on the Material Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. **PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described.** This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

DATE OF PREPARATION: May 1, 2007