

Sure-Chek® Privacy Curtains

Cubicle and Shower

Specifications

General Fabrication Specifications

Top hems to be 1 1/2" wide, triple thickness double lock stitched or pre-woven to finish at 1 1/2". Traditional privacy curtains will include a 1 1/2" wide double thickness double lock stitched bottom hem. Shower curtains fabricated with Sure-Chek fabric shall not include a bottom hem. Side hems shall be 3/4" wide turned and single lock stitched. Seams to be 1/2" wide double turned and double lock stiched. When possible curtains will be railroaded to avoid vertical seams. Points of stress are reinforced, assuring a top quality product that will provide years of outstandingservice.

Rustproof aluminum grommets are machined into the top hem 6" O.C.



Curtains are available with #50 mesh (1/2" hole) flame resistant nylon mesh. Available in 6 colors. The nylon mesh is double lock stitched to top of curtain fabric with a 1/2" wide triple thick top seam. The mesh also has a 1 1/4" 100% polyester tape double lock stitched into the top hem for secure machining of grommets (unless pre-woven). All curtains are inspected for workmanship.

Curtain Drops

If mesh cannot be used, Imperial offers stainless steel drop chains in 6", 9", 12", 15" and 18" lengths. PVC curtain drops are also available with hooks of any length.

100% F/R Vinyl

Curtains to be 100% F/R vinyl with filament reinforcement, permanently and inherently flame resistant for the life of fabric. Sure-Chek is extremely durable, self-deodorizing, fluid-proof, anti-microbial and tear resistant.

Sure-Chek fabric meets NFPA 701, California Fire Marshall title 19, City of Boston Chapter 3.

Available with a Variety of Mesh Colors White Blue Bone Green Peach Rose


Available in 12 Colors

Imperial offers the largest selection of in-stock Sure-Chek colors.



Reinforced Mesh Borders

Standard mesh height is 20". Mesh heights up to 45" are available upon request. Edges of mesh are reinforced with 1/2" polyester tape to ensure long-term strength and durability.



QUESTIONS? CONTACT US info@imperialprivacy.com