

The regeneration process should be conducted every <u>12-18 months</u> depending on household size and daily usage. This process regenerates the contaminated CATALYTIC CARBON® and re-activates it up to 99%. Consistent and timely regeneration prolongs the life of your HydroCare™ system and insures optimum performance. Listed below are:

- 1. Avoid contact with eyes and skin. Wear gloves and eye protection
- 2. Store in cool dry place. Harmful if swallowed
- 3. Keep container sealed and dry



CATALYTIC CARBON® is re-activated and is like brand new by following these steps.

## Mix the solution

- 1. Open the package of regeneration mix and pour contents into the one gallon jug.
- 2. Slowly add water to fill the jug leaving approximately 2 inches from the top.
- 3. Gently shake the contents for 2-3 minutes.
- 4. Let the contents sit for 10 minutes before adding to tank. Gently shake before adding to tank.

## **Regeneration Process**

- 1. Turn off the water supply to the tank.
- 2. Open a nearby faucet to relieve pressure in the plumbing system.
- 3. Slowly unscrew the 2" access port on top of the tank. <u>Be careful as there still may be pressure build-up</u> and water may spill.
- 4. If necessary, withdraw enough water from the tank using the siphon pump provided with your initial order to ensure that the 1 gallon solution can be safely added back in.
- Slowly pour the mixed contents into the tank and re-install the access port.
   Do not use a wrench- this must be firmly tightened by hand.
   Turn the water back on to the supply tank.
- 6. ALLOW CONTENTS TO SIT IN THE TANK FOR 30-45 MINUTES BEFORE PROCEEDING TO NEXT STEP.
- 7. Press and hold the regeneration button for 5 seconds to initiate the Backwash and Fast Rinse process.

  When complete, the system will automatically go back to normal service mode and the display will show the current time as indicated by faucet symbol in the upper left of the digital display.

