



## LIQUID WAX CLEANER

Cleans and refreshes in one step!



3029 Clear



3087 White



1 APPLICATION

### Product description:

Clear or transparent wax-based care product for occasionally refreshing interior wooden flooring treated with Polyx®-Oil, furniture as well as other interior oiled and waxed wood surfaces. Through appropriate care, the surface is provided with the natural, safe hard waxes. The floor stays hard-wearing without forming a film.

### Recommended use:

Osmo Liquid Wax Cleaner is ideal for removing tough stains, e.g. grease or shoe polish, and best suited for refreshing all surfaces treated with Osmo Polyx®-Oil.

### Ingredients:

Based on natural plant waxes; paraffin, aliphatic hydrocarbons (>30%). Detailed declaration of ingredients available upon request.

### Technical Data:

Specific gravity: 0.77-0.8 g/cm<sup>3</sup>  
Viscosity: >30s DIN EN ISO 2431/3 mm, viscid  
Odour: faint/mild, odourless after drying  
Flashpoint: > 60 °C, acc. DIN EN ISO 2719  
pH value: not required

### Storage:

5 years and longer if stored in the closed original can. If thickened by frost, store at room temperature for 24 hours prior to use.

### Surface Preparation:

Wood surface must be dust-free and dry. A dust mop, a mop or a vacuum cleaner is usually suitable for removing dust. For simple cleaning and upkeep, Osmo Cleaning Kit for Floors (Dust-Mop, Micro-Mop Plush and an Active Fibre Cloth) is highly recommended. High traffic and high wear floor surfaces, for example commercial interiors, should first be cleaned with a damp mop (water with Osmo Wash and Care).

### Methods of Application:

Manual application: For removing stains and intensive maintenance, please use Osmo Liquid Wax Cleaner together with Osmo Active Fibre Cloth (approx. 2 teaspoons per sq m). Rub away especially tough stains with Osmo Liquid Wax Cleaner with a cloth or a scouring pad. Machine application: Apply Osmo Liquid Wax Cleaner with a single disc machine and a white pad (approx. 2 teaspoons per sq m). Spread Osmo Liquid Wax Cleaner evenly on the surface and buff in. If streaks appear, turn pad over or replace with a new pad. For more information, see FloorXcenter description. For more sheen, polish the dried surface with a white pad.

### Cleaning of tools:

With Osmo Brush Cleaner (free of aromatic compounds).



#### Drying time:

Approx. 30-40 minutes (normal climatic conditions, 23 °C/50 % rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times.

#### Coverage:

Product coverage of Osmo Liquid Wax Cleaner strongly depends on the absorption and on the level of contamination on the substrate. (1 litre of care product covers approx. 80-100 m<sup>2</sup>, 2 teaspoons for approx. 1 m<sup>2</sup>).

#### Note:

By applying hard waxes regularly, flooring stays refreshed and stain and wear resistance is improved. However over the years, it is absolutely essential to re-apply the necessary oil ingredients in Polyx®-Oil to flooring. Only use very sparingly otherwise traffic marks may appear. Use Osmo Liquid Wax Cleaner White only on white substrates. On especially high traffic areas, refinish the cleaned area with Osmo Polyx®-Oil.

#### Caution:

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Repeated exposure may cause skin dryness or cracking. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Safety data sheet available on request.

#### Disposal:

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 12). Only completely emptied cans can be recycled.

#### Colour tone:

3029 Clear  
3087 White

#### Size:

Liquid Wax Cleaner: 0.5 l; 1 l; 10 l  
Liquid Wax Cleaner White: 0.5 l; 1 l

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 09/20