

# Crosby RIGGING HARDWARE

## Crosby WIRE ROPE CLIPS



SIZE		EFFICIENCY	NUMBER OF CLIPS	TURNBACK LENGTH MM	TORQUE Nm
INCH	MM				
1/8	3 - 4	80%	2	85	6.1
3/16	5	80%	2	95	10.2
1/4	6 - 7	80%	2	120	20.3
5/16	8	80%	2	133	40.7
3/8	9 - 10	80%	2	165	61
7/16	11	80%	2	178	88
1/2	12 - 13	80%	3	292	88
9/16	14 - 15	80%	3	305	129
5/8	16	80%	3	305	129
3/4	18 - 20	80%	4	460	176
7/8	22	80%	4	480	305
1	24 - 26	90%	5	660	305

\*APPLY U-BOLT OVER DEAD END OF THE WIRE ROPE, LIVE END OF THE ROPE RESTS IN THE SADDLE; NEVER SADDLE A DEAD HORSE!

-USE THE RECOMMENDED NUMBER OF CLIPS AND APPLY THE RECOMMENDED TORQUE AS SPECIFIED IN THE TABLE.

\*A TERMINATION IS ONLY FINISHED WHEN IT HAS BEEN LOADED AT THE REQUIRED WILL AND THE NUTS HAVE BEEN RETORQUED A SECOND TIME.



## Crosby TURNBUCKLES

SIZE	WLL (t) JAW AND EYE D.F. 5/1	WLL (t) HOOK END FITTING D.F. 5/1
1/4	230	180
5/16	360	320
3/8	540	450
1/2	1,000	680
5/8	1,590	1,020
3/4	2,360	1,360
7/8	3,270	1,810
1	4,540	2,270
1-1/4	6,890	-
1-1/2	9,710	-
1-3/4	12,700	-
2	16,780	-

THE USE OF LOCKNUTS OR MOUSING IS AN EFFECTIVE METHOD OF PREVENTING TURNBUCKLES FROM ROTATING.



REFER TO THE Crosby CATALOG FOR ADDITIONAL INFORMATION