COMPOZITE ELITE DAVIT CRANE





Individually tested and certified at 125%



OZPED2 base shown Bases and cable assemblies sold separately weighs only

1200 lbs. Capacity (OZCF1200DAV)


- Carbon fiber / High-strength aluminum construction
- Manual Din rated CE winch with brake (Includes power drill adaptor)
- Synthetic Cable Assembly Available
- Headache Ball (OZHB10) available and sold separately
- Carrying case (OZRB1) available and sold separately

Load Ratings (lbs.)

*OZCF1200DAV based on 1/4" wire rope

	1st. Layer	Mid. Drum	Full Drum
Position 1 (0°)	500	500	500
Position 2 (+22.5°)	700	700	550
Position 3 (+45°)	1200	875	550

Introducing the world's most innovative davit cranes. Utilizing carbon fiber our CompOZite Elite Davit Cranes are pound for pound the lightest and strongest in the market.



Position 1, Height 46", Reach 42" Position 2, Height 62", Reach 36" Position 3, Height 74", Reach 24"

*Dimensions are for reference only and subject to change without notice.















Steel Wire Rope (For manual winch)

OZGAL.19-80B	3/16" x 80'	Galvanized cable assembly
OZSS.19-80B	3/16" x 80'	Stainless steel cable assembly
OZGAL.25-55B	1/4" x 55'	Galvanized cable assembly
OZSS.25-55B	1/4" x 55'	Stainless steel cable assembly


All cable assemblies come with swaged ball and swivel hook with latch. Custom cable length available. 3/16" - 80 ft max. length • 1/4" - 55ft max. length

Steel Wire Rope (For manual and power winch)


OZGAL.19-90	3/16" x 90'	Galvanized cable assembly
OZSS.19-90	3/16" x 90'	Stainless Steel cable assembly
OZGAL.25-45	1/4" x 45'	Galvanized cable assembly
OZSS.25-45	1/4" x 45'	Stainless Steel cable assembly

All cable assemblies come with swaged ball and swivel hook with latch. Custom cable length available. 3/16" - 90 ft max. length • 1/4" - 45ft max. length

Options for faster lowering and raising



Detach winch handle for drill option.



AC and DC power winches available.


DAVIT CRANE MOUNTING BASES (Sold Separately)

*Includes mounting template




COMPOZITE ELITE DAVIT CRANE - OZCF1200DAV

OZPED2




OZSOC2



*Bases inside diameter 3.0"

OZWALL2









APPLICATION DATA SHEET | DAVIT CRANES

Date: _____

Company Name:				
Phone:	Fax:			
Address: City:		State:	Zip Code:	
1. JOB DESCRIPTION:				
2. WEIGHT OF LOAD:			Reach	
3. HOW FAR IS THE LOAD MOVING?		Height		
4. REACH REQUIREMENTS:		Pedestal		
5. WHAT CAPACITY DO YOU NEED AND WHAT F	REACH?			
6. HEIGHT REQUIREMENTS:			Wall Base ase	
7. WINCH REQUIREMENTS:				
] Hand [] 115 Volt AC [] 12 Volt DC				
B. BASE REQUIREMENTS:				
] Pedestal [] Socket [] Wall Mount] Base Extension	Pu	Consulting with a	ble for proper base installation a civil engineer or qualified s highly recommended.	
9. WHERE IS THE DAVIT CRANE BEING USED?		Each crane is tested at 125%. Test cert included. Cable and base sold separately.		
			rs are not for lifting up people ects over people.	
10. HOW DID YOU HEAR OF US?	Lo	ad ratings may vary	ects over people. depending on position of boomength and winch used.	