


Eye & Eye Slings



Flat Tapered Code FT



Flat No Taper Code FE


Eye and Eye slings can be used in choker, vertical and basket hitches. Slings with Half Twist (Type 4) eyes are furnished unless Flat (Type 3) eyes are specified. Sling eyes will be wrapped at the bearing point unless otherwise specified.

Tapered eyes are automatically furnished on slings over 2 inches wide to provide for a proper relationship between the sling and the lifting hardware. Eyes with no taper are available.

The bearing points of Half Twist (Type 4) eyes are oriented 90° to the sling body. The perpendicular relationship between the eye and body in Half Twist, Type 4 eyes results in a comparatively advantageous choke hitch, when compared to Flat (Type 3) eyes. Half Twist eyes perform equally well in vertical or basket hitches.

For Half Twist Eyes with Taper, specify "HTT" (EE1-902 HTT) Eye Width-1"
 For Half Twist Eyes with no taper, specify "HT" (EE1-902 HT) Eye Width-2"
 For Flat Eyes with Taper, specify "FT" (EE1-902 FT) Eye Width-1"
 For Flat Eyes with no taper, specify "FE" (EE1-902 FE) Eye Width-2"

Eyes depicted feature standard eye protection, Order Code "J" and does not need to be added to sling stock number. Other eye treatments are available. See page 56 for ordering information, eye protection options and material designations.



Half Twist Tapered Code HTT



Half Twist No Taper Code HT

Width (Inches)	Stock Number	Eye Dimensions (Inches)		WORK LOAD LIMITS (Lbs.)					Sling Weight (Lbs.)		Minimum Sling Length (Ft.)
				Choker	Vertical	Basket Hitches					
				Width	Length	⌚	⌚	90°	60°	45°	
1"	EE1-601	1"	9"	900	1,200	2,400	2,070	1,690	.40	.03	4
1"	EE1-901	1"	9"	1,200	1,600	3,200	2,770	2,260	.67	.05	4
1"	EE2-601	1"	9"	1,900	2,400	4,800	4,150	3,390	.59	.06	3
1"	EE2-901P	1"	9"	2,500	3,200	6,400	5,540	4,520	1.00	.11	3
1"	EE4-601	1"	12"	3,800	4,800	9,600	8,310	6,780	1.22	.13	4
1"	EE4-901P	1"	12"	5,000	6,400	12,800	11,080	9,050	2.07	.22	4
1-1/2"	EE1-915	1-1/2"	9"	1,800	2,300	4,600	3,980	3,250	1.11	.09	4
1-1/2"	EE2-915	1-1/2"	9"	3,600	4,600	9,200	7,960	6,500	1.67	.19	3
1-1/2"	EE4-915	1-1/2"	12"	7,200	9,200	18,400	15,930	13,000	3.44	.37	4
2"	EE1-602	2"	12"	1,900	2,400	4,800	4,150	3,390	.96	.08	4
2"	EE1-902P	2"	12"	2,500	3,200	6,400	5,540	4,520	1.34	.11	4
2"	EE2-602	2"	12"	3,800	4,800	9,600	8,310	6,780	1.44	.16	4
2"	EE2-902P	2"	12"	5,000	6,400	12,800	11,080	9,050	2.02	.22	4
2"	EE4-602	2"	12"	7,000	8,860	17,720	15,340	12,530	2.96	.32	4
2"	EE4-902P	2"	12"	9,000	11,400	22,800	19,740	16,120	4.14	.40	4
3"	EE1-603	1-1/2"	12"	2,700	3,600	7,200	6,230	5,090	1.82	.14	4
3"	EE1-903P	1-1/2"	12"	3,800	4,800	9,600	8,310	6,780	2.29	.18	4
3"	EE2-603	1-1/2"	12"	5,300	6,600	13,200	11,430	9,330	2.52	.28	4
3"	EE2-903P	1-1/2"	12"	7,000	8,860	17,720	15,340	12,530	3.24	.35	4
3"	EE4-603	1-1/2"	18"	9,000	11,400	22,800	19,740	16,120	5.18	.56	5
3"	EE4-903P	1-1/2"	18"	13,600	17,000	34,000	29,440	24,040	6.60	.70	5
4"	EE1-604	1-1/2"	14"	3,800	4,800	9,600	8,310	6,780	2.24	.17	5
4"	EE1-904P	1-1/2"	14"	5,000	6,400	12,800	11,080	9,050	2.86	.22	5
4"	EE2-604	1-1/2"	14"	7,000	8,860	17,720	15,340	12,530	3.10	.34	5
4"	EE2-904P	1-1/2"	14"	9,000	11,400	22,800	19,740	16,120	3.96	.44	5
4"	EE4-604	2"	18"	12,000	15,000	30,000	25,980	21,210	6.54	.69	6
4"	EE4-904P	2"	18"	18,000	22,800	45,600	39,480	32,240	8.36	.88	6
5"	EE1-905P	1-3/4"	18"	6,000	8,000	16,000	13,850	11,310	3.48	.27	6
5"	EE2-905P	1-3/4"	18"	11,400	14,250	28,500	24,680	20,150	4.82	.54	6
5"	EE4-905P	2-1/2"	24"	19,000	24,000	48,000	41,560	33,940	10.18	1.07	8
6"	EE1-906P	2"	24"	7,600	9,600	19,200	16,620	13,570	4.21	.32	8
6"	EE2-906P	2"	24"	13,600	17,000	34,000	29,440	24,040	5.83	.65	8
6"	EE4-906P	3"	24"	24,000	30,000	60,000	51,960	42,420	12.31	1.30	8
8"	EE1-908P	3"	24"	10,250	12,800	25,600	22,170	18,100	6.27	.45	8
8"	EE2-908P	3"	24"	18,000	22,800	45,600	39,490	32,240	8.51	.90	8
8"	EE4-908P	4"	24"	32,000	40,000	80,000	69,280	56,560	17.47	1.79	8
10"	EE1-910P	3-1/2"	24"	12,000	15,000	30,000	25,980	21,210	8.20	.59	8
10"	EE2-910P	3-1/2"	24"	19,000	24,000	48,000	41,560	33,940	11.13	1.17	8
10"	EE4-910P	5"	30"	36,000	45,000	90,000	77,940	63,630	22.85	2.34	10
12"	EE1-912P	4"	30"	15,000	19,000	38,000	32,910	26,860	10.08	.72	10
12"	EE2-912P	4"	30"	24,000	30,000	60,000	51,960	42,420	13.68	1.44	10
12"	EE4-912P	6"	36"	43,000	53,000	106,000	91,790	74,940	28.80	2.88	12

Consider using High Performance Fiber Slings in applications requiring 3 and 4 ply thick slings, wider than 4 inches.

WARNING

To avoid SEVERE INJURY or DEATH from equipment failure:

- Users MUST BE TRAINED on proper selection/use.
- NEVER damage, misuse or overload - observe and NEVER EXCEED the Work Load Limit (WLL).
- Properly maintain and inspect before use.

NEVER ON

NEVER UNDER

NEVER IN-LINE