

Dumond® Laminated Paper Technical Data Sheet

PRODUCT DESCRIPTION:

Dumond® Laminated Paper assists in the removal of architectural, industrial, and high-performance paints and coatings. It is specially designed to keep Dumond® paint removers in a wet state, reducing evaporation and allowing them to work more quickly and efficiently. Also, paint removers and the coatings beneath will stick to the paper aiding in clean-up. When used outdoors, Dumond Laminated Paper also assists in protecting the remover from the elements.

Recommended for use with all Dumond® brand paint removers: Peel Away® 1, Peel Away® Marine, Smart Strip® Advanced, Smart Strip® PRO, Smart Strip® Marine, Smart Strip® Marine PRO, Smart Strip® Auto, Confined Space® Paint Strip Gel, Watch Dog® All Purpose Citrus Paint Remover, and Smart 'n Easy™ Citrus Paint & Varnish Remover.

MAIN FEATURES & BENEFITS:

- Paper keeps paint removers in a wet state, preventing premature drying. If our waterbased paint removers dry out, they stop working!
- Helps to speed up the paint removal process, reducing total dwell time.
- Protects the remover from the elements during outdoor projects.
- Applies continual positive pressure on vertical surfaces, keeping the product in contact with the surface.
- Can be used on ANY project size, big or small.
- Not just for DIY use, trusted by Professionals on major projects.

TECHNICAL DATA:

FORM: Laminated Paper Sheets or Rolls SIZE (SHEETS): 3¼ feet x 3¼ feet (1m x 1m)

SIZE (ROLLS): 13 inches x 300 feet (33cm x 91.44m)

RECOMMENDED SUBSTRATES:

Dumond® Laminated Paper sticks to the removal product, **NOT** the substrate. Review the **Technical Data Sheet (TDS)** for the specific paint removal product for efficacy on a particular substrate. Test your paint remover before beginning a full project.



APPLICATION:

When using **Dumond® Laminated Paper**, it is always best to work in small, manageable sections at a time. This ensures the paint remover doesn't dry out on sections not yet covered by the paper.

Apply the selected **Dumond®** paint remover to the surface according to the instructions provided by the remover. Working in manageable sections, cover with Dumond® Laminated Paper. Smooth the paper without pressing too firmly to ensure no visible air pockets. Gently poke any remaining bubbles with a hole to release the air.

DWELL TIME:

The dwell time is determined by the specific **Dumond®** paint remover used. This dwell time will be reduced when covered with paper, which protects the remover from the elements and helps to maintain the product's wet state. This allows the remover to continue working longer to remove the coating faster.

Refer to product testing for approximate dwell times.

REMOVAL:

Remove, scrape, and clean 1 - 2 sq. ft. (0.09m2 - 0.19m2) of area at a time. This will prevent the other covered sections from drying out during removal. Insert a trowel, spatula, or paint scraping tool underneath the **Dumond® Laminated Paper** and lift the while slowly scraping along the substrate. The paint remover and removed paint should stick to the paper as you pull it away from the surface.

Scrub all surfaces clean with a sponge or nylon bristle brush and water, or a pressure washer. Rinse thoroughly with water to ensure all remaining residue is removed. Collect paint and product residue in plastic bags and dispose of it in compliance with federal, state, and local regulations.

Refer to the paint remover **TDS** for additional information.

AVAILABILITY:

Dumond® Laminated Paper is available in sheets and rolls. **Dumond®** products are available through a nationwide network of paint and hardware stores, safety supply distributors, or online. For an in-person outlet nearest you, please visit www.dumondglobal.com. Once on the website, type your postal/zip code into the dealer locater to find addresses and phone numbers of your nearest dealers.



HEALTH AND SAFETY REQUIREMENTS:

The full Safety Data Sheet (SDS) for the specific **Dumond®** paint remover can be found online at www.dumondglobal.com. View the SDS of your chosen paint remover **BEFORE** product use for required safety information.

For additional emergency assistance, please call **1-800-535-5053** in the United States. International assistance is available at **1-325-323-3500**. Both numbers are available **24/7/365**.

WARRANTY:

Dumond Inc. warrants all its products to be free from defects and makes no other warranties with respect to its products, express or implied, including without limitation the implied warranties of MERCHANTABILITY OF FITNESS FOR PURPOSE. **Dumond Inc.'s** liability shall be limited in all events to supplying sufficient products to re-treat the specific areas to which defective product(s) have been applied. **Dumond Inc.** shall have no other liability, including liability for incidental, consequential, or resultant damages whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of **Dumond Inc.** or its distributors and dealers.

TECHNICAL SERVICES:

Dumond Inc.'s expert staff is available to answer technical questions and provide product-specific information. For business hours, see our website for more information.

Address: 253 S. Bailey Road

Downingtown, PA 19335

Phone: (610) 383-6061

Email: info@dumondglobal.com
Website: www.dumondglobal.com