

PRODUCT DESCRIPTION:

Smart 'n Easy™ Concrete Oil, Grease, & Stain Remover is a highly effective, heavy-duty water-based emulsifier engineered to penetrate deep into porous masonry surfaces to remove years of stubborn petroleum-based stains (transmission & brake fluid, gasoline, motor oil), grease, grime, and dirt buildup.

POROUS MASONRY SURFACES: Concrete, Cement, Brick, Natural/Man-Made Stone, Tiles, Asphalt, Limestone, Brownstone, Sandstone, Granite, Marble, Slate, and More!

USEFUL EVERYWHERE: Around the Home (Retaining Walls, Sidewalks, Pavers, Garage Floors, Walkways) or Commercial Areas (Gas Stations, Parks, Mechanic Shops, Parking Lots & Garages, Industrial Factories, Manufacturing Plants, Restaurants, Storefronts).

Smart 'n Easy™ Concrete Oil, Grease, & Stain Remover is easy to use. Simply spray on, let set, and rinse off. For difficult stains agitate with a nylon brush. Generally, little to no scrubbing is required! Spot clean motor oil spills on concrete garage floors and driveways in as little as 15 minutes!

MAIN FEATURES & BENEFITS:

- Ready-To-Use de-greasing solvent.
- Cleans and removes petroleum-based stains and residue, as well as other deeply embedded organic dirt, grime, and stains.
- Engineered to penetrate deep into porous masonry surfaces like concrete, asphalt, and brick; does not sit on top of the surface like other cleaners!
- Ideal for use in commercial and residential spaces like homes, garages, workshops, and more!
- Also works on glass, stainless steel, and most other substrates. A multi-surface cleaner!
- Won't cause pitting, etching, or altering of the surface texture.
- User-friendly; can be applied by pump sprayer, brush, or roller.
- Restores masonry substrates to its natural appearance!



TECHNICAL DATA:

- Form: Green Liquid
- Weight/Gal: 12 lbs.
- pH: 12.3
- Freezing Point: 32° F / 0° C
- Shelf Life: 3 years in a tightly sealed container kept in a room temperature, clean, and dry environment.

RECOMMENDED SUBSTRATES:

Recommended for use on brick, concrete, cement, terrazzo, most fiberglass, tile, terra cotta, limestone, brownstone, sandstone, granite, marble, slate, stone, and asphalt. Not recommended for the use on copper, zinc, aluminum, drywall, plywood, wood surfaces, gypsum, veneer, and most plastics. Before applying to any substrate, perform as product test.

TESTING:

Always prepare a test area on each type of surface. Testing before beginning is the best way to ensure product suitability and efficacy. It informs on how to handle the product, gauge how to apply, and determine how long it must remain in place before removing. Applying incorrectly or removing too quickly may result in the need for more than one application, increasing labor and material costs.

SURFACE & AIR TEMPERATURES:

To avoid product freezing and reducing effectiveness do not use below 40°F. For best results, use this product in temperatures between 40°F and 90°F. Product effectiveness is increased in warmer temperatures, but may dry out sooner.

PREPARATION:

Cover and protect areas where cleaning is not desired, including adjoining surfaces where overspray may travel; keep protection in place during removal process. Polyethylene plastic and masking tape create an effective barrier. Nearby plants and other foliage should be covered during application and removal. On hot and humid days, or when working in direct sunlight, dampen the surfaces with water prior to application to prevent rapid evaporation.

APPLICATION:

Apply with a pump-up sprayer or trigger spray bottle. It is important to apply bottom to top to avoid any streaking. Leave on for a minimum of 15 – 30 minutes or the time determined during testing. Depending on the contaminants present, it may be necessary to agitate with a nylon bristle brush. **Smart 'n Easy™ Concrete Oil, Grease, & Stain Remover** provides an average spread rate of about 200 - 250 sq. ft. per gallon; results may vary. Work in small manageable areas that can be rinsed before the product can dry to the surface.

Spray Application: Low pressure sprayer or garden sprayer recommended.

REMOVAL & CLEAN UP:

Remove by either high pressure washing at minimum of 1500 PSI or using a scrub brush to agitate the surface then rinsing with a hose or water. Thoroughly wash the surface from top to bottom to avoid streaking until the foaming action stops. Allow the surface to dry completely before re-coating.

AVAILABILITY & COST:

Smart 'n Easy™ Concrete Oil, Grease, & Stain Remover is available in 22oz trigger spray bottles, 1 gallon refills, and 5 gallon containers. **Dumond®** products are available through a nationwide network of paint and hardware stores, safety supply distributors, or online. For an in-person outlet nearest you, please visit www.dumondglobal.com. Once on the website, type your postal/zip code into the dealer locator to find addresses and phone numbers of your nearest dealers.

HEALTH & SAFETY REQUIREMENTS:

The full Safety Data Sheet (SDS) for **Smart 'n Easy Concrete Oil, Grease & Stain Remover** can be found online at www.dumondglobal.com. View the SDS **BEFORE** product use for required safety information.

DANGER: CAUSES SEVERE BURNS & EYE DAMAGE

Contains: Disodium Trioxosilicate, 1-Butoxy-2-Propanol, and Potassium Hydroxide

Avoid contact with skin, eyes, or clothing. Use personal protective equipment (PPE) as required. Remove PPE immediately after handling this product. Wash thoroughly after handling before eating, drinking, smoking, or using toilet facilities. Protect the container from physical damage. Follow all label precautions even after container is emptied because it may retain product residues. Do not breathe vapors, dust, or spray mist.

EYE CONTACT: Rinse carefully with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Immediate medical attention is required.

SKIN CONTACT: Remove contaminated clothing and shoes. Wash thoroughly with soap and water until no traces of the chemical remain. Wash contaminated clothing before reuse.

For additional emergency assistance, please call **1-800-535-5053** in the United States. International assistance is available at **1-325-323-3500**. Both numbers are available **24/7/365**.

WARRANTY:

Dumond® warrants all its products to be free from defects and makes no other warranties with respect to its products, express or implied, including without limitation the implied warranties of MERCHANTABILITY OF FITNESS FOR PURPOSE. Dumond's liability shall be limited in all events to supplying sufficient products to re-treat the specific areas to which defective product have been applied. Dumond® shall have no other liability, including liability for incidental, consequential, or resultant damages whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of Dumond® or its distributors and dealers.

TECHNICAL SERVICES:

Dumond®'s expert staff is available to answer technical questions and provide product-specific information. On-site assistance is also available, time permitting, at no additional cost.



Address: 253 S. Bailey Rd.
Downingtown, PA 19335
Phone: (610) 383 - 6061
Website: www.dumondglobal.com
Email: support@dumondglobal.com
info@dumondglobal.com