

## Product Specifications

Product name	Xtal Gacrux		
Product code	XTL-GX		
<b>Main body</b>			
Light source	LED		
Dimmer level (3 steps)	LOW	MID	HIGH
Color temperature	2000K		
Battery run time	24 Hours	12 Hours	6 Hours
Automatic on / off function	LED is automatically turns off when the main body is placed on the charger stand and turns on when it is removed.		
Charge method / Period	USB Charge / Approx. 3 Hours		
Power supply	Rechargeable lithium-ion battery, 3.7V / 190mAh		
Recharging life	Approx. 500 cycles		
	* The recharging life refers to the standard number of times the battery can be recharged before battery performance drops below 50% when fully charged.		
Waterproofing	IPX6 equivalent		
	* IPX6 means the degree of liquid ingress protection at which "water projected in powerful jets against the enclosure from any direction shall have no harmful effects".		
Dimensions	Φ80mm × 82mmH (Approx.)		
Weight	720g		
Main materials	Glass shade : Crystal glass		
	Aluminum base : Aluminum alloy, Silicon rubber, ABS, etc.		
Operating temperatures	0°C to 40°C		
<b>Charger stand</b>			
Dimensions	85mmW × 85mmD × 8.5mmH		
Weight	54g		
Main materials	Polycarbonate, Aluminum alloy, Non-migrating rubber, etc.		

Design and specifications are subject to change without notice.