

Product Specifications

2023.03.30

Product name	T			
Product code	N/A			
Price	N/A			
Light source	LED ※1 ※2			
Color rendering index	Ra95			
Dimming level	LOW	MID	HIGH	EX-HIGH
Power consumption (W)	0.1	0.5	1.2	3.5
Illuminance	10	100	350	800
Color temperature (K)	1800	2300	2400	2500
Battery run time (h)	150	38	12	5
Power supply	Rechargeable lithium-ion battery, 3.6 V / 5100mAh			
Recharging time	Approx. 6 hours*6			
Recharging cycle	Approx. 500 times*4			
Waterproofing	Main body	IP66		
	Charger stand	Not waterproof		
Main materials	Main body	Aluminum,PC,Silicone rubber		
	Shade	Aluminum,Acrylic resin		
	Charger stand	Zinc die cast alloy,ABS,Silicone rubber		
Surface treatment	Main body	Anodized oxide coating		
	Shade	Anodized oxide coating		
	Charger stand	Baked paint		
Weight(g)	Main body	930g		
	Charger stand	30g		
Dimensions(mm)	Main body	Outer diameter : ϕ 130 × Height : 205		
	Charger stand	Outer diameter : ϕ 54 × Height : 8		
Operating temperature (° C)	0°C~40°C			

*1 The brightness of the LED elements decreases by about 70% after about 40,000 hours of use.

*2 The color and brightness of each individual LED element's light varies even when used in a light source with the same product

*3 Varies depending on operating conditions and environments.

*4 Applies when the battery performance drops below 50%.

Design and specifications are subject to change without notice.