

**Xtal**  
**Xtal Acrux**  
**Xtal Becrux**  
**Xtal Gacrux**  
 Design Ryuchl Kozeki



Product name	Xtal	Xtal Acrux	Xtal Becrux	Xtal Acrux Dark Gray	Xtal Gacrux
Product code	XL2-ST	XL2-AX	XL2-BX	XL2-AXGRY	XL2-GX
Main materials	Shade : Crystal glass Base : Aluminum, Silicone rubber, ABS, etc.				
Charger stand	Zinc alloy, Silicone rubber, ABS				
Dimensions (mm)	90 (Including charger stand)				
Outer diameter	ø80	ø87	ø85	ø87	ø80
Height	90 (Including charger stand)				
Weight(g)	620	740	700	740	720
Light source	LED				
Dimming level	LOW / MID / HIGH				
Battery run time (h)	Battery power mode: 32 / 16 / 8		USB power mode: Unlimited		
Automatic on / off function	LED is automatically turns off when the main body is placed on the charger stand and turns on when it is removed.				
Power consumption (w)	Less than 0.2				
Color temperature (K)	2000				
Charging	USB charging : Approx. 3 hours				
Power supply	Rechargeable lithium-ion battery, 3.7 V / 190mAh				
Waterproofing	IPX6 equivalent* (Charger stand is not waterproof) NOTE : IPX6 means the degree of liquid ingress protection at which "water projected in powerful jets against the enclosure from any direction shall have no harmful effects".				

Accessories



Case



USB cable (Type-C)



Charger stand

\* Thanks to widespread use of computers and mobile phones, most people today already possess a USB-compatible AC adapter. To minimize waste, AC adapter is not provided with this product.

\* In addition to Ambientec's optional AC adapter (AMB-AC02), you can also use a USB AC adapter compatible with DC 5V/≥1A output.

**Ambientec**

Ambientec Corporation  
[www.ambientec.co.jp](http://www.ambientec.co.jp)



Design and specifications are subject to change without notice.

Photo by Hiroshi Iwasaki

10068-800G