

Adhesives & Sealants

General Construction Adhesives & Sealants

EUROFIX FAST

AN AMAZING NEW 10 SECOND BOND PROFESSIONAL ADHESIVE



High strength, commercial grade cyanoacrylate adhesive that bonds in 10 seconds.

Features

- 10 second bond
- Commercial grade adhesive
- High bonding strength
- Suitable for vertical and overhead applications
- Bonds porous and non-porous substrates
- Bonds difficult surfaces
- Gel adhesive

Applications

- For bonding most common surfaces where high strength and rapid bonding times are required
- Suitable for bonding metal, MDF, wood, chipboard, glass, rubber, many plastics, leather, fibreglass and many other common substrates
- Suitable for many commercial and industrial applications

Colour	Size	Code
Clear	50ml	EUROFAST/50
Clear	100ml	EUROFAST/100



Scan for more information

BONDS TO

WOOD • CONCRETE • METAL • RUBBER • MOST PLASTICS • LEATHER • PLUS MANY OTHER SUBSTRATES



10 SECOND BOND



COMMERCIAL GRADE



HIGH STRENGTH



BONDS POROUS AND NON-POROUS SURFACES



BONDS DIFFICULT SURFACES

Adheseal Multi-Tack Construction Adhesive

Newly formulated green star compliant solvent free Builders' Nails / Gap Filler / Joint Sealant.



Features

- 3 products in 1 - adhesive / joint sealant / gap filler
- Suitable for interior and exterior applications
- Paintable
- High initial grab
- Does not become brittle
- Flexible
- Water clean up
- Excellent UV resistance
- Low VOC (complies with Green Star VOC)

Applications

- General purpose construction adhesive
- General purpose gap filling and joint sealing
- Flooring and wall systems
- Bonding timber, metal concrete and most common construction materials
- Cornice adhesive
- Bonding timber to studs and joists
- Installation of wall sheeting, internal and external mouldings
- Bond polystyrene foam components

Available Colours*



Colour	Size	Code
Beige	300ml Cartridge	MULTITACK/CTG
Beige	600ml Sausage	MULTITACK/SSG

NEW
NEW PRODUCT

UV
UV RESISTANT

LOW VOC
GREEN STAR VOC

UV
LOW VOC



Adheseal Gap Filla

Flexible multipurpose acrylic gap filler.

Features

- Commercial grade
- Interior and exterior applications
- Paintable
- Water clean up
- Highly flexible
- Excellent UV resistance

Available Colours*



Colour	Size	Code
White	450gm Cartridge	GAPFILLA/CTG



Adheseal Builders Nails

General purpose construction adhesive suitable for a wide range of applications.

Features

- Good adhesion to most common construction materials
- Suitable for interior and exterior applications
- Fast tack time

Available Colours*



Colour	Size	Code
Beige	320gm Cartridge	BUILDNAIL/CTG

UV
LOW VOC
FIRE RATED



HV Duct

An acrylic sealant for sealing around the connecting flanges on high velocity ducting.

Features

- Fire rated (tested to AS1530.3)
- Flexible
- Water clean up
- Excellent UV resistance
- Low VOC (complies with Green Star VOC)

Available Colours*



Colour	Size	Code
Grey	450gm Cartridge	HVDUCT/CTG

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.

LOW VOC



Adheseal Unobond

COHESIVE STRENGTH ★★★★★ ELASTICITY ★☆☆☆☆

Unobond is a single component, quick setting, moisture cured polyurethane adhesive. Commonly used for structural applications. It has excellent water resistance and provides an extremely strong structural bond.

Features

- High bond strength
- Can be used on slightly damp surfaces
- Resistant to temperature extremes
- Resistant to moisture and chemicals
- Fast curing
- Adheres to most common building materials
- Water resistant
- D4-DIN EN204 (Unobond Cartridge only)
- Low VOC (complies with Green Star VOC)

Applications

- Fixing and gluing wooden elements to other various porous and non-porous elements
- Timber joinery, metal fabrication and boat production and more
- All bonding applications that need a high water resistance
- Wood, plasterboard, particleboard, aluminium, iron, steel, sheet metal, polystyrene foam, insulation foam, concrete, FC sheeting, brick, masonry, veneer, melamine, many plastics and many other common substrates.

Type	Colour	Size	Code
Gel (D4-DIN EN204)	Opaque	310ml Cartridge	UNOBOND/CTG
Liquid	Blue	6Kg Can	UNOFC/6

LOW VOC



Eurofix PU Marine

COHESIVE STRENGTH ★★★★★ ELASTICITY ★☆☆☆☆

A one-component, fast curing, moisture cured, liquid polyurethane adhesive. It possesses high water resistance and structural bonding strength.

Features

- Easy application, low viscosity
- High bond strength
- Water resistant (D4-DIN EN204)
- Can be used on slightly damp surfaces
- Resistant to temperature extremes
- Resistant to moisture and chemicals
- Fast Curing (370 PU Marine Express only)
- Low VOC (complies with Green Star VOC)

Applications

- Fixing and gluing wooden elements to other various porous and non-porous elements as wood, metal, concrete, polystyrene foam
- Timber joinery, metal fabrication and boat production and more
- All bonding applications that need a high water resistance

Type	Colour	Size	Code
360 PU Marine	Opaque	560g Bottle	EUROPUMAR/560
370 PU Marine Express (Fast Cure)	Opaque	560g Bottle	EUROPUEXP/560



Polyurethane NBS Foam

A single component polyurethane expanding foam. It expands up to 40 times its size when exposed to air. Suitable for sealing and insulating around window and door frames as well as an adhesive for polystyrene architectural mouldings.

Features

- Excellent adhesion on most construction
- No primer required
- Expands up to 40 times its size
- Paintable
- Applied with specialised applicator gun for greater control

Applications

- Sealing and insulating around window and door frames
- Adhesive for polystyrene architectural mouldings
- Adhesive, Insulator
- Void Filler

Colour	Size	Code
Cream	750ml Can	FOAMPUGG/750



Hot Melt Glue Sticks

A translucent, general-purpose hot melt in a stick used to will bond to a wide variety of materials including cardboard, most plastics metals, timbers, fabrics and ceramics and more. A Hot Melt Glue Gun (K-1000) is required for application.

Colour	Size	Code
Opaque	1kg Bag	GLUESTICKAE110

Adhesives & Sealants

Polyurethanes

Coverage Calculation Guide

Step 1 - Calculate litres required

Joint Width (cm) x Joint depth (cm) x Joint length (cm) ÷ 1000 = Litres required

Step 2 - Calculate product quantity required

Cartridges: Litres required ÷ 0.3 = quantity of cartridges required

Sausages: Litres required ÷ 0.6 = quantity of sausages required

Please note: Allow for approximately 15% wastage

Rating System

The star rating system used in this catalogue is a guide only. Refer to the TDS when selecting suitable products. A product with a cohesive strength rating of 3 stars or more is considered a structural grade adhesive.



Available Colours*



Adheseal PU-240

COHESIVE STRENGTH ★★★★★ ELASTICITY ★★★★★

Single component, moisture curing, polyurethane adhesive / sealant. This tough and durable adhesive / sealant can be used in a wide range of applications such as joint sealing or structural bonding. Suitable for construction, industrial, marine and automotive industries.

Features

- Low modulus
- Excellent bond to most construction materials
- Very tough and durable
- Paintable
- Good weathering properties
- Low VOC (complies with Green Star VOC)

Applications

- High performance
- Structural bonding
- Fast curing waterproofing sealant
- General joint sealing
- Boat deck sealant
- Construction, marine and automotive

Colour	Size	Code
White	310ml Cartridge	PU240WH/CTG
Grey	310ml Cartridge	PU240GR/CTG
Black	310ml Cartridge	PU240BL/CTG



Available Colours*



Adheseal PU-50FC

COHESIVE STRENGTH ★★★★★ ELASTICITY ★★★★★

PU-50FC is a fast curing, extremely tough and durable polyurethane adhesive / sealant. With a high shore A hardness this is a high performance product suitable for many applications from a high structural strength adhesive to a non-pick joint sealant and more. Suitable for construction, industrial, marine and automotive industries.

Features

- Fast curing
- Medium modulus
- High performance
- Paintable
- Easily sandable
- Extremely tough and durable
- Good weathering properties
- Excellent bond to most construction materials
- Low VOC (complies with Green Star VOC)

Applications

- Structural bonding
- Joint sealing
- Non-pick sealant suitable for prisons, schools and public access areas
- Marine manufacturing
- Boat deck sealant
- Automotive body building

Colour	Size	Code
White	600ml Sausage	PU50WH/SSG
Grey	600ml Sausage	PU50GR/SSG



Available Colours*



Adheseal PU-25FC

COHESIVE STRENGTH ★★★★★ ELASTICITY ★★★★★

Adheseal PU-25FC is a fast curing, single component, moisture curing, polyurethane adhesive / sealant. This tough and durable adhesive / sealant can be used in a wide range of applications such as joint sealing or structural bonding. Suitable for construction, industrial, marine and automotive industries.

Features

- Fast curing
- High performance
- Low modulus
- Excellent bond to most construction materials
- Very tough and durable
- Paintable
- Potable water certificate AS/NZS4020:2005
- Good weathering properties
- Low VOC (complies with Green Star VOC)

Applications

- General bonding
- Tilt up and precast joints in buildings and civil structures (fast curing)
- Trafficable expansion joints
- Construction joints (fast curing)
- Fast curing waterproofing sealant
- Sealing water retaining structures
- General joint sealing (fast curing)

Colour	Size	Code
White	600ml Sausage	PU25WH/SSG
Grey	600ml Sausage	PU25GR/SSG
Off-Grey	600ml Sausage	PU25OFGR/SSG
Black	600ml Sausage	PU25BL/SSG

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.



Available Colours*



Adheseal PU-15

COHESIVE STRENGTH ★★★★★ ELASTICITY ★★★★★

Adheseal PU-15 is a high performance, single component, moisture curing, polyurethane joint sealant. Tough and durable, it is suitable for applications such as facade joints, window frame installations, tilt up and precast joints and will bond to most common construction materials. Suitable for construction, industrial, marine and automotive industries.

Features

- Very Low modulus
- Excellent bond to most common construction materials
- Very durable
- Paintable
- Good weathering resistance
- Non-sag in vertical joints
- Long skin time
- Low VOC (complies with Green Star VOC)

Applications

- Tilt up and precast joints in buildings and civil structures
- Construction joints
- External walling and cladding joints
- Curtain walling
- Window frame installation
- Sealing penetrations in walls or floors such as ducts and piping
- Retaining walls
- General purpose sealant in construction

Colour	Size	Code
White	600ml Sausage	PU15WH/SSG
Concrete Grey	600ml Sausage	PU15CGR/SSG
Black	600ml Sausage	PU15BL/SSG



Available Colours*



PU25 SOL

COHESIVE STRENGTH ★★★★★ ELASTICITY ★★★★★

Self-levelling, fast curing, single component, moisture curing, polyurethane adhesive / sealant. This tough and durable adhesive / sealant can be used in applications where a low viscosity product is required..

Features

- Self-levelling
- Low modulus
- Very long skin time
- Excellent bond to most common construction materials
- Very tough and durable
- Paintable
- Non- bubbling
- Good weathering properties
- Low VOC (complies with Green Star VOC)

Colour	Size	Code
Grey	600ml Sausage	PU25GRSOL/SSG



Available Colours*



Megaprene 40

COHESIVE STRENGTH ★★★★★ ELASTICITY ★★★★★

Single component gun grade moisture curing polyurethane construction joint sealant.

Features

- Trafficable
- Tough and durable commercial grade joint sealant
- Good resistance to fuel
- Good weathering properties
- Good chemical resistance
- Main Roads approved product
- Low VOC (complies with Green Star VOC)

Colour	Size	Code
Grey	600ml Sausage	MEGA40GR/SSG

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.



Available Colours*



PU Construction

COHESIVE STRENGTH ★★★★★ ELASTICITY ★★★★★

One part, moisture curing, elastic joint polyurethane sealant. It is commonly used as a general purpose sealant for sealing joints in building construction.

Features

- Low VOC (complies with Green Star VOC)

Colour	Size	Code
Grey	600ml Sausage	PUCONGR/SSG



Available Colours*



Bostik Seal n Flex 1

Low modulus, one component moisture curing polyurethane sealant. It is durable with a long skin time. Seal n Flex 1 bonds to most common construction materials.

Colour	Size	Code
White	600ml Sausage	SNFWH/SSG
White	300ml Cartridge	SNFWH/CTG
Grey	600ml Sausage	SNFGR/SSG
Grey	300ml Cartridge	SNFGR/CTG
Black	600ml Sausage	SNFBL/SSG
Black	300ml Cartridge	SNFBL/CTG
Off White	600ml Sausage	SNFOW/SSG
Classic Bone	600ml Sausage	SNFCB/SSG
Manilla Sand	600ml Sausage	SNFMAN/SSG
Bahama Beige	600ml Sausage	SNFBB/SSG
Limestone	600ml Sausage	SNFLI/SSG
Sandstone	600ml Sausage	SNFSST/SSG
Epping Grey	600ml Sausage	SNFEPGR/SSG
Redwood	600ml Sausage	SNFRW/SSG
Bronze	600ml Sausage	SNFBR/SSG



Available Colours*



Bostik Seal n Flex FC

One part, fast curing, elastic joint sealant polyurethane sealant suitable for a wide range of building and construction purposes. It can be used in indoor and outdoor applications and for various jobs which require a flexible adhesive or a durable joint sealant.

Colour	Size	Code
White	600ml Sausage	SNFFCWH/SSG
White	300ml Cartridge	SNFFCWH/CTG
Grey	600ml Sausage	SNFFCGR/SSG
Grey	300ml Cartridge	SNFFCGR/CTG
Black	600ml Sausage	SNFFCBL/SSG
Black	300ml Cartridge	SNFFCBL/CTG

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.

Adheseal

Polyurethane Range

Automotive / Construction / Industrial / Marine

High Performance Commercial Grade



Tough & durable



Excellent weathering resistance



Australian owned



Internal & external applications



Paintable



Low VOC



Good UV resistance

Adheseal PU-15 Joint Sealant



Features:

- Long skinning time
- Short cut off string
- Outstanding movement capabilities

Uses:

- Expansion joints
- Construction joints
- External wall & cladding joints
- General purpose sealant

COHESIVE STRENGTH



ELASTICITY



Adheseal PU-25FC Adhesive / Sealant



Features:

- Fast curing sealant
- High strength adhesive
- High abrasion resistance
- High tear strength
- Sandable
- Potable water certificate

Uses:

- Waterproofing applications
- Industrial general purpose adhesive
- General joint sealing
- Trafficable joint sealant

COHESIVE STRENGTH



ELASTICITY



Adheseal PU-50FC Structural Adhesive / Sealant



Features:

- Fast curing
- High abrasion resistance
- High tear strength
- Structural strength adhesive
- Tough joint sealant
- Sandable

Uses:

- Permanent structural applications
- Non-pick joint sealant
- Trafficable joint sealant
- Automotive/marine structural adhesive

COHESIVE STRENGTH



ELASTICITY



Adheseal
The Adhesive and Sealant Specialists

Adheseal Head Office
26 Wolverhampton Street
Stafford, Queensland 4053
Phone: (07) 3356 0000
sales@adheseal.com.au

Adheseal Sunshine Coast
2/18 Kessling Ave
Kunda Park, Queensland 4556
Phone: (07) 5477 0022
sc@adheseal.com.au

www.adheseal.com.au



Available Colours*



Sikaflex Construction (AP)

One part, moisture curing, polyurethane joint sealant. It is commonly used as a general purpose sealant for sealing joints in building construction.

Colour	Size	Code
Grey	600ml Sausage	SIKACONGR/SSG



Available Colours*



Sika Pro

One part, moisture curing, elastic joint polyurethane sealant. It is commonly used for expansion / construction joints and general sealing joints in building construction.

Colour	Size	Code
White	600ml Sausage	SIKAPROWH/SSG
White	310ml Cartridge	SIKAPROWH/CTG
Off White	600ml Sausage	SIKAPROFFWH/SSG
Off White	310ml Cartridge	SIKAPROFFWH/CTG
Sandstone	600ml Sausage	SIKAPROSAN/SSG
Sandstone	310ml Cartridge	SIKAPROSAN/CTG
Pale Brown	600ml Sausage	SIKAPROPALEBR/SSG
Pale Brown	310ml Cartridge	SIKAPROPALEBR/CTG
Beige (Japan)	600ml Sausage	SIKAPROJBE/SSG
Beige (Japan)	310ml Cartridge	SIKAPROJBE/CTG
Grey	600ml Sausage	SIKAPROGR/SSG
Grey	310ml Cartridge	SIKAPROGR/CTG
Dark Grey	600ml Sausage	SIKAPRODKGR/SSG
Dark Grey	310ml Cartridge	SIKAPRODKGR/CTG
Dark Amber	600ml Sausage	SIKAPRODKAM/SSG
Dark Amber	310ml Cartridge	SIKAPRODKAM/CTG
Red Brick	600ml Sausage	SIKAPROBRIC/SSG
Red Brick	310ml Cartridge	SIKAPROBRIC/CTG
Redwood	600ml Sausage	SIKAPRORED/SSG
Redwood	310ml Cartridge	SIKAPRORED/CTG
Black	600ml Sausage	SIKAPROBL/SSG
Black	310ml Cartridge	SIKAPROBL/CTG

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.



Sika 11-FC

One part, moisture curing, elastic joint sealant and multipurpose adhesive based on polyurethane. It is suitable for indoor and outdoor use and various applications which require a flexible adhesive or a durable joint sealant.

Colour	Size	Code
White	600ml Sausage	SIKA11FCWH/SSG
White	310ml Cartridge	SIKA11FCWH/CTG
Grey	600ml Sausage	SIKA11FCGR/SSG
Grey	310ml Cartridge	SIKA11FCGR/CTG
Black	600ml Sausage	SIKA11FCBL/SSG
Black	310ml Cartridge	SIKA11FCBL/CTG
Japan Beige	600ml Sausage	SIKA11FCBE/SSG

Available Colours*



Sika Tank

One part, moisture curing, elastic polyurethane joint sealant which is used in areas for the storage, filling and handling of water polluting liquids.

Features

- Potable Water Approved
- Chemical Resistant

Colour	Size	Code
Grey	600ml Sausage	SIKATANKGR/SSG

Available Colours*



Adheseal

Cordless Caulking Gun

Lithium Ion Power / The Choice Of Professionals

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.

Adheseal

Hybrid MS Polymer Range

Automotive / Construction / Industrial / Marine



Low
VOC



Solvent
Free



Isocyanate
Free



Easy tooling & finishing



Excellent colour stability



Excellent primer-less adhesion



Internal & external applications



Paintable



Non-bubbling



Excellent UV resistance

Hi Flex Construction Joint Sealant



Features:

- Low VOC
- Outstanding UV resistance
- Low modulus
- Easy tooling - creamy texture
- Paintable (instantly with most paints)
- Matt finish
- Excellent primer-less adhesion

Uses:

- Expansion joints
- Construction joints
- External wall & cladding joints
- General purpose sealant

COHESIVE STRENGTH ★★★★★
ELASTICITY ★★★★★

Hi Flex 60LS Structural Adhesive / Sealant



Features:

- Low VOC
- Outstanding UV resistance
- Excellent colour stability
- Low modulus
- Easy tooling - creamy texture
- Paintable (instantly with most paints)
- Excellent primer-less adhesion

Uses:

- Permanent structural applications
- Non-pick joint sealant
- Trafficable joint sealant
- Automotive/marine structural adhesive

COHESIVE STRENGTH ★★★★★
ELASTICITY ★★★★★

Hi Power Extreme Structural Adhesive



Features:

- Low VOC
- Outstanding UV resistance
- Very high flexible bond strength
- High immediate grab strength
- Tough and durable
- Paintable (instantly with most paints)
- Excellent primer-less adhesion

Uses:

- Permanent structural applications
- Extreme vibration applications
- Extreme deformation applications
- Automotive/marine structural adhesive

COHESIVE STRENGTH ★★★★★
ELASTICITY ★★★★★

Adheseal
The Adhesive and Sealant Specialists

Adheseal Head Office
26 Wolverhampton Street
Stafford, Queensland 4053
Phone: (07) 3356 0000
sales@adheseal.com.au

Adheseal Sunshine Coast
2/18 Kessling Ave
Kunda Park, Queensland 4556
Phone: (07) 5477 0022
sc@adheseal.com.au

www.adheseal.com.au

Adhesives & Sealants

MS Polymers & Hybrids

Coverage Calculation Guide

Step 1 - Calculate litres required

Joint Width (cm) x Joint depth (cm) x Joint length (cm) ÷ 1000 = Litres required

Step 2 - Calculate product quantity required

Cartridges: Litres required ÷ 0.3 = quantity of cartridges required

Sausages: Litres required ÷ 0.6 = quantity of sausages required

Please note: Allow for approximately 15% wastage

Rating System

The star rating system used in this catalogue is a guide only. Refer to the TDS when selecting suitable products. A product with a cohesive strength rating of 3 stars or more is considered a structural grade adhesive.



Available Colours*



Hi Flex MS Construction

COHESIVE STRENGTH ★★★★★ ELASTICITY ★★★★★

Hi Flex Construction is a high performance MS polymer based hybrid sealant. It cures to form a tough, elastic seal with outstanding UV and weather resistance. It is green star compliant (low VOC) and is suitable for many construction, industrial, marine and automotive applications.

Features

- One component
- Low modulus
- Easy tooling - creamy texture
- Paintable (instantly with most paints)
- Outstanding UV resistance and colour stability
- Low VOC - Green star project compliant
- Non-hazardous - Isocyanate free
- Does not sag or slump in joints up to 30mm
- Excellent primer-free adhesive properties on most substrates

Applications

- Bonding and sealing
- Tilt up and precast joints in buildings and civil structures
- Trafficable expansion joints
- Construction joints
- External walling and cladding joints
- Curtain walling
- Window frame installation
- Sealing penetrations in walls and floors such as ducts and piping
- Retaining walls (above and below grade)

Colour	Size	Code
White	600ml Sausage	HIFLEXCONWH/SSG
Grey	600ml Sausage	HIFLEXCONGR/SSG
Black	600ml Sausage	HIFLEXCONBL/SSG



Available Colours*



Adheseal Hi Flex 40

COHESIVE STRENGTH ★★★★★ ELASTICITY ★★★★★

Hi Flex 40 is a high performance MS polymer based hybrid sealant/adhesive. This tough and durable adhesive / sealant can be used in a wide range of applications such as joint sealing or structural bonding with outstanding UV and weather resistance. It is green star compliant (low VOC) and is suitable for many construction, industrial, marine and automotive applications.

Features

- One component
- Low modulus
- Easy tooling - creamy texture
- Tough and durable
- Paintable (instantly with most paints)
- Outstanding UV resistance and colour stability
- Low VOC (complies with Green Star VOC)
- Non-hazardous - Isocyanate free
- Excellent primer-free adhesive properties on most substrates

Applications

- Tilt up and precast joints in buildings and civil structures
- Trafficable expansion joints
- Construction joints
- External walling and cladding joints
- Curtain walling
- Window frame installation
- Sealing penetrations in walls or floors such as ducts and piping
- Retaining walls (above and below grade)
- Sealing joints in water retaining structures
- Marine manufacturing
- Boat deck sealant
- Automotive body building

Colour	Size	Code
White	290ml Cartridge	HIFLEX40WH/CTG
Grey	290ml Cartridge	HIFLEX40GR/CTG
Black	290ml Cartridge	HIFLEX40BL/CTG

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.



Adheseal Hi Flex 60LS

COHESIVE STRENGTH ★★★★★ ELASTICITY ★★★★★

Hi Flex 60LS is an extremely tough and durable MS Polymer based adhesive / sealant. With a high shore A hardness this is a high performance product suitable for many uses from high structural strength adhesive applications to joint sealing.



Available Colours*



Features

- One component
- Structural Strength Adhesive
- Trafficable
- Paintable (instantly with most paints)
- Outstanding UV resistance and colour stability
- Pick Resistant
- Low VOC (complies with Green Star VOC)
- Non-hazardous - Isocyanate free
- Excellent primer-free adhesive properties on most substrates

Applications

- Structural bonding
- Joint sealing
- Non-pick sealant suitable for prisons, schools and public access areas
- Marine manufacturing
- Boat deck sealant
- Automotive body building

Colour	Size	Code
White	600ml Sausage	HIFLEX60LSWH/SSG
Grey	600ml Sausage	HIFLEX60LSGR/SSG
Black	600ml Sausage	HIFLEX60LSBL/SSG



Adheseal Hi Power

COHESIVE STRENGTH ★★★★★ ELASTICITY ★★★★★

Adheseal Hi-Power is a hybrid adhesive with outstanding initial grab strength. It is a powerful structural strength adhesive that can be used for bonding materials exposed to extreme applications such as vibrations or deformation in building and industrial applications. Adheseal Hi-Power has excellent adhesion to most common building materials.



Available Colours*



Features

- High performance adhesive
- Very high flexible bond strength
- Exceptional green strength
- Excellent shear strength
- Does not contain isocyanates, silicone or solvent
- Tough and durable
- Easy to tool and finish
- Excellent colour stability and UV resistance
- Paintable (instantly with most paints)
- Exceptional weather resistance
- Low VOC (complies with Green Star VOC)

Applications

- Applications exposed to excessive vibration or deformation
- Structural bonding
- Applications when a flexible structural bond is required
- Construction and industrial
- Marine manufacturing
- Automotive body building

Colour	Size	Code
White	290ml Cartridge	HIPWRWH/CTG
White	600ml Sausage	HIPWRWH/SSG

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.

Adheseal

S-100 Sanitary & Tile Silicone

Bathrooms / Kitchens / Glazing

High Performance Sanitary Grade



Mould resistant



Excellent weathering resistance



Low VOC



UV stable



Internal & external applications



Highly flexible

S-100 Sanitary Silicone is a high performance sanitary grade neutral cure silicone sealant. It is suitable for many applications including sealing bathrooms and kitchens and also glazing.

Features

- Resistant to mould and mildew growth
- Forms a durable, flexible waterproof seal
- Suitable for internal and external applications
- UV stable
- Excellent weather resistance
- It has excellent adhesion to most common building and engineering materials such as glass, aluminium, steel, ABS, stainless, tiles, marble and granite etc.
- Low VOC (complies with Green Star VOC)

Available Colours*



Clear



Stark White



Off White



Ivory



Travertine



Tile Grey



Eva Grey



Ashville Grey



Koala Grey



Dark Grey

Adheseal
The Adhesive and Sealant Specialists

Adheseal Head Office
26 Wolverhampton Street
Stafford, Queensland 4053
Phone: (07) 3356 0000
sales@adheseal.com.au

Adheseal Sunshine Coast
2/18 Kessling Ave
Kunda Park, Queensland 4556
Phone: (07) 5477 0022
sc@adheseal.com.au

*Colours shown are a representation only. Please refer to the actual product sample for exact colours.

www.adheseal.com.au

Adhesives & Sealants

Silicones

Coverage Calculation Guide

Step 1 - Calculate litres required

Joint Width (cm) x Joint depth (cm) x Joint length (cm) ÷ 1000 = Litres required

Step 2 - Calculate product quantity required

Cartridges: Litres required ÷ 0.3 = quantity of cartridges required

Sausages: Litres required ÷ 0.6 = quantity of sausages required

Please note: Allow for approximately 15% wastage



Available Colours*



Adheseal Roof & Gutter Silicone

Neutral cure, general purpose silicone sealant with fungicides, to reduce the growth of mould and mildew.

Features

- Excellent weathering resistance and durability
- UV stable
- Provides excellent bonding, without primer, to most materials used in the building and engineering industries such as glass, aluminium, steel, ABS, stainless steel, anodised products, concrete and wood
- Low VOC (complies with Green Star VOC)


Applications

- Bonding and sealing
- Weatherproofing
- General purpose applications

Colour	Size	Code
Translucent	300ml Cartridge	SILADRGR/CTG
White	300ml Cartridge	SILADRGRW/CTG
Light Grey	300ml Cartridge	SILADRGLG/CTG
Black	300ml Cartridge	SILADRGRBL/CTG



Available Colours*



Adheseal S-100 Kitchen & Bathroom Silicone

A high performance sanitary grade neutral cure silicone sealant. It is suitable for many applications including sealing bathrooms and kitchens and also glazing.

Features

- Resistant to mould and mildew growth
- Forms a durable, flexible waterproof seal
- Suitable for internal and external applications
- UV stable
- Excellent weather resistance
- It has excellent adhesion to most common building and engineering materials such as glass, aluminium, steel, ABS, stainless, tiles, marble and granite etc.
- Low VOC (complies with Green Star VOC)

Colour	Size	Code
Clear	300ml Cartridge	SILADS100CL/CTG
Stark White	300ml Cartridge	SILADS100WH/CTG
Off White	300ml Cartridge	SILADS100OW/CTG
Ivory	300ml Cartridge	SILADS100IV/CTG
Travertine	300ml Cartridge	SILADS100TV/CTG
Tile Grey	300ml Cartridge	SILADS100TG/CTG
Eva Grey	300ml Cartridge	SILADS100EG/CTG
Ashville Grey	300ml Cartridge	SILADS100AG/CTG
Koala Grey	300ml Cartridge	SILADS100KG/CTG
Dark Grey	300ml Cartridge	SILADS100DG/CTG



Available Colours*



Adheseal N80 Silicone

A versatile architectural grade, neutral curing silicone sealant/adhesive.

Features

- High performance, architectural grade sealant
- Excellent weathering resistance and durability
- UV stable
- Provides excellent bonding, without primer, to most materials used in the building and engineering industries such as glass, aluminium, steel, ABS, stainless steel, anodised products, concrete and wood
- Low VOC (complies with Green Star VOC)

Applications

- Glazing butt joints
- Mirrors
- Bonding and Sealing
- Weatherproofing
- Construction architectural marine and manufacturing applications

Colour	Size	Code
Translucent	300ml Cartridge	SILADN80TR/CTG
Grey	300ml Cartridge	SILADN80GR/CTG
Black	300ml Cartridge	SILADRGRBL/CTG

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.



Available Colours*



Adheseal Facade 3200

Adheseal Facade 3200 is a neutral cure, versatile, architectural grade hybrid silicone sealant that exhibits outstanding physical properties for projects and general building construction. It has excellent weathering resistance, durability, sealing and primer-less adhesive properties to most common substrates. Once cured, Facade 3200 bonds firmly to many substrates and gives a high performance seal for curtain walls, composite facades, weatherproofing and non-structural applications.

Features

- High performance, architectural grade sealant
- Excellent weathering resistance and durability
- No primer required (in most applications)
- Excellent UV Resistance
- Low VOC (complies with Green Star VOC)

Applications

- Window and door perimeter joints
- Weatherproofing, movement joints; facade panels, composite panel joints, metal cladding, glazing and caulking
- Non-structural curtain walls and building construction applications
- Sign installation

Colour	Size	Code
White	590ml Sausage	FACADEWH/SSG
Matt Grey	590ml Sausage	FACADEMGR/SSG
Matt Black	590ml Sausage	FACADEMBL/SSG



Available Colours*



Sealants Australasia N-10 Silicone

Designed for general purpose glazing and sealing applications where long term reliability is required. Weathering and UV resistance is excellent.

Features

- Outstanding UV and Weather Resistance
- Excellent Adhesion
- Excellent UV Resistance

Colour	Size	Code
Off White	300ml Cartridge	SILSN10OW/CTG
Sandstone	300ml Cartridge	SILSN10SST/CTG
Aluminium Grey	300ml Cartridge	SILSN10AL/CTG
Dark Grey	300ml Cartridge	SILSN10DG/CTG
Brown	300ml Cartridge	SILSN10BRN/CTG



Available Colours*



Sealants Australasia Sanitary Silicone

SA Sanitary Silicone Sealant is a one part, 100% oxime, neutral curing adhesive / sealant containing anti-fungicide to prevent mould growth. It resists mildew when exposed to prolonged hot and humid environments and is suitable for sealing in kitchens, vanities, bathrooms, shower screens and any other wet area applications.

Features

- Outstanding UV and Weather Resistance
- Excellent Adhesion
- Excellent UV Resistance

Colour	Size	Code
Translucent	300ml Cartridge	SILSANTRN/CTG
White	300ml Cartridge	SILSANWH/CTG
Ivory	300ml Cartridge	SILSANIV/CTG
Stone Beige	300ml Cartridge	SILSANSB/CTG
Tile Grey	300ml Cartridge	SILSANTG/CTG
Light Grey	300ml Cartridge	SILSANLG/CTG
Mid Grey	300ml Cartridge	SILSANMG/CTG

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.

N-60 Silicone - Sealants Australasia

An architectural grade, high bodied, non-slump silicone which has high green strength and an extra fast cure. Designed for applications such as butt joints, colonial bars, commercial glazing and roof mounted solar panels.



Available Colours*




Features

- Fast Cure
- High Strength
- Architectural Grade
- Excellent Adhesion
- Outstanding Weatherability

Colour	Size	Code
Translucent	300ml Cartridge	SILSN60TRN/CTG
White	300ml Cartridge	SILSN60WH/CTG
Grey	300ml Cartridge	SILSN60GR/CTG
Aluminium	300ml Cartridge	SILSN60AL/CTG
Black	300ml Cartridge	SILSN60BK/CTG



Available Colours*



Sealants Australasia Silicone N

Premium architectural grade, neutral cure silicone sealant/adhesive. It is fast curing, highly elastic and has excellent performance with glazing and construction applications.

Colour	Size	Code
Translucent	300ml Cartridge	SILNTR/CTG
White	300ml Cartridge	SILNWH/CTG
Black	300ml Cartridge	SILNBL/CTG

Sealants Australasia Sealproof

Sealproof Silicone is a premium structural grade, neutral cure silicone sealant/adhesive. It has a high strength and is suitable for a wide variety of applications including structural glazing and butt joints. Sealproof was specially designed for use with many plastics including acrylic and polycarbonate (Lexan) - commonly used as a marine windscreen.



Available Colours*



Colour	Size	Code
White	300ml Cartridge	SILPRUWH/CTG
Grey	300ml Cartridge	SILPRUGR/CTG
Black	300ml Cartridge	SILPRUBL/CTG

Sealants Australasia Contractors

One part 100% acetic curing adhesive / sealant. It is an easy to use silicone designed for general purpose glazing and sealing applications where long term reliability is required. Weathering and UV resistance is excellent.



Available Colours*



Features

- Fast Curing
- Outstanding UV and Weather Resistance
- Excellent Adhesion
- Excellent UV Resistance

Colour	Size	Code
Translucent	300ml Cartridge	SILCONTTR/CTG
White	300ml Cartridge	SILCONTWH/CTG
Black	300ml Cartridge	SILCONTBL/CTG

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.

Pasco 911 Glazing Silicone

Pasco Hypersil 911 is a high performance neutral cure silicone sealant which cures to form a tough and flexible waterproof seal. Suitable for a wide range of glazing, weatherproofing and specialist trade applications.



Available Colours*



Colour	Size	Code
Sandstone	300ml Cartridge	SILP911SST
Beige	300ml Cartridge	SILP911BEIGE
Chocolate	300ml Cartridge	SILP911CHOC
Stone Grey	300ml Cartridge	SILP911STGR
Volcano	300ml Cartridge	SILP911VOL

Pasco 912 Silicone

Pasco Hypersil 912 is a high performance neutral cure sanitary grade silicone sealant which cures to form a tough and flexible waterproof seal with the added advantage of resisting the growth of mould and mildew.



Available Colours*



Colour	Size	Code
White	300ml Cartridge	SILP912WHITE
Off White	300ml Cartridge	SILP912OFFWH
Magnolia	300ml Cartridge	SILP912MAGNO
Light Ivory	300ml Cartridge	SILP912LTIVORY
Almond Ivory	300ml Cartridge	SILP912ALMOND
Travertine	300ml Cartridge	SILP912TRAV
Caramel	300ml Cartridge	SILP912CARMEL
Teak	300ml Cartridge	SILP912TEAK
Mushroom	300ml Cartridge	SILP912MUSH
Beige Grey	300ml Cartridge	SILP912BEIGEGR
Tile Grey	300ml Cartridge	SILP912TGR
Light Grey	300ml Cartridge	SILP912LTGREY
Pewter	300ml Cartridge	SILP912PEWTER
Bluestone	300ml Cartridge	SILP912BLUST
Slate Grey	300ml Cartridge	SILP912SLATE

Bostik 6S Silicone

6S is a one component, neutral cure, silicone sealant with a mould inhibitor.

Features

- Sealing showers, bathrooms, laundries and other wet areas.
- Sealing architectural joints



Available Colours*



Colour	Size	Code
Gloss White	310ml Cartridge	SILZBGLWH/CTG
Antique White	310ml Cartridge	SILZBANWH/CTG
Titanium	310ml Cartridge	SILZBTIT/CTG
Mid Grey	310ml Cartridge	SILZBMIDGR/CTG
Silver Ash	310ml Cartridge	SILZBSILASH/CTG
Charcoal	310ml Cartridge	SILZBCHAR/CTG
Taupe	310ml Cartridge	SILZBTAUP/CTG
Pewter	310ml Cartridge	SILZBPEWTCTG

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.



Available Colours*



Dow Corning 888

Dow Corning 888 Silicone is a low-modulus silicone joint sealant that is suitable for new and remedial joint sealing applications. It provides outstanding UV and weathering resistance and is excellent for joint sealing applications such as highway, airport and bridge joints and environments where high movement occurs.

Features

- + 100 % / -50% joint movement
- Trafficable
- Suitable for saw cuts
- Suitable for roads and runways

Colour	Size	Code
Grey	600ml Sausage	SILDC888/SSG



Available Colours*




Sikasil WS-305CN

Sikasil WS-305 CN is a neutral curing silicone sealant with a high movement capability. It has excellent UV and weathering resistance and is commonly used for weatherproofing and sealing many substrates such as glass, metals, coated and painted metals, plastics and wood.

Colour	Size	Code
Black	600ml Sausage	SIKASILWS305BL



Available Colours*



Sikapool

Sikapool is a one-part neutral curing silicone sealant for use in swimming pools and permanently wet areas.

Features

- Very high water resistance
- High chlorine resistance (as required in swimming pools due to use of disinfecting solutions)
- Extremely high resistance to fungal attack
- Excellent UV and weathering resistance
- High tear resistance
- Non-corrosive
- High elasticity and flexibility

Colour	Size	Code
Transparent	300ml Cartridge	SIKAPOOLTR/CTG
White	300ml Cartridge	SIKAPOOLWH/CTG
Grey	600ml Sausage	SIKAPOOLGR/SSG

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.

Adhesives & Sealants

Fire Rated Sealants



Available Colours*



Adheseal Firefill

Firefill is a high performance water based acrylic fire-rated joint sealant.

Features

- Up to 4-hour fire rating (tested in accordance with AS1530 Pt 4: 2014 Section 2,4,10. BS476: Pt 20: 1987: AS4072.1-2005 as appropriate)
- Outstanding UV and weather resistance
- Suitable for exterior and interior applications
- Water clean up
- Easy workability and application
- Joint movement capability +/- 20%
- Paintable
- Excellent adhesion to metal, concrete, plasterboard and cable coverings
- Outstanding acoustic properties
- Low VOC (complies with Green Star VOC)

Applications

- Expansion joints
- Gap sealing wall penetrations such as ducts, pipes or cables
- Expansion and construction joints
- Tilt-up construction
- Brick and blockwork
- Plasterboard
- Fibre cement sheet
- Acoustic sealant (suitable for cinemas and sound booths etc)

Colour	Size	Code
Grey	600ml Sausage	FIREFILL/SSG
Grey	10L Pail	FIREFILL/10



Available Colours*



Bostik Fire Ban 1

Bostik Fireban One is a one part, fire rated, polyurethane joint sealant. When cured it will form a tough, flexible seal with good weather resistance.

Features

- Up to 4-hour fire rating
- Suitable for exterior and interior applications
- Paintable
- Excellent adhesion to metal, concrete, plasterboard and cable coverings
- Excellent acoustic properties

Applications

- Expansion joints
- Tilt-up construction
- Brick and blockwork
- Plasterboard
- Fibre cement sheet
- Acoustic sealant (suitable for cinemas and sound booths etc)

Colour	Size	Code
Grey	600ml Sausage	FIREBAN/SSG



Available Colours*



Sika Firerate PU

Firerate PU is a one component, moisture cure polyurethane joint sealant. It is designed to cure into a fire rated, elastic weatherproof seal.

Features

- Up to 4-hour fire rating
- Suitable for exterior and interior applications
- Paintable
- Excellent adhesion to metal, concrete, plasterboard and cable coverings
- Excellent acoustic properties

Applications

- Expansion joints
- Tilt-up construction
- Brick and blockwork
- Plasterboard
- Fibre cement sheet
- Acoustic sealant (suitable for cinemas and sound booths etc)

Colour	Size	Code
Grey	600ml Sausage	FIRERATEPU/SSG

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.

Adhesives & Sealants

Acrylics / Water Based Sealants



Everflex 250 JS

Everflex 250 JS is a specially formulated acrylic joint sealant that provides good weather resistance and flexibility in joints and gaps. It has good flexibility (+25%) and is designed for sealing exterior and interior joints that are subject to movement.

Applications

- Precast panels and tilt up construction
- Blockwork
- Brickwork
- Timber
- Metal
- Plasterboard
- Acoustic perimeter sealant
- General cracks and gaps

Colour	Size	Code
Grey	600ml Sausage	EV250JS/SSG
Grey	10L Pail	EV250JS/10



Everflex JS

Everflex JS is a premium, highly elastic, hybrid acrylic, joint sealant. It has exceptional UV and weathering resistance and excellent adhesion to most building materials whilst still maintaining its superb elasticity.

Features

- Water clean up
- Excellent Slump Resistance
- Capable of + / - 50% Joint Movement
- Superior Adhesion
- Non-Staining
- Non-Toxic
- Non-Hazardous
- No Isocyanates
- Paintable
- Low VOC (complies with Green Star VOC)

Applications

- Precast panels and tilt up construction
- Blockwork
- Brickwork
- Timber
- Metal
- Windows and doors
- Many plastics including Acrylic and Polycarbonate.

Colour	Size	Code
Grey	600ml Sausage	EEVJS/SSG
Grey	10L Pail	EVJS/10



Allflex 101

Allflex 101 is a specialised hybrid acrylic joint sealant which has exceptional resistance to weathering. It cleans up easily with water and has superb adhesion and elasticity. It is commonly used as an alternative to silicone sealants in applications such as beading glass into timber in glazing and timber joinery.

Features

- Excellent Weathering
- Water clean-up
- Non-Staining
- Non-Toxic
- Paintable
- Non-Hazardous
- Superior Adhesion (no priming)
- Low VOC (complies with Green Star VOC)
- UV Resistant

Colour	Size	Code
Clear	300ml Cartridge	ALLFLCLR/CTG

Adhesives & Sealants

Flooring Adhesives



Adheseal Parquetry PS1300

Parquetry PS1300 is a premium, flexible, MS polymer based timber flooring adhesive that contains neither isocyanates nor silicones. It can be used to adhere most types of wood, parquetry strip and sheet timber flooring systems to concrete, timber and over existing floors.

Features

- Single component
- Low modulus
- Easy to use
- No isocyanates
- Excellent bond strength and flexibility
- Low VOC (complies with Green Star VOC)

Colour	Size	Code
Beige	21kg Pail	PARQ/21



Adheseal PU50 Parquetry

PU50 Parquetry is a flexible one component, moisture curing, polyurethane, timber flooring adhesive. It will adhere most types of wood, parquetry, strip and sheet timber flooring systems to concrete, timber and over existing floors.

Features

- Easy to spread
- Gun Grade
- Medium modulus
- Remains flexible
- Excellent bond strength
- Low VOC (complies with Green Star VOC)

Colour	Size	Code
Grey	600ml Sausage	PARQ/SSG



Bostik Ultraset SF

Ultraset SF is a flexible one component, moisture curing, polyurethane, timber flooring adhesive. It is formulated to adhere most types of wood, parquetry, strip and sheet timber flooring systems to concrete, timber and over existing floors.

Features

- Easy to spread
- Low modulus
- Remains flexible
- Excellent bond strength

Colour	Size	Code
Brown	600ml Sausage	ULTRASET/SSG
Brown	16kg Pail	ULTRASET/16



Adheseal Everbond SG

Everbond SG is a synthetic rubber based adhesive that is particularly suited for interior and exterior carpet as well as synthetic grass laying applications.

Colour	Size	Code
Green	20L Pail	EVERBOND SG/20

Sikabond T55J

SikaBond-T55 (J) is a one-part polyurethane adhesive for direct elastic bonding of timber floors. It adheres to most types of wood, parquet, strip and sheet timber flooring systems to concrete, timber and over existing floors.



Features

- One part, easy to use
- Low modulus
- Excellent elasticity
- Quick tack free time

Colour	Size	Code
Brown	600ml Sausage	SIKAT55J/SSG
Brown	16kg Pail	SIKAT55J/16

Adheseal Multi-Grip Construction Adhesive

Newly formulated premium grade solvent free Builder's Nails with outstanding initial grab properties.



Features


- Suitable for interior and exterior applications
- Paintable
- High initial grab
- Does not become brittle
- Water clean up
- Excellent UV resistance
- Complies with Green Star VOC

Applications

- General purpose construction adhesive
- General purpose gap filling
- Bonding timber to studs and joists
- Flooring and wall systems
- Bonding timber, metal concrete and most common construction materials
- Cornice adhesive
- Installation of wall sheeting, internal and external mouldings
- Bond polystyrene foam components





Colour	Size	Code
White	600ml Sausage	MULTIGRIP/SSG




Multi-Tack

Builders' Nails / Gap Filler / Joint Sealant






Low VOC




3 in 1 Multi-Use

High Strength Construction Adhesive


Multi-Tack is a newly formulated, green star compliant, solvent free multi purpose construction adhesive, ideal for use as an adhesive, joint sealant or gap filler.




Internal & external use




Flexible




Water cleanup



Paintable



High initial grab



UV stable

Adheseal

Hi-Power

Automotive / Construction / Industrial / Marine

Extreme Strength Structural Adhesive



Low
VOC



Solvent
Free



Isocyanate
Free



Easy tooling &
finishing



Excellent colour
stability



Excellent primer-less
adhesion



Internal & external
applications



Paintable



Excellent UV
resistance

Adheseal Hi-Power is a hybrid adhesive with outstanding initial grab strength. It is a powerful structural strength adhesive that can be used for bonding materials exposed to extreme applications such as vibrations or deformation in building and industrial applications.

Features

- High performance adhesive
- Very high flexible bond strength
- Exceptional green strength
- Excellent sheer strength
- Does not contain isocyanates, silicone or solvent
- Tough and durable
- Easy to tool and finish
- Excellent colour stability and UV resistance
- Paintable (instantly with most paints)
- Exceptional weather resistance



Adheseal
The Adhesive and Sealant Specialists

Adheseal Head Office
26 Wolverhampton Street
Stafford, Queensland 4053
Phone: (07) 3356 0000
sales@adheseal.com.au

Adheseal Sunshine Coast
2/18 Kessling Ave
Kunda Park, Queensland 4556
Phone: (07) 5477 0022
sc@adheseal.com.au

Adhesives & Sealants
PVA Glues



General Purpose PVA - Everbond

A commercial grade, PVA based adhesive suitable for general interior woodworking and joinery applications.

Features

- High strength
- Clear drying
- Non-toxic
- Non-staining
- Water clean up

Size	Code
5L	PVAGP/5
20L	PVAGP/20
200L	PVAGP/200



Melamine PVA Adhesive - Everbond

A water-borne synthetic resin for bonding difficult surfaces in shop-fitting, joinery and kitchen applications. Melamine adhesive is commonly used for bonding melamine-laminated boards to timber and end-grain particleboard. It has excellent adhesion to a wide variety of difficult to bond substrates such as timbers, ceramics and several plastics.

Size	Code
5L	PVAMEL/5
20L	PVAMEL/20
200L	PVAMEL/200



Cross Link PVA Adhesive - Everbond

A premium quality, water resistant cross linking PVA adhesive that is used when a higher strength bond is required. It is suitable for both internal and external applications.

Features

- High strength
- Sandable
- Fast setting
- Dries clear
- Water clean-up
- Water resistant (D3 standard)
- Suitable for interior & exterior applications

Size	Code
5L	PVAXL/5
20L	PVAXL/20
200L	PVAXL/200



Cross Link 3500 Roller Grade PVA - Everbond

A high performance, lower viscosity, cross-linking PVA adhesive commonly used for laminating, door pressing and veneering applications.

Size	Code
20L	PVAXLRG/20
200L	PVAXLRG/200

*Colours are not exact. Colours shown are a representation only. Please refer to the actual product sample.

Adhesives & Sealants

Contact Adhesives



SP-230 Spray Contact Adhesive - Everbond

A premium spray contact adhesive with very high heat resistance and fast initial grab.

Uses

- Bonding laminates in cabinet making and shop-fitting applications
- Motor and marine trimming applications
- Bonding surfaces such as timber, MDF and particleboard, metal, urethane foam, cloth backed and polyester backed vinyl, leather, carpet and polyurethane foam in motor trimming applications

Size	Colour	Code
20L	Natural	CONTSP230N/20
200L	Natural	CONTSP230N/200
20L	Red	CONTSP230R/20
200L	Red	CONTSP230R/200



Brush Contact Adhesive - Everbond

A brush contact adhesive with high heat resistance and fast initial grab.

Suitable for

- Timber, MDF and particleboard
- Metal
- Urethane foam
- Cloth backed and polyester backed vinyl
- Leather
- Carpet
- Polyurethane foam in motor trimming applications

Size	Colour	Code
1L	Natural	CONTRUSH/1
4L	Natural	CONTRUSH/4
20L	Natural	CONTRUSH/20



Ultra-Clear Brush Contact Adhesive - Everbond

A high performance, clear, brushable contact adhesive designed for applications where glue lines are preferred not to be visible. It is commonly used in applications such as the manufacturing process of neoprene drink coolers.

Size	Colour	Code
20L	Ultra Clear	CONTRUSHCL/20



Styrobond ST Contact Adhesive - Everbond

A specialised spray contact adhesive designed for bonding polystyrene foam to hardboard, aluminium and surfaces that may be affected by the solvents in standard contact adhesives.

Size	Colour	Code
20L	Natural	STYROSTN/20
200L	Natural	STYROSTN/200
20L	Green	STYROSTGR/20
200L	Green	STYROSTGR/200



Beading Adhesive - Everbond

A natural rubber based adhesive suitable for bonding surfaces such as leather, rubber, and many other materials, where a soft bond is initially required. Beading adhesive has good initial tack and bonding strength and has good resistance to water, humidity, detergents, non-aromatic fuels, oils and ageing.

Suitable applications

- Assembling Leather Jackets, where some re-positioning may be required
- Attaching sanding discs, or other 'temporary' bonding situations


Size	Colour	Code
20L	Translucent	BEADING/20



2P Contact Adhesive Additive - Everbond

A crosslinking additive that is designed to increase the bond strength, heat resistance and water resistance of suitable contact adhesives. It is ideal for bonding rubber and specialised applications.

Size	Code
50ml	CONT2P/50



Unobond

Woodworking / Outdoor / Marine

Super Strength Polyurethane Adhesive



Unobond is a single component, quick setting, moisture cured polyurethane adhesive. Commonly used for structural applications. It has excellent water resistance and provides an extremely strong structural bond.

- 
Low VOC
- 
Solvent Free
- 
Fast Setting
- 
Heat resistant
- 
Acid & chemical resistant
- 
Classified D4 water resistant
- 
Paintable and sandable
- 
Super strong bond
- 
Structural strength



Adheseal

Cordless Caulking Gun

Professional / Lithium Ion Power

The Adheseal Cordless Caulking Gun is designed with the user in mind. Light weight for easy use and dual flow controls deliver a smooth and steady action for precise application.



The professionals' choice

Features

- Anti drip mechanism
- Low power consumption
- High output thrust
- Variable speed trigger
- Maximum speed control
- LED auxiliary light
- Light weight

Kit contains

- 600ml sausage sealant gun
- 2 x lithium ion batteries
- Battery charger
- Carry case



Adheseal
The Adhesive and Sealant Specialists

Adheseal Head Office
26 Wolverhampton Street
Stafford, Queensland 4053
Phone: (07) 3356 0000
sales@adheseal.com.au

Adheseal Sunshine Coast
2/18 Kessling Ave
Kunda Park, Queensland 4556
Phone: (07) 5477 0022
sc@adheseal.com.au

www.adheseal.com.au

Adhesives & Sealants

Megapoxy Epoxies / Grouts / Pigments

Megapoxy

OFFICIAL DISTRIBUTOR



Adheseal has proudly been the official Queensland distributor of Megapoxy products since 1989.

Regarded as Australia's top selling construction epoxy products, Megapoxy is used extensively across a wide range of industries in Australia and global markets and has been providing effective adhesive solutions for over thirty years.

Currently there are over 300 Megapoxy products available such as construction adhesives for manufacturing, surface coatings, industrial compounds for civil engineering, mining, electrical and general manufacturing industries. Listed below are the most common Megapoxy products used. Ask your Adheseal representative which product best suits your application.

Details may have changed since printing. Please check with your Adheseal representative.

Megapoxy Megabond

Structural Epoxy Paste Adhesive

Features

- Suitable for bonding stone and tile to masonry surfaces
- Creamy white colour
- Can be coloured using Megapoxy coloured pigment pastes
- Easy to mix and spreads readily with a notched trowel
- High impact and chemical resistance

Colour	Size	Code
Grey	4L Kit	MPMEGAB/4
Grey	20L Kit	MPMEGAB/20

Megapoxy P1

Gap Filling / Structural Epoxy Adhesive Paste

Features

- Ideal for concrete structural bonding, filling and repair applications
- Commonly used in pipeline and civil construction
- Suitable for potable water applications
- 60 minute work time / 24 hour cure time

Colour	Size	Code
Grey	1L Kit	MPP1/1
Grey	4L Kit	MPP1/4
Grey	20L Kit	MPP1/20

Megapoxy 69

High Strength Impact Resistant Epoxy Gel / Liquid Adhesive

Features

- Translucent non-sag gel type epoxy
- Ideal for structural bonding to metals, concrete, masonry, timber, assembly of granite and marble fabrications, and many other civil engineering applications
- Suitable for timber joinery and in the marine environment applications
- Structural bond strength
- Retains its high strength after repeated high impact forces

Colour	Size	Code
Opaque Gel	1L Kit	MP69/1
Opaque Gel	4L Kit	MP69/4
Opaque Gel	20L Kit	MP69/20
Opaque Liquid	4L Kit	MP69LQ/4
Opaque Liquid	20L Kit	MP69LQ/20

Megapoxy 84

Epoxy Paste Adhesive for Ceramic Tile Linings

Features

- Suitable for fixing high alumina ceramic tile linings to steel or concrete for applications where elevated temperatures will be encountered

Colour	Size	Code
Pail Blue	2.5L Kit	MP84/2.5

Megapoxy PM *(Paste, medium work time)*

Gap Filling / Structural Adhesive Epoxy Paste Adhesive

Features

- Commonly used for structural bonding, gap filling and repairs on concrete, marble and granite and other construction materials.
- Tensile and compressive strength superior to concrete
- Very good chemical resistance
- 45 minute work time / 24 hour cure time

Colour	Size	Code
Natural (white)	1L Kit	MPPMWH/1
Grey	4L Kit	MPPMGR/4
Natural (white)	4L Kit	MPPMWH/4
Grey	20L Kit	MPPMGR/20
Natural (white)	20L Kit	MPPMWH/20

Megapoxy PF *(Paste, fast work time)*

Rapid Set Gap Filling / Structural Epoxy Paste / Gel / Liquid Adhesive

Features

- Commonly used for structural bonding, gap filling and repairs on concrete, marble and granite and other construction materials.
- Suitable for immediate on the spot emergency repairs to tanks, pipes, machinery, concrete structures
- Tensile and compressive strength superior to concrete
- Very good chemical resistance
- 5 minute work time / 60 minute cure time

Colour	Size	Code
Natural (white)	1L Kit	MPPFWH/1
Grey	4L Kit	MPPFGR/4
Natural (white)	4L Kit	MPPFWH/4
Grey	20L Kit	MPPFGR/20
Natural (white)	20L Kit	MPPFWH/20
Opaque Gel	4L Kit	MPPFGEL/4
Opaque Gel	20L Kit	MPPFGEL/20
Opaque Liquid	4L Kit	MPPFLIQ/4
Opaque Liquid	20L Kit	MPPFLIQ/20

Megapoxy H

Low Viscosity Hydrophilic Epoxy Resin Liquid

Features

- High strength epoxy for bonding and anchoring steel reinforcement, starter bars and tie bars into concrete, brick work and stone
- Wet to dry binding agent (new to old concrete)
- Suitable for use in damp conditions
- Ideal for sealing and/or waterproofing concrete structures and can be mixed with sand to make epoxy mortar systems
- Addition of pigments can also be added for industrial floor coatings

Colour	Size	Code
Natural (Clear)	4L Kit	MPH/4
Natural (Clear)	20L Kit	MPH/20
Grey N35	4L Kit	MPHGR/4
Grey N35	20L Kit	MPHGR/20
Pacific Blue	4L Kit	MPHPB/4
Pacific Blue	20L Kit	MPHPB/20

Megapoxy H Rapid

Rapid Set Low Viscosity Hydrophilic Epoxy Resin Liquid

Features

- Rapid set high strength epoxy for repairs and coatings in areas where prolonged shutdowns or interruptions to traffic are not desired
- Suitable for use in damp conditions
- Ideal for sealing and/or waterproofing concrete structures and can be mixed with sand to make mortar systems
- Addition of pigments can also be added for industrial floor coatings
- Pot life 8 minutes / Initial cure 30 - 45 minutes

Colour	Size	Code
Natural (Clear)	4L Kit	MPHRAP/4
Natural (Clear)	20L Kit	MPHRAP/20

Megapoxy HT

Non-Sag Hydrophilic Epoxy Resin

Features

- High strength epoxy
- Suitable for applications overhead, vertical or inclined surfaces
- Suitable for use in damp conditions
- Non-sag characteristic assists greatly in underwater applications

Colour	Size	Code
Grey	4L Kit	MPHT/4
Grey	20L Kit	MPHT/20

Megapoxy HX

Extra Low Viscosity Hydrophilic Epoxy Resin Liquid

Features

- Suitable for repair of cracked concrete by gravity penetration or low pressure injection impregnation of porous substrates such as masonry and timber
- Suitable for use in damp conditions

Colour	Size	Code
Natural (Extra Clear)	4L Kit	MPHX/4
Natural (Extra Clear)	20L Kit	MPHX/20

Megapoxy 132

Chemical Resistant Epoxy Coating

Features

- Megapoxy 132 is a two-component solvent-less 100% solids epoxy resin
- Heavy duty, protective, chemical resistant epoxy coating suitable for decorative floor and wall cladding
- Suitable for garage floors, warehouse or factory floors and can also be used to create a trowel-able mortar for screeding floors

Colour	Size	Code
Clear	15L Kit	MP132CL/15
Clear	30L Kit	MP132CL/30
Grey - N35	15L Kit	MP132GR/15
Grey - N35	30L Kit	MP132GR/30

Megapoxy 154

High Solids Water Based Liquid Epoxy

Features

- Forms a tough impervious coating with a matte finish
- Excellent adhesion to wet or dry surfaces including freshly poured concrete
- Commonly used as a vapour barrier on decks and balconies
- Non-flammable / non-toxic
- Cleans up with water

Colour	Size	Code
Grey	20L Kit	MP154/20

Megapoxy L

Multipurpose Liquid Epoxy

Features

- Commonly used for rail and machinery grouting, wear and slip resistant floors, bridge load bearing pads and repair of broken concrete
- Typically mixed with sand for high build structural grouting of machinery

Colour	Size	Code
Clear	18L Kit	MPL/18

Megapoxy HICB

High Impact Crusher Backing

Features

- Epoxy grout for backing crusher parts, grouting machinery, locking bearings, setting anchor bolts and chocking of machinery
- Outstanding compressive strength properties with very low shrinkage

Colour	Size	Code
Blue	10kg Kit	MPHICB/10

Megapoxy MC

Heavy Duty Protective Coating

Features

- Excellent heavy duty protective coating of concrete, steel, timber, masonry etc
- Ideal coating of storage tanks for chemicals, foodstuffs, fuel, garage floors, warehouse floors, pools and more
- Resistant to abrasion, impact and wide range of chemicals (chemical resistance chart available on data sheet)
- Can be applied by airless spray equipment, roller or brush
- Working time approximately 2 hours
- Custom colours available with small batches

Colour	Size	Code
White	5kg Kit	MPMCWH/5
Grey	5kg Kit	MPMCGR/5
Koala Grey	5kg Kit	MPMCKOGR/5
Dark Grey	5kg Kit	MPMCDKGR/5
Pacific Blue	5kg Kit	MPMC PB/5
Safety Yellow	5kg Kit	MPM CYELL/5
Black	5kg Kit	MPMCBLK/5

Megapoxy Megaprene Hot Melt

Joint Sealant

Features

- High movement sealant for horizontal joints in asphaltic and cement concrete, ceramic tiled surfaces and timber decks
- Commonly used for sealing expansion joints in bridges, roads and carparks

Colour	Size	Code
Black	20kg Kit	MPHMELT/20

Megapoxy 57

Heavy Duty Epoxy Grout

Features

- Epoxy grout, suitable for grouting machinery, locking bearings, setting anchor bolts, chocking of machinery, rail track grouting, and bridge bearing pads

Colour	Size	Code
Green	9.4kg Kit	MP57/9

Megapoxy 206

High Strength Epoxy Grout

Features

- Epoxy grout, suitable for grouting machinery, locking bearings, setting anchor bolts, chocking of machinery, rail track grouting, and bridge bearing pads

Colour	Size	Code
Grey	6L Kit	MP206/6

Megapoxy 108

Rapid Set Liquid Binding Epoxy for Pile Splicing

Features

- Typical application is splicing of bridge piles where fast development of high compressive and impact strength is required
- For civil engineering applications where early development of high strength is essential

Colour	Size	Code
Clear Liquid	6L Kit	MP108/6
Clear Liquid	18L Kit	MP108/18

Megapoxy E

High Impact Epoxy for Electrical Castings for Room or Elevated Temperature Service

Features

- Recommended for encapsulation of instrument and lighting transformers, small power transformers and coils, casting electrical switchgear components and for mechanical, chemical resistant applications
- Cured, it has excellent static and dynamic mechanical properties
- Superior electrical and dielectric properties

Colour	Size	Code
Grey	6kg Kit	MPE/6
Grey	30kg Kit	MPE/30

Megapoxy LVS

Low Viscosity Sealer

Features

- Penetrative sealer for concrete, brick and other porous surfaces
- Recommended as a primer for use with Megapoxy MC

Colour	Size	Code
Clear	15L Kit	MPLVS/15

Megapoxy CT5

Installation Compound for Airport Lighting and Inductive Detector Loops

Features

- Cold pour compound for backfilling and encapsulating inductive detector loops, weigh in motion sensors, and aircraft landing lights on asphaltic and concrete roadways
- Sets rapidly in all weather conditions properties

Colour	Size	Code
Black	20L Kit	MPCT5/20

Megapoxy 34

100% Solids Epoxy Resin Formulation

Features

- Recommended for underground cable jointing, encapsulation of instrument transformers, lighting transformers, small power transformers and coils, casting electrical switchgear components
- Suitable for mechanical and chemical resistant applications
- Excellent static and dynamic mechanical properties
- Superior electrical and dielectric properties

Colour	Size	Code
Clear	18kg Kit	MP34/18

Megapoxy 36

Gun Grade Epoxy Adhesive for Bituminous and Concrete Surfaces

Features

- Recommended for bonding reflective markers and other objects to bituminous and concrete surfaces

Colour	Size	Code
Grey	600ml Twin Cartridge	MP36/600
Grey	4L Kit	MP36/4
Grey	20L Kit	MP36/20

Megapoxy 260

Solvent-less Flexible Epoxy Resin

Features

- Suitable for control construction joints, cracks and high impact applications
- Recommended for sealing constructions joints, factory floors, parking structures, warehouse floors, ramps, driveways and more

Colour	Size	Code
Clear	2.5kg Kit	MP260/2.5