

The safe, efficient way to recycle fluorescent lamps.

The Bulb Eater* 3 system not only crushes spent fluorescent lamps of any length, u-tubes, and CFL's into 100% recyclable material, but it also captures over 99.99% of the vapors released! The system, which is mounted to a 55-gallon drum, can hold up to 1350 4' fluorescent lamps. A five-stage filtering process removes hazardous particulates and vapors. A recent study showed non-detectable levels of emitted mercury vapor even after crushing 1700 lamps. A digital control panel gives the operator added security by monitoring various aspects of the machine to better ensure operator safety.

In addition to providing OSHA and ACGIH compliance, the Bulb Eater® 3 frees up valuable storage space normally filled with boxes of spent intact lamps, reduces handling and related labor costs, and typically cuts recycling costs by 50% or more.



The Bulb Eater® 3 with Intelli Technology® was named a "Money Saving Product for 2015" by Buildings Magazine.

Air Cycle Corporation: www.AirCycle.com: 800-909-9709
Visit www.AirCycle.com To Request A Comprehensive Recycling & Product Proposal

Machine Benefits



Eliminate storage hassles - Reduce your needed storage space for lamps by crushing 1350 T8 4' lamps per 55-gallon drum.

Reduce handling - Handle your spent bulbs once. Simply roll your Bulb Eater * lamp crushing system on a 55-gallon drum dolly (sold separately) to the work area or into a storage area. Save roughly 20 hours of labor per 1000 lamps by crushing rather than boxing the lamps!

Safer work environment - EPA studies show an estimated 2-3% accidental breakage rate while boxing lamps prior to pick-up. The 0.001% emission rate from the Bulb Eater amp crushing system provides for less mercury vapor emission. Your workers are not only safer, but your liability is reduced!

Cut costs - By pre-crushing the lamps, facilities are able to save money on their lamp recycling costs. Savings are typically anywhere from a dime to \$1 per lamp!

Nationwide recycling program - Enjoy competitive rates for lamp recycling. Fully permitted trucks are used for transportation and Certificates of Recycling are provided once the lamps are recycled.

Bulb Eater® 3 Certified Training - online, 5-step program covering Bulb Eater® 3 assembly, operations, safety, and maintenance. This program includes a training video, quiz, and certificate of completion.

The Bulb Eater® 3 Specifications

| FEED RATE | 30 lamps per minute (Operator's speed may vary) | | |
|--|---|--|---|
| CRUSHED LAMP CAPACITY *Approximate; individual experience may vary | 1500 1350 875 300 400 550 3,000 | 4' T5 Straight Lamps (0.625" diameter) per drum 4' T8 Straight Lamps (1.0" diameter) per drum 4' T12 Straight Lamps (1.5" diameter) per drum 4' T17 Straight Lamps (2.0" diameter) per drum 8' T12 Straight Lamps (1.5" diameter) per drum 4' T12 U-tube Lamps (1.5" diameter) per drum CFL's (Compact Fluorescent Lamps) per drum | |
| FILTDATION | Exposure In Operator's Breathing Zone | ¹ All air sample results collected during assessment were below the limits of analytical detection, and less than the OSHA PEL (0.1 mg/m³) and ACGIH TLV (0.025 mg/m³) | |
| 1 Air Sampling for Mercury Vapor and Particulates, As tested by Burea Veritas (N.A.) on June 10th, 2013; Results based upon crushing 1700 T12 4' fluorescent lamps and changing the drums out twice in a warehouse and small office with normal ventilation. | Stage 2 | High Capacity Cartridge Filter (Approximate life: 6 drums) | 1 micron @ 99% particle retention |
| | Stage 3 & 5 | H.E.P.A. Filter (Approximate life: 12 drums) | .3 micron @ 99.99% particle retention (Exceeds H.E.P.A. standard @ 99.97%) |
| | Stage 4 | Activated Carbon Filter (1500 hrs. running time) | Calculated life of approximately 1 million lamps |
| CONTROL PANEL | | Control Panel with a Digital LCD Display with <i>Intelli Technology</i> ® | LCD Display for indicating which mode the machine is in and any defaults that might occur. Additional measuring points that assist with machine diagnostics and maintenance/filter change outs. Emergency stop button, start/stop button. |
| TOTAL FULL L | LOAD AMPS 8.5 amps @ 120 vac, 50-60 Hz, single phase; 4.25 amps @240 vac, 50-60 Hz, single phase | | |
| VACUUM | Flow-through type vacuum motor, series wound, brush type, 5.42 amps, 120 vac, 650 w, 60 Hz, single phase | | |
| ETL Certified | UL 73: Issued: 2011/03/02 Ed: 10 UL Standard for Safety for Motor-Operated Appliances CAN/CSA C22.2 No. 68: Issue: 2009/09/01 Ed: 7 Motor-Operated Appliances | | |
| MOTOR | TENV Enclosure, 1/5 h.p. – 2 amp – 120vdc | | |
| Model #'s : Description | | | Call Today |

Model #'s; Description

333-200-120; 110v, BE3 crushes straight, u-bend, & CFL lamps 330-200-240; 220v, BE3 crushes straight, u-bend, & CFL lamps

Call Today! 800.909.9709

Air Cycle Corporation: www.AirCycle.com: 800.909.9709
Visit www.AirCycle.com To Request A Comprehensive Recycling & Product Proposal