

Project :	Date :
Cat. No :	Type :
Notes :	Volts :

Description:

The **NTALB-68R4** LED bar design provides a unique linear lighting solution combining style, performance and durability while reducing construction and operating costs through installation time, energy savings and a maintenance free application. Ideal for recessed installation.

Housing:

The **NTALB-68R4** is a high precision extruded anodized aluminum bar that can accept a low-power to high power LED source

Lens:

Precision fit polycarbonate for indoor use:
PC polycarbonate

Mounting:

Mounts within a recessed section

Application/Installation:

The **NTALB-68R4** bar can be installed recessed under cabinets or within cabinets. Consult factory for damp application or splash area using our silicone jacketed IP67 sources. (**WP**)

Voltage:

12 VDC
24 VDC


Electrical and Electronics:

High quality diodes tested (LM80) and certified life cycle for 60,000 hours (L80). All certified electrical and electronic components have been re-tested over the years for compatibility within products and for specific applications. All products exceed current standards.

Power supply not included, consult factory. Consult the LED specification sheet for the appropriate optional dimmers and controls combination for your project.

Homologation:

Conforms to ANSI/UL standard UL-2108
Certified to CAN/CSA standard 22.2-9.0



NTALB-68R4




Endcap



Ordering Matrix / Specification

Model	Bar	Length	Lens	LED**	Color	Volts
NTALB	68R4	1000 mm 2000 mm XX mm*	PC polycarbonate	UT30 UT30 WP UT60 UT60 WP	VWW (2400K) WW (2700, 3000, 3500K) NW (4100K) WH (5000K) R (Red)*** B (Blue)*** G (Green)*** A (Amber)***	12VDC 24VDC
		* Consult factory for special lengths		HP30 HP60 HP120 HP240	VWW (2400K) WW (3000K) NW (4100K) WH (5000K) R (Red)*** B (Blue)*** G (Green)*** A (Amber)***	
				UT39K CCT (White)	(2700-6500K)****	
				RGB 150		
				RGB 300		



** Consult the LED linear source and driver data sheets for available wattages and characteristics.
*** Consult Factory
**** Color Correction

Natech Industrie

3154 boulevard Industriel, Laval, QC, H7L 4P7 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, info@natechlighting.com

This specification is valid as of 2022-01 and is subject to change without notice. Please confirm with the manufacturer before placing an order.
Copyright 2014 Natech Industrie. All rights reserved.