TRENZ Pilot Plug +IP65



Specifications:

- Weight: 220 g
- Dimensions: 130 x 75 x 28 mm
- GNSS: internal
 - Accuracy RMS <1,2 m
 - Position standards: GPS+GLONASS+GALILEO+BEIDOU+QZSS
 - ▶ GNSS correction standards: A-GPS, EPO Data, D-GPAS
 - SBAS worldwide
- Autonomous rate of turn (ROT)
 - Calibration time: ~ 10 seconds on cold start
 - ▶ ROT accuracy: +/-0.5 °
 - ▶ Roll/Pitch accuracy: +/-0.2
 - > Datasource: Gyroscope, Accelerometer, Magnetometer
 - High accuracy with slow rotations



TRENZ Pilot Plug +IP65

More specifications:

Battery

- ▶ Quick Charge max. 3 hours with USB-C charger
- Runtime: up to 24 hours
- Charging during operations (2 Ports)

AIS

- Superior AIS circuit protection
- AIS check: consistency, checksum
- Decode AIS data: Heading, ROT, Name

Connectivity

- ▶ Wi-Fi: up to 32 clients, 19 dBm,TX, WEP/WPA/WPA2
- Bluetooth: Class 1, BT 4.2
- High range WiFi and Bluetooth (post-Panamax vessels tested)
- USB-C (AIS, charge, notebook)
- Other features
 - Two high strength internal magnets
 - IP 65 protection
 - > Anti vandal metal pushbutton with charging indicator
 - Configuration, sensor test and firmware update via "Pilot Plug Manager App" (iOS, Android, Windows)





Pilot Plug Manager App



Availabe for iOS, Android and Windows

Test sensors

- Configuration of Pilot Plug
- Firmware update





TRENZ Pilot Plug +IP65 package contains:

- Pilot Plug
- USB-C AIS connection cable
- USB-C charging cable
- Charging device
- Watertight transport bag
- Operating instructions
- Quick Start Guide
- Pilot Plug Manager App for iOS, Android and Windows

Service:

- 24 months warranty included
- 12 months warranty extension possible for EUR 125 per unit
- Free firmware updates for improvements, custom firmware possible

