

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Terrain CT30

Product number 7293

Internal identification GHS21531

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Transmission and Hydraulic oil

Uses advised against Non specified unless otherwise stated within this MSDS

1.3. Details of the supplier of the safety data sheet

Supplier Morris Lubricants NZ DISTRIBUTOR:

Castle Foregate Aktron

 Shrewsbury
 14 Railway Road

 Shropshire
 Rangiora 7400

 SY1 2EL
 Ph: 0800 70 10 10

 admin@aktron.co.nz

+44 (0) 1743 232200

+44 (0) 1743 353584 ERMA Approval Code: HSR002606

sds@morris-lubricants.co.uk

1.4. Emergency telephone number

Emergency telephone + National Poison Control Centre 0800 764 766

National emergency telephone United Kingdom: National Poisons Information Service. 0844 892 0111 (UK only, 24/7,

number healthcare professionals only) Ireland: National Poisons Information Centre: 353 (1) 809 2166

(8.00 a.m. to 10.00 p.m. 7 days a week). Healthcare Professionals: +353 (1) 809 2566 (24

hour service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319

Environmental hazards Not Classified

Classification (67/548/EEC or -

1999/45/EC)

2.2. Label elements

Hazard pictograms



Terrain CT30

Signal word Warning

Hazard statements H319 Causes serious eye irritation.

Precautionary statements P264 Wash contaminated skin thoroughly after handling.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention.

Supplementary precautionary P501a Dispose of container/contents to a hazardous or special waste collection point.

statements

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Distillates, hydrotreated heavy paraffinic 60-100%

CAS number: 64742-54-7 EC number: 265-157-1 REACH registration number: 01-

2119484627-25-0014

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified

10-30% Distillates, hydrotreated heavy paraffinic

CAS number: 64742-54-7 EC number: 265-157-1 REACH registration number: 01-

2119484627-25-0014

Classification Classification (67/548/EEC or 1999/45/EC)

Asp. Tox. 1 - H304

2-ethylhexyl zinc dithiophosphate 1-5%

CAS number: 4259-15-8 EC number: 224-235-5 REACH registration number: 01-

2119493635-27-0000

Classification Classification (67/548/EEC or 1999/45/EC)

Eye Dam. 1 - H318 Xi;R41. N;R51/53.

Aquatic Chronic 2 - H411

1-5% Phenol, dodecyl-, sulfurized, carbonates, calcium salts,

overbased

CAS number: 68784-26-9 EC number: 272-234-3 REACH registration number: 01-

2119524004-56-0000

Classification Classification (67/548/EEC or 1999/45/EC)

Aquatic Chronic 4 - H413 R53.

Terrain CT30

Phenol, dodecyl-, branched <1%

CAS number: 121158-58-5 EC number: 310-154-3 REACH registration number: 01-

2119513207-49-XXXX

M factor (Acute) = 10 M factor (Chronic) = 10

Classification Classification (67/548/EEC or 1999/45/EC)

Skin Corr. 1C - H314 Repr. Cat. 3;R62. Xi;R36/38. N;R50/53.

Eye Dam. 1 - H318 Repr. 1B - H360F Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

Ingredient notes A petroleum product. DMSO extract < 3 % weight (IP 346)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical

attention if any discomfort continues.

Ingestion Get medical attention if any discomfort continues. Do not induce vomiting.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

Eye contact Remove affected person from source of contamination. Remove any contact lenses and open

eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use

water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases or vapours. Heat from fire could result in drums bursting

5.3. Advice for firefighters

Protective actions during

firefighting

Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment

Use air-supplied respirator, gloves and protective goggles.

for firefighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Terrain CT30

Personal precautions In case of spills, beware of slippery floors and surfaces. For personal protection, see Section

8.

6.2. Environmental precautions

Environmental precautions Contain spillage with sand, earth or other suitable non-combustible material. Avoid the

spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed

containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of

spillage on water prevent the spread by use of suitable barrier equipment

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Always remove oil with soap and water or skin cleaning agent, never use

organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags

moistened with oil into pockets. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Distillates, hydrotreated heavy paraffinic

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³ Short-term exposure limit (15-minute): ACGIH 10 mg/m³

Distillates, hydrotreated heavy paraffinic

Long-term exposure limit (8-hour TWA): ACGIH 5 Short-term exposure limit (15-minute): ACGIH 10 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

Ingredient comments WEL = Workplace Exposure Limits

2-ethylhexyl zinc dithiophosphate (CAS: 4259-15-8)

DNEL Workers - Dermal; systemic effects: 0.14 mg/kg/day

Workers - Inhalation; systemic effects: 0.422 ppm

Workers - Inhalation; Long term systemic effects: 0.07 ppm

Workers - Dermal; local effects: 0.09 mg/cm² Workers - Inhalation; local effects: 0.42 ppm

Workers - Inhalation; Long term systemic effects: 0.21 ppm Workers - Dermal; Long term systemic effects: 0.09 mg/cm²

Workers - Dermal; Long term systemic effects:

Terrain CT30

PNEC - Fresh water; 0.004 mg/l

- Soil; 0.0548 mg/kg

- Sediment (Freshwater); 0.0701 mg/kg

- marine water; 0.0046 mg/l

- Sediment (Marinewater); 0.00701 mg/kg

STP; 3.8 mg/l
 Air; 7.1 mg/m³

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased (CAS: 68784-26-9)

DNEL Industry - Dermal; Short term systemic effects: 80 mg/kg/day

Industry - Inhalation; Short term systemic effects: 167 mg/m³ Industry - Dermal; Long term systemic effects: 20.8 mg/kg/day Industry - Inhalation; Long term systemic effects: 70.52 mg/m³ Consumer - Dermal; Short term systemic effects: 40 mg/kg/day Consumer - Oral; Short term systemic effects: 50 mg/m³ Consumer - Oral; Long term systemic effects: 5 mg/kg/day

Consumer - Dermal; Long term systemic effects: 10.42 mg/kg/day Consumer - Inhalation; Long term systemic effects: 52.6 mg/m³

PNEC - Fresh water; 0.1 mg/l

- marine water; 0.01 mg/l

Sediment (Freshwater); 132000 mg/kgSediment (Freshwater); 13200 mg/kg

- Soil; 263000 mg/kg

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact. Wear apron or protective clothing in case of contact. Use of suitable barrier/afterwork creams to protect skin may be beneficial.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Do not eat, drink or smoke when using this product.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

Terrain CT30

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour

Odour Characteristic. Oil-like.

Odour threshold Not determined. pΗ Not applicable.

Melting point -36°C Pour point

Initial boiling point and range >320°C @ 101.3 kPa

Flash point 217°C Pensky-Martens closed cup.

Amber.

Other flammability Product is not flammable but on excessive heating may become combustible.

<0.1 kPa @ 20°C Vapour pressure Not determined. Vapour density

Relative density 0.880 @ 15.6°C

Solubility(ies) The product is insoluble in water. Soluble in the following materials: Organic solvents.

Partition coefficient log Kow: > 7 This figure is typical of mineral oil.

>320°C **Auto-ignition temperature**

Decomposition Temperature Not determined. 86.75 cSt @ 40°C Viscosity

Explosive properties Not considered to be explosive. Explosive under the influence Not considered to be explosive.

of a flame

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria

for classification as oxidising.

9.2. Other information

Volatile organic compound The product is a complex mixture, the majority of which would not be classed as a VOC.

However it cannot be discounted that trace or low levels of VOCs may be present.

SECTION 10: Stability and reactivity

10.1. Reactivity

products

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended. Stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition Oxides of carbon. Protection against nuisance dust must be used when the airborne

concentration exceeds 10 mg/m3.

Terrain CT30

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General information This product has low toxicity. Only large quantities are likely to have adverse effects on

human health.

Inhalation Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at

ambient temperature.

Ingestion May cause discomfort if swallowed.

Eye contact Causes serious eye irritation.

Acute and chronic health Prolonged or repeated contact with used oil may cause serious skin diseases, such as

hazards dermatitis and skin cancer.

SECTION 12: Ecological information

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient log Kow: > 7 This figure is typical of mineral oil.

12.4. Mobility in soil

MobilityThe product is non-volatile. The product is insoluble in water and will spread on the water

surface.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste, residues, empty containers, discarded work clothes and contaminated cleaning

materials should be collected in designated containers, labelled with their contents. This

material and its container must be disposed of as hazardous waste.

Disposal methods Dispose of waste via a licensed waste disposal contractor.

Waste class European Waste Catalogue (EWC) = 13 01 13* (other hydraulic oils)

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

Terrain CT30

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

Special Waste regulations 1996.

EU legislation Dangerous Substances Directive 67/548/EEC.

Dangerous Preparations Directive 1999/45/EC.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Guidance Workplace Exposure Limits EH40.

CHIP for everyone HSG228.

Approved Classification and Labelling Guide (Sixth edition) L131.

Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 02/11/2020

Revision 4

Supersedes date 16/12/2019

SDS number 21531

Terrain CT30

Hazard statements in full

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H360F May damage fertility if swallowed.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.