



SAFETY DATA SHEET

Ankorsol Anti Corrosion Fluid

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Ankorsol Anti Corrosion Fluid

Product number 7797

Internal identification GHS21698

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Water soluble corrosion inhibitor

Uses advised against Non specified unless otherwise stated within this MSDS

1.3. Details of the supplier of the safety data sheet

Supplier Morris Lubricants
Castle Foregate
Shrewsbury
Shropshire
SY1 2EL
+44 (0) 1743 232200
+44 (0) 1743 353584
sds@morris-lubricants.co.uk

1.4. Emergency telephone number

Emergency telephone +44(0)1743 232200 (08.45 - 17.00 GMT)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) -

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H319 Causes serious eye irritation.

Ankorsol Anti Corrosion Fluid

Precautionary statements	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P501a Dispose of contents/container to hazardous or special waste collection point.</p>
---------------------------------	---

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

amine carboxylate mixture			10-30%
CAS number: 53980-88-4		EC number: 258-897-1	
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335			
2,2'-OXYBISETHANOL			1-5%
CAS number: 111-46-6		EC number: 203-872-2	REACH registration number: 01-2119457857-21-XXXX
Classification Acute Tox. 4 - H302		Classification (67/548/EEC or 1999/45/EC) Xn;R22	
Nitrilotriacetic Acid Trisodium Salt			<1%
CAS number: 5064-31-3		REACH registration number: 01-2119519239-36-XXXX	
Classification Acute Tox. 4 - H302 Eye Irrit. 2 - H319 Carc. 2 - H351			
Triethanolamine			<1%
CAS number: 102-71-6		EC number: 203-049-8	
Classification Eye Irrit. 2 - H319		Classification (67/548/EEC or 1999/45/EC) -	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

Ankorsol Anti Corrosion Fluid

Ingestion	Get medical attention if any discomfort continues. Do not induce vomiting.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically
-----------------------------	-----------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Toxic gases or vapours. Heat from fire could result in drums bursting
-------------------------	---

5.3. Advice for firefighters

Protective actions during firefighting	Control run-off water by containing and keeping it out of sewers and watercourses.
---	--

Special protective equipment for firefighters	Use air-supplied respirator, gloves and protective goggles.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	In case of spills, beware of slippery floors and surfaces. For personal protection, see Section 8.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment
--------------------------------	---

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Avoid spilling. Avoid contact with skin and eyes. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.
--------------------------	---

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.
----------------------------	--

Ankorsol Anti Corrosion Fluid

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

2,2'-OXYBISETHANOL

Long-term exposure limit (8-hour TWA): WEL 23 ppm 101 mg/m³

Short-term exposure limit (15-minute): WEL

Triethanolamine

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

WEL = Workplace Exposure Limit

ACGIH = American Conference of Governmental Industrial Hygienists.

Ingredient comments WEL = Workplace Exposure Limits

Nitritotriacetic Acid Trisodium Salt (CAS: 5064-31-3)

PNEC

- Fresh water; 0.93 mg/l
- marine water; 0.093 mg/l

2-AMINOETHANOL (CAS: 141-43-5)

DNEL

- Workers - Dermal; Long term systemic effects: 1 mg/kg/day
- Workers - Inhalation; Long term local effects: 3.3 mg/m³
- Consumer - Oral; Long term local effects: 3.75 mg/kg/day
- Consumer - Dermal; Long term systemic effects: 0.24 mg/kg/day
- Consumer - Inhalation; Long term local effects: 2 mg/m³

PNEC

- Fresh water; 0.085 mg/l
- marine water; 0.0085 mg/l
- Secondary Poisoning; 0.025 mg/l
- Sediment (Freshwater); 0.425 mg/kg
- Sediment (Marinewater); 0.0425 mg/kg
- Soil; 0.035 mg/kg
- STP; 100 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Ankorsol Anti Corrosion Fluid

Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact. Wear apron or protective clothing in case of contact. Use of suitable barrier/afterwork creams to protect skin may be beneficial.
Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.
Respiratory protection	No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Green.
Odour threshold	Not determined.
pH	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	>320°C @ 101.3 kPa
Flash point	Not applicable.
Other flammability	Product is not flammable but on excessive heating may become combustible.
Vapour pressure	<0.1 kPa @ 20°C
Vapour density	>1
Relative density	1.1 @ 15.6°C
Solubility(ies)	Soluble in water
Partition coefficient	Not determined.
Auto-ignition temperature	>320°C
Viscosity	130 cSt @ 40°C
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Ankorsol Anti Corrosion Fluid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 34,722.22222222

General information This product has low toxicity. Only large quantities are likely to have adverse effects on human health.

Inhalation Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature.

Ingestion May cause discomfort if swallowed.

Eye contact Causes serious eye irritation.

Acute and chronic health hazards Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

SECTION 12: Ecological information

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product is non-volatile.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class European Waste Catalogue Code: 16 10 04 (Aqueous concentrates other than those mentioned)

Ankorsol Anti Corrosion Fluid

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).
The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Dangerous Substances Directive 67/548/EEC.
Dangerous Preparations Directive 1999/45/EC.

Guidance Workplace Exposure Limits EH40.
CHIP for everyone HSG228.
Approved Classification and Labelling Guide (Sixth edition) L131.
Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 22/01/2020

Revision 2

Supersedes date 20/01/2016

SDS number 21698

Hazard statements in full H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.