



Product Information:

GOLDEN FILM FLUSHING OIL

Description:

Golden Film Flushing Oil is a combination of highly refined light mineral oils and detergent/dispersant additives to enhance removal of sludge and lacquers. Golden Film Flushing oil can be used where a system's history is unknown or the service fill lubricant may have been used beyond its oil drain interval. This product can also be used if the service fill lubricant has to be drained because of a contamination problem.

Applications:

Golden Film Flushing Oil can be used in petrol and diesel engines, hydraulic systems and compressors.

Directions for Use:

1. Run the system until it reaches normal running temperature.
2. Drain old oil.
3. Fill with Morris Flushing Oil between minimum and maximum fill levels.
4. Run the system without load for 5 to 10 minutes.
5. Drain flushing oil. Repeat steps 2 to 4 if necessary.
6. Refill with recommended service fill lubricant.

Physical Characteristics:

Appearance	Amber liquid
Density @ 15°C	0.895
Kinematic Viscosity @ 40°C (cSt)	43.1
Kinematic Viscosity @ 100°C (cSt)	5.9
Viscosity Index	60
Pour Point (°C)	-39
Closed Flash Point (°C)	180

Figures based on average production values

Part No.s: FLU005

(TDS GoldenFilm Flushing Oil– 160116 Issue 2)

