

## MATERIAL SAFETY DATA SHEET

IDENTITY:

LOW CARBON STEEL PRODUCTS - ALL GRADES

SECTION I

Manufacturer's Name:

KEYSTONE STEEL & WIRE CO.

7000 SW ADAMS ST.

PEORIA, IL 61641

Emergency Telephone No:

309-697-7020

Telephone No. for Information

309-697-7020

Date Prepared: May 13, 1999 Date Revised: February 26, 2004

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components:

C.A.S. Number

lron

7439-89-6

>99

Manganese

7439-96-5

<1

Zinc

7440-66-6

Lime

Percentages are representative of product and may vary depending on batch composition. Due to the variance in batch composition, trace quantities of antimony, arsenic, barium, beryillium, cadmium, chromium, copper, lead, mercury, nickel, selenium, silver, and thallium may be present in amounts <1%.

\*A thin coating of oil, lime (<0.5% of total weight of product), or zinc (<2.4 % total weight of product) may be added to the surface as a corrosion inhibitor or preventative.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:

N/A

Specific Gravity:

Approx. 8

Vapor Pressure (mm Hg):

N/A

Melting Point:

2800°F

Vapor Density (Air = 1):

N/A

Evap.Rate (Butyl Acetate = 1):

N/A

Solubility in Water:

Negligible

Appearance and Odor:

odorless solid with metallic lustre

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method

Flammable Limits:

N/A

Used):

Extinguishing Media

Dry Compound or Dry Powder

Special Fire Fighting

NIOSH approved positive pressure, self-contained breathing apparatus.

Procedures:

Unusual Fire and

Spraying water on molten metal may cause an explosion. Use a dry type extinguisher.

Explosion Hazards:

Product is non-combustible.

Stability: Unstable Conditions to Avoid: N/A Stable  $_{\rm XX}$ Incompatibility (Materials Strong acids or bases to Avoid): Hazardous Decomposition Metal fumes and certain noxious gases such as CO may be produced or By-Products: during welding or burning operations. SECTION VI - HEALTH HAZARD DATA ROUTE(S) OF ENTRY: Inhalation? Skin? Ingestion? xxxxHealth Hazards: (Acute and Chronic): No toxic effects are expected from its inert form. Prolonged, repeated exposure to fumes or dusts generated during heating, cutting, welding, or brazing may cause the following health effects: Inhalation: Iron (Fe): Siderosis, no fibrosis Manganese (Mn): Pneumonitis. CNS involvement, including irritability, difficulty in walking, speech disorders, compulsive behavior, masklike face, and Parkinson like syndrome. Zinc oxide fumes can cause metal fume fever with symptoms similar to flu: chills, Zinc (Zn): fever, headache, cough, nausea, diarrhea, vomiting, etc. Soluble Oil: Pulmonary effects Lime (CaO): May cause irritation. Skin Contact: May cause irritation. Soluble oil may cause dermatitis. Eye Contact: May cause irritation. Ingestion: May cause irritation to mouth and throat. CARCINOGENICITY: NTP? IARC Monographs? OSHA Regulated? NO NÖ NO Sign and Symptoms of Exposure: Zinc (Zn): Metal Fume Fever Manganese (Mn): irritability, difficulty in walking, speech disorders, compulsive behavior, masklike face, and Parkinson like syndrome. Medical Conditions Generally None found Aggravated by Exposure: Emergency First Aid Procedures: Inhalation -If inhaled in large amounts, remove exposed person to fresh air. Get medical attention. Ingestion -Call a physician. If swallowed, if conscious, induce vomiting immediately. Exposure Limits: Ingredient: OSHA PEL (mg/M3) ACGIH TLV (mg/M3) Iron (Fe) 10 (as Fe<sub>2</sub>O<sub>3</sub> fume) 5 (as Fe<sub>2</sub>O<sub>3</sub> fume) Manganese (Mn) 1.0 (as fume) 5-Fume or Respirable dust 5-Fume 10-Dust Zinc (Zn) 10-Total dust Lime (CaO) 5 5

SECTION V - REACTIVITY DATA

SECTION VII - PRECAUTIONS FOR SAFE HANDLING USE

Steps To Be Taken in Case Material Is Released or

Spilled:

Sweep up spill and place in a container.

Waste Disposal Method:

Dispose in accordance with all applicable federal, state, and

local environmental regulations. Can often be sold for scrap

Precautions To Be Taken In Handling and Storage:

Other Precautions:

Avoid breathing fume or dust. Store away from strong acids

and bases.

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specific Type):

NIOSH approved dust and fume cartridge respirator or supplied air if

airborne dust or fume levels are or may be above the PEL. Consult respirator manufacturer for assistance in choosing

appropriate respirator. If respirators are used, employees must have a

respirator program which complies with OSHA 1910.134

Ventilation:

Local Exhaust - Use to maintain airborne levels below PEL.

Protective Gloves:

Standard

Eye Protection:

As necessary to protect against particles or radiation from welding

type operations.

Other Protective Clothing or Equipment:

Work/Hygienic Practices:

As needed to protect against heat.

Use good personal hygiene to avoid ingestion or inhalation through

food or smoking.

## SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME

CONCENTRATION

Combination of Zinc (CAS No. 7440-66-6)

and Zinc Oxide (CAS No. 1314-13-2).

<2.4%

Manganese (CAS No. 7439-96-5)

<1%

Percentages are representative of product and may vary depending on batch composition.

NFPA RATINGS:

Health - 1

Flammability - 0

Reactivity - 0

Special Hazards - NA

The information herein is provided in good faith and is believed to be correct and complete as of the date issued. This document is intended as a guide to appropriate handling precautions for the material. The user is responsible for determining the precautions and dangers of this material for his or her particular application.

No representations or warranties either expressed or implied of merchantability, fitness for a particular purpose or any other nature are made with respect to either the information set forth herein or to the product to which the information refers.

Keystone Steel and Wire shall not be liable for any loss or damage directly or indirectly arising form the use of this product. Keystone Steel and Wire assumes no obligation or liability for reliance on the information contained in this data sheet.