

LXcollection

LX2 Running LED Nav Lights

Models: LX2-PT, LX2-SB, LX2-ST, LX2-TW

OWNER'S MANUAL



USCG 2NM Approved
33 CFR 183.810 Meets ABYC-A16

Weems & Plath®

214 Eastern Avenue • Annapolis, MD 21403 p (410) 263-6700 • f (410) 268-8713 www.Weems-Plath.com/OGM

INTRODUCTION

Thank you for your purchase of Weems & Plath's OGM LX2 Running LED Navigation Lights. The rugged construction and long bulb life will provide years of trouble-free service for your marine application. This collection provides well over 2 nautical miles of visibility, suitable for both power and sailing vessels that are under 165-feet (50-meters). The lights are US Coast Guard certified, meet the COLREGS '72 and ABYC-16 standards. Additional certifications may be required for commercial applications. Check with your local regulations.

The LX2 Models:

There are 4 LX2 models: Port, Starboard, Stern, and Towing. The lens and LED bulb are clear which can make identifying the particular light difficult from a casual glance but the part number is labeled on the back of each unit to help identify it. The type of light can also be determined by applying power to the light and observing the illuminated color. The table below outlines each part number:

Model #	Description	LED Color	Horiz. View Angle	Vert. View Angle
LX2-PT	Port Running Light	Red	112.5°	> 70°
LX2-SB	Starboard Running Light	Cyan (Green)	112.5°	> 70°
LX2-ST	Stern Running Light	White	135°	> 70°
LX2-TW	Towing Running Light	Yellow	135°	> 70°

INSTALLATION INSTRUCTIONS

General:

The LX2 lights are designed to meet the requirements of the Convention on the International Regulations for Preventing Collisions at Sea, 1972, commonly called '72 COLREGS. These regulations were developed and adopted by the International Maritime Organization (IMO). These instructions and the '72 COLREGS should be followed during installation to ensure compliance with these regulations.

Mounting:

1. **PORT & STARBOARD:** The Port and Starboard lights must be mounted at an angle of 33.75° from the centerline of the vessel. The lights come with a mounting bracket to facilitate mounting at the proper angle.

STERN: The Stern light must be mounted as nearly as is practical at the stern of the vessel, facing directly aft.

TOWING: When towing another vessel, the tower must mount the Towing light in a vertical line above the Stern light.

- 2. The '72 COLREGS documents the proper locations for navigation lights. Specific rules also apply for vessels over 65.5-feet (20-meters), including the use of screens. Please refer to those regulations when installing these lights.
- 3. The light is completely waterproof so no extra precautions are necessary to protect the components within the light. The light is <u>not</u> designed to be opened; doing so will void the warranty.
- 4. The light is designed to be mounted using two 8-32 or similar sized through bolts, preferably high-grade stainless steel, pan-head screws.
- 5. Avoid any undue tension, pulling or bending of the wires behind the housing. Contact Weems & Plath directly if you have any questions.

Wiring:

The LX2 lights come standard with 2.5-feet of marine-grade 2-conductor, 20-gauge wire. A waterproof splice should be made for extending the run of wire length. Wire of 20-gauge or larger is sufficient for the small current draw (\leq 0.17 Amps) of these lights. The light must be protected with a 1 Amp circuit breaker or fuse. To install, connect the black wire to the boat's DC ground and the red wire to the boat's DC positive power source. *Improper fuse protection may result in fire or other catastrophic damage in the case of a short or other failure.*

SPECIFICATIONS

Visibility: 2 nautical miles


Waterproof: yes, completely submersible

Power Consumption: 2 Watts

Voltage Range: 9V to 30V DC

Current Draw: ≤ 0.17 Amps at 12V DC

Wiring: 2-conductor 20 AWG UV jacketed 2.5-foot cable



Warranty:

This product is covered by a LIFETIME Warranty. For more details on the warranty, please visit: www.Weems-Plath.com/Support/Warranties

To register your product visit: www.Weems-Plath.com/Product-Registration