Technical specifications



Framery One features and options

- Colors
 - · 8 Exterior panel colors
 - · 4 Interior panel colors
 - · 8 Seat fabric colors
 - 4 Carpet colors
 - · 3 Table colors
- · Framery Connect Occupancy indicator
- Wireless charger
- Activated carbon filter
- LAN
- Movability kit
- Seismic anchors

The adjustable work surface provides ample space for laptops, personal devices and other work tools. The electric height adjustable table can be positioned vertically between 70 - 120 cm (27,6 - 47,2 in) to allow for different working positions and provide comfort for all users.

	Measurements - cm	Measurements - in
Exterior	225,5 cm x 122 cm x 100 cm (height, width, depth)	88,8 in x 47,9 in x 40 in (height, width, depth)
Interior	204 cm x 102 cm x 93 cm (height, width, depth)	80,3 in x 40 in x 36,7 in (height, width, depth)
Door (left- and right-handed)	Doorway 204 cm x 101,5 cm (height, width)	Doorway 80,2 in x 40 in (height, width)
Table	76 cm x 45 cm (width, depth) Adjustment height 70 cm - 120 cm	30 in x 17,7 in (width, depth) Adjustment height 27,6 in - 47,2 in
Adjustable seat height	59 cm - 85 cm	23,2 in x 33,5 in

The door handedness can be changed on-demand with simple tools, by flipping the front frame in its place. No additional components are needed, should the customer want to have the door opening to the right instead of left.

UI panel	
High resolution touchscreen	Outlet 1 power socket + USB C socket + optional LAN (extra cost)

Adjust airflow & brightness of the light according to your own preference from the touchscreen. See both the availability of the pod and/or book a reservation (by using the optional calendar integration) from your own laptop or phone or just walk in and the pod reserves itself automatically for you. Integrated 4G technology module enables three way communication between you, the pod and Framery. Whether it's about calendar reservation, pod maintenance, updates or notifications, all matters related to the Framery One pod are handled remotely (digitally).

	Features		
Exterior	Powder coated deep-drawn steel panels		
Interior	Replaceable interior panels made from PET sheets which are laminated with polyester fabric		
Glass	Sound control laminated glass		
Frames	Semi-gloss black frames made from steel & aluminum		
Solid walls and floor	A sandwich element chassis, made of deep-drawn sheet metal & recycled acoustic foam. Fabric interior panels and an anti-static and stain resistant low loop pile carpet for the floor.		
Tabletop	Formica laminate on birch plywood with varnish trim		
Weight	325 kg / 716,5 lb		
Airflow	Maximum airflow is 29 l/s. (Minimum recommended space for the air to circulate is 5 cm $/$ 1,9" on the sides – 20 cm $/$ 8" above the pod.)		
Acoustics	Speech level reduction (Ds.A) according to ISO 23351-1 testing method: >30 dB		
	Power		
	Maximum power consumption:		

	Power	
Power consumption	35 W while in use (Default) LED lights: 19 W Fans in total: 7 W 6 W standby power consumption Fans are working on 25 % of the maximum power	Maximum power consumption: 80 W total LED light: 24 W Fans in total: 9 W USB C charger: 21 W Wireless charger: 12 W Input: 100-240 VAC, 10.0 A, 50-60 Hz
Outlets	Always included Power socket + USB charger	Optional Wireless charger LAN
Output values	Output VAC (power socket): $100-240$ VAC, $6,6$ A, $50-60$ Hz Output USB C charger: 18 W Output Qi wireless charger: 10 W	



