

## SLINGWING V3 // QUICK START GUIDE



#### **SLINGWING V3 FEATURES**

We designed the all new Slingwing V3 to give you drastically more power in a given size. Using a smaller wing in the same wind provides all the advantage of the higher speed an increased control, with less weight and drag. The larger strut and LE diameter provide a completely rigid frame for big airs with tons of hangtime. A tight canopy cancels oscillaton and flutter to increases luffing performance. The V3's new elongated handle system allows riders to perfectly place their grip for maximum responsiveness.

FOR COMPLETE USER INFORMATION PLEASE VISIT: www.slingshotsports.com/slingshot-qsg



#### SLINGWING V3

2.5m - 3.5m - 4.0m - 4.5m - 5.0m - 5.5m - 6.5m - 7.5m The Slingwing V3 comes in and expanded range of 8 sizes. The one pump valve makes inflation quick and simple, while the added dump valve on the strut make deflation and packing a breeze. The Profile Entry Batten provides smooth aerodynamic shaping where the inflatable leading edge transitions to the wing canopy for efficient air flow across the wing. Light and tough 4x4 canopy tech material combined with our Skate Scuff tough strips on the wingtips and LE provide increased durability all terrain surfaces. Like its predecessor, the V3 features harness line attachment pigtails allowing you to use a harness for higher speeds, better tack angles and longer sessions.







#### 1. INFLATE

Open neoprene valve cover and unscrew inflation valve cap. Attach pump hose (sold separately) onto inflation valve and pump to indicated PSI. Squeeze one-pump clip to separate leading edge and strut bladders.

#### 2. ATTACH

Feed the wrist loop through the wing loop on the leading edge and pull wrist loop through itself to complete the connection.



### 4. DEFLATE & STORE

Unclip the one-pump valve, open the strut deflate valve and unscrew the inflate valve to deflate. While inflated remember to weigh it down or teather it to keep it from flying away.

While not in use, make sure it's dry before packing. Use the storage bag and keep it in a cool, dry place.\*\* DO NOT LEAVE SLING-WING EXPOSED TO DIRECT SUNLIGHT OR HEAT WHEN NOT IN USE

## 3. CONTROL

Use strut handles to power the wing and control wingtip roll.



# SLINGSHOT SUPPORT

FOR FURTHER INSTRUCTIONS GO TO: WWW.SLINGSHOTSPORTS.COM

CONTACT US: INFO@SLINGSHOTSPORTS.COM

RIDER SERVICE LINE IN THE US: 877.775.4832

INTERNATIONAL PHONE: 509.427.4950

LOG ON TO: SLINGSHOTSPORTS.COM/REGISTRATION TO REGISTER YOUR PRODUCT. RECEIVE SERVICE GUARANTEES, AND ACCESS TO YOUR OWN PERSONAL RIDER HOTLINE PROFESSIONAL.

REGISTER YOUR SLINGWING WITHIN THE FIRST 30 DAYS OF PURCHASE AND EXTEND YOUR 1 YEAR WARRANTY TO A 2-YEAR WARRANTY!!

