


| Model # | U552 NK5SV/WL+4G431(4XLED3K) | |
|-------------------------------------|-----------------------------------|--|
| SKU | 18920 | |
| Metal Finish | Brushed Nickel | |
| Blade Finish | Silver/Walnut | |
| Glass Finish | White | |
| Blade Span | 52" | |
| Motor Specs | 153mm x 12mm | |
| Wire Length (Shown in inches) | 80" | |
| Down Rod Included (Shown in inches) | 4" | |
| Blade Pitch | 12 Degrees | |
| Speed | 3 | |
| Forward/Reverse | Yes | |
| Airflow Average | 3414 | |
| Power Use (Watts) | 33 | |
| Airflow Efficiency (CFM/Watt) | 103 | |
| Light Kit Included | Yes | |
| Laman Infa | 4X 9.5W LED 3000K *Lamps included | |
| Location Use | Indoor Only | |
| Wall Control | Not Included | |





ELECTRICAL REQUIREMENTS: Fixture requires a grounded electrical supply line of 120 volts AC.

INSTALLATION REQUIREMENTS: Fixture attaches to electrical junction box securely anchored in wall or ceiling. **All mounting hardware included.**

HOMEnhancements / 1505-A Kelly Blvd., Carrollton, TX. 75006

Product specifications subject to change without notice.

| REFERENCE | QTY. | REMARKS | Project | |
|-----------|------|---------------|---------------|--|
| | | | Location/Type | |
| | | | Architect | |
| | | · | Engineer | |
| | | | Contractor | |
| | | Submitted By: | Date: | |