

Warranty Service

Hi friend,

We are devote to provide happy shopping experience for our customers. If you have any questions or issue, pls feel free to contact us fivklemnz_service@yeah.net. We will take full responsibility, effectively help solve any problems you may have .

If think we have done work good job with our product ,please spend a few seconds to us ,share your happy experience, it is of great help and means a lot us. Thanks for your support!

Have a good day!
Your sincerely,
fivklemnz_service@yeah.net
Customer Service Team

FIVKLEMNZ

Car Roof Bag



Please read User Manual carefully before using it

Package includes:

Please check package and accessories, accessories list as below:

ITEM	NAME	QUANTITY
1	Car Roof Bag	1
2	Storage Bag	1
3	User Manual	1
4	Warranty Card	1
5	Door Hooks	6
6	Anti-Slip Mat	1
7	Luggage Lock	1

Note:

- Tip 1: Always face the side with no zipper towards the FRONT of the vehicle.
- Tip 2: The Protective Mat may have a little strange smell when take out of package for the first time. It will disappear after one day.
- Tip 3: After each use, clean the surface by a damp sponge or towel.
- Tip 4: Keep the front of the carrier at least 8" behind the top of the windshield, to avoid air turbulence.
- Tip 5: Lock the zipper after packing and make sure the rain flap covers the zipper.
- Tip 6: When fastening the straps, make sure they are as vertical as possible, to create a secure attachment and to avoid movement during travel.

Installed on any car with/without roof rack and side rail

Notice:

Side rails: Straps attach to side rails left-to-right.
Cross bars: Straps attach to bars front-to-back.

Important Tips:

1. If you don't have across bars, just need to install the 6 side straps and then you can remove the front and back straps. But DO NOT install front and back straps to door hooks to avoid tearing!!!
2. If you have across bars, you can install all 10 straps together.



How to install and tightly secure the car roof bag if without roof rack



Step 1

Put the anti-slip mat on the car roof top. Then just place the car roof bag on the mat.



Step 2

Open your door and carefully pull back the weatherstripping seal.



Step 3

With the seal pulled back, place one of the 4 included door hooks on the metal doorframe.



Step 4

Applying gentle force, pop the weatherstripping seal back into place with your hand and close the door.



Step 5

Apply the same procedure to the other doors. These hooks will safely anchor the rooftop cargo bag.