

LSM • PUMPS

LSM10 / LSM15 TECHNICAL DATA SHEET



PUMP APPLICATIONS:

- Sewage Treatment plants
- Combinet heat and power plants
- Fishing industry
- Meat plants
- Chemical industry
- Food industry
- Off-Shore
- Mining

PUMP ADVANTAGES:

- Low energy Consumption
- High pressure
- Self priming
- Tolerates dry-run
- Passes large objects
- Low maintenance



ATLANTIC
PUMPS

OFFICIAL UK DISTRIBUTOR FOR LSM PUMPS

T: 01246 284 420 E: info@atlanticpumps.co.uk

Atlantic Pumps Ltd is a Limited Company registered in England number 09400148.
Registered Office: Atlantic Pumps, Unit 21 Prospect House, Colliery Close,
Staveley, Derbyshire, United Kingdom, S43 3QE.

LSM10 / LSM15 TECHNICAL DATA SHEET

TECHNICAL DATA LSM 10


Nominal flowrate:	2,5 l/min
Nominal pressure:	5 bar (0,25 kW motor)
Max. Pressure:	10 bar
Connection:	MALE 3/8" BSP
Weight:	Approx. 25 kg / 55 lbs

TECHNICAL DATA LSM 15

Nominal flowrate:	5,5 l/min
Nominal pressure:	5 bar (0,25 kW motor)
Max. Pressure:	10 bar
Connection:	MALE 1/2" BSP
Weight:	Approx. 25 kg / 55 lbs

- Worm gearbox and motor is selected for the specific pressure and flowrate needed
- Optional with Variable Frequency Drive.
- High vacuum possible, suction lifts up to 8m. (Above 4m lifting height, vacuum is applied to the pump housing to improve efficiency).
- Low friction rollers
- Polyurethane housing

Q [l/min.] Pump Flowrate - LSM10



Q [l/min.] Pump Flowrate - LSM15

