



Mining



Construction



Autonomous



Logistics & Port Operations



Automation



Rail

Multi-frequency, multi-constellation GNSS positioning and heading receiver, which includes wired and wireless communications in a rugged IP68 housing, for the broadest range of applications.

KEY FEATURES

- ▶ **Full-constellation, triple-frequency satellite tracking on both antennas**
- ▶ **Sub-degree GNSS heading & pitch or heading & roll**
- ▶ **Centimetre-level (RTK)**
- ▶ **Septentrio GNSS+ algorithms for reliable performance**
- ▶ **Integrated UHF radio, cellular modem, Bluetooth and Wi-Fi (depending on configuration)**

BENEFITS

Consistently accurate now and into the future

The AsteRx-U3 is the most advanced integrated multi-constellation dual-antenna receiver from Septentrio. Its multi-frequency engine can track signals from all Global Navigation Satellite System (GNSS) constellations: GPS, GLONASS, Galileo, BeiDou, NavIC and QZSS – on both antennas. This guarantees you reliable and accurate GNSS positioning now and into the future.

Reliable centimetre accuracy

Septentrio's knowledge and 20 years of experience in the GNSS industry ensures that the AsteRx-U3 offers the highest possible accuracy, down to the centimetre level. LOCK+ technology maintains tracking during heavy vibrations and IONO+ ensures position accuracy even during periods of elevated ionospheric activity. The AsteRx-U3 offers the very latest in advanced interference mitigation technology AIM+, which filters out ambient intentional and unintentional RF interference.

Any device, any platform

Use any device with a web browser to operate the AsteRx-U3 without any special configuration software via the Web interface, accessible over Ethernet, Wi-Fi or USB connections.

FEATURES

GNSS technology

544 Hardware channels for simultaneous tracking of most visible signals:

- ▶ GPS: L1 C/A, L1C¹, L2C, L2 P(Y), L5
- ▶ GLONASS: L1 C/A, L2 C/A, L3, L2P
- ▶ BeiDou: B1I, B1C, B2a, B2I, B3I
- ▶ Galileo: E1, E5a, E5b, E5 AltBOC
- ▶ QZSS: L1 C/A, L1C¹, L2C, L5
- ▶ NavIC: L5
- ▶ SBAS: EGNOS, WAAS, GAGAN, MSAS, SDCM

Septentrio's patented GNSS+ technologies

- ▶ **AIM+** unique mitigation and monitoring system against narrow and wideband interference with spectrum analyser
- ▶ **IONO+** advanced scintillation mitigation
- ▶ **APME+** a posteriori multipath estimator for code and phase multipath mitigation
- ▶ **LOCK+** superior tracking robustness under heavy mechanical shocks or vibrations
- ▶ **RAIM+** Receiver Autonomous Integrity Monitoring

RTK (base and rover)

Integrated 4-channels L-band receiver

Moving base

GNSS heading & pitch or heading & roll

16 GB internal memory

Formats

Septentrio Binary Format (SBF), fully

documented with sample parsing tools

RTCM v2x and 3x (MSM included)

CMR 2.0 and CMR+ (CMR+ input only)

NMEA 0183, v3.01, v4.0

UHF: Satel, Trintalk (450S) Pacific

Crest (GMSK, 4FSK, FST)

Connectivity

3 Hi-speed serial ports (RS232)

Ethernet port (TCP/IP and UDP)

CAN port

High-speed USB

1 Event marker

xPPS output (max. 100 Hz)

Bluetooth² (2.1 + EDR/4.0)

WiFi² (802.11 b/g/n)

UHF² (410-475 MHz)

Cellular modem²: LTE CAT4

4G LTE CAT4 (B1, B3, B5, B7, B8, B20)

3G UMTS/HSDPA/HSUPA (850/900/1900/2100)

2G GSM/GPRS/EDGE (850/900/1800/1900)

PERFORMANCE

Position accuracy^{3,4}

	Horizontal	Vertical
Standalone	1.2 m	1.9 m
SBAS	0.6 m	0.8 m
DGNSS	0.4 m	0.7 m

RTK performance^{3,4,5,6}

Horizontal accuracy	0.6 cm + 0.5 ppm	
Vertical accuracy	1 cm + 1 ppm	
Initialisation	7 s	

GNSS attitude accuracy^{3,4}

	Heading	Pitch/Roll
Antenna separation		
1 m	0.15°	0.25°
5 m	0.03°	0.05°

Velocity accuracy^{3,4}

0.03 m/s

Maximum update rate

Position	100 Hz
Position and attitude	50 Hz
Measurements	100 Hz

Latency⁷

<20 ms

Time precision

xPPS out ⁸	5 ns
Event accuracy	< 20 ns

Time to first fix

Cold start ⁹	< 45 s
Warm start ¹⁰	< 20 s
Re-acquisition	avg. 1 s

Tracking performance (C/N0 threshold)⁹

Tracking	20 dB-Hz
Acquisition	33 dB-Hz

PHYSICAL AND ENVIRONMENTAL

Size 157 x 245 x 45mm

Weight 1.5 kg

Input voltage 9-48 VDC

Power consumption 8 W maximum

Operating temperature -30° C to +65° C

Storage temperature -40° C to +75° C

Humidity IEC60721-3-5, Class 5K2

Dust MIL-STD-810H, Method 510.7, Procedure I

Shock MIL-STD-810H, Method 516.8, Procedure I/II

Vibration MIL-STD-810H, Method 514.8, Procedure I

Corrosion IEC60068-2-52, Method 2

Connectors

Antennas	TNC female
COM1/3	M8 6 pins female
USB	M8 4 pins female
I/O	M8 6 pins male
Ethernet	M12 8 pins female
Power	M12 4 pins male
COM2/PPS	M12 8 pins female

Antenna LNA power output

Output voltage	User selectable 3.3V/5V
Maximum current	150 mA

Certification

IP68, RoHS, WEEE, CE, ISO 9001-2015, UKCA



¹ Hardware ready

² Optional feature

³ Open sky conditions

⁴ RMS levels

⁵ RTK fixed ambiguities

⁶ Baseline < 40 Km

⁷ 99.9%

⁸ Including software compensation of sawtooth effect

⁹ No information available (no almanac, no approximate position)

¹⁰ Ephemeris and approximate position known

EMEA

Greenhill Campus (HQ)
Interleuvenlaan 15i
3001 Leuven, **Belgium**

Espoo, **Finland**

Americas

2601 Airport Drive,
Suite 360
Torrance, CA 90505, **USA**

septentrio.com/contact

Asia-Pacific

Shanghai, **China**
Yokohama, **Japan**
Seoul, **Korea**

septentrio.com



septentrio[®]