

AsteRx-m2 UAS

Centimetre accuracy and easy integration into UAS



UAV



Survey & GIS



Logistics



Automation



Mapping



The AsteRx-m2 UAS is a GNSS receiver specifically designed for straightforward integration into UAS applications providing centimetre-level RTK positioning at less than 1 W (GPS and GLONASS L1/L2). It features standard connections to Pixhawk and ArduPilot and a wide range 6-30 V power input as well as an event marker input to accurately time stamp camera shutter events.

Key Features

- ▶ Multi-constellation, multi-frequency all-in-view satellite tracking
- ▶ Centimetre-level (RTK) position accuracy with or without a real-time datalink
- ▶ AIM+ anti-jamming and monitoring system
- ▶ Camera shutter synchronisation
- ▶ Plug compatible with ArduPilot/Pixhawk
- ▶ Easy-to-integrate

Designed for UAS

The AsteRx-m2 UAS is designed for easy integration into any system. Standard connectors connect directly to your autopilot (e.g. Pixhawk) and the wide 6-30 V input power range allows you to use the power directly from the vehicle power bus. Event markers can accurately synchronise a camera shutter with GNSS time. The command interface is fully open and an SDK is provided to help create professional custom applications.

Interference robustness

The AsteRx-m2 UAS features AIM+, the most advanced on-board anti-jamming technology on the market. It can suppress the widest variety of interferers, from simple continuous narrowband signals to the most complex wideband and pulsed jammers. The RF spectrum can be viewed in real-time in both time and frequency domains.

No need for ground control points

The AsteRx-m2 UAS works seamlessly with GeoTagZ software and its SDK library for PPK (Post-processed kinematic) offline processing. This gives RTK accuracy without the need for ground control points or a real-time datalink.

Ultra-low power design

The AsteRx-m2 UAS provides RTK positioning at the lowest power consumption of any comparable device on the market. This means longer operation on a single battery charge, smaller batteries and greater usability.

AsteRx-m2 UAS

FEATURES

GNSS technology

448 Hardware channels for simultaneous tracking of all visible satellite supported signals:

- ▶ GPS: L1, L2, L5
- ▶ GLONASS: L1, L2, L3
- ▶ Galileo¹: E1, E5a, E5b, AltBoc
- ▶ BeiDou¹: B1, B2
- ▶ SBAS: EGNOS, WAAS, GAGAN, MSAS, SDCM (L1, L5)
- ▶ IRNSS¹: L5
- ▶ QZSS: L1, L2, L5
- ▶ Integrated dual-channel L-band receiver

Septentrio's patented GNSS+ technologies

- ▶ **AIM+** unique anti-jamming and monitoring system against narrow and wideband interference with spectrum analyser
- ▶ **IONO+** advanced scintillation mitigation
- ▶ **APME+** a posteriori multipath estimator for code and phase multipath mitigation

RAIM (Receiver Autonomous Integrity Monitoring)

RTK (base and rover)¹

PPP (Precise Point Positioning with SECORX)^{1,2}

Moving base^{1,3}

Formats

Septentrio Binary Format (SBF), fully documented with sample parsing tools

NMEA 0183, v2.3, v3.01, v4.0

RINEX¹ (obs, nav) v2.x, v3.x

RTCM v2.x, v3.x (MSM messages included)

CMR v2.0 and CMR+ (CMR+ input only)

UAS interface board

Wide range power supply input (6-30 VDC)

On-board logging on micro-SD card

(max 32 GB)

Plug compatible with Pixhawk and Ardupilot

xPPS output (max 100 Hz)

Event marker for camera shutter synchronisation¹

Push-button to start/stop logging on the SD-card.

LEDs for power, logging and PVT status.

Connectivity

3 Hi-speed serial ports (LVTTTL)

1 Full speed USB device port (micro USB with access to internal disk, TCP/IP communication and with 2 extra serial ports)

General purpose output

Time and frequency synchronisation inputs

NTRIP (server, client, caster)

FTP server, FTP push¹, SFTP

PERFORMANCE

Position accuracy^{4,5}

	Horizontal	Vertical
Standalone	1.2 m	1.9 m
SBAS	0.6 m	0.8 m
DGNSS	0.4 m	0.7 m
SECORX-C (PPP) ^{2,6}	4 cm	6 cm
SECORX-D (PPP) ^{2,6}	6 cm	9 cm

RTK performance^{4,5,7}

Horizontal accuracy	0.6 cm + 0.5 ppm
Vertical accuracy	1 cm + 1 ppm
Initialisation	7 s

Velocity accuracy^{4,5}

	0.03 m/s
--	----------

Maximum update rate

Position	100 Hz
Measurements	100 Hz

Latency⁸

	<10 ms
--	--------

Time precision

xPPS out ⁹	5 ns
Event accuracy	< 20 ns

Time to first fix

Cold start ¹⁰	< 45 s
Warm start ¹¹	< 20 s
Re-acquisition	avg. 1 s

Tracking performance (C/N0 threshold)

Tracking	20 dB-Hz
Acquisition	33 dB-Hz

SUPPORTING COMPONENTS

- ▶ Web UI for easy configuration and monitoring via Ethernet or USB connectivity.
- ▶ RxTools, a complete and intuitive GUI tool set for receiver control, monitoring, data analysis and conversion.
- ▶ GNSS receiver communication SDK. Available for both Windows and Linux OS.

Optional accessories

- ▶ Antennas
- ▶ GeoTagZ re-processing software and SDK library for aerial mapping

PHYSICAL AND ENVIRONMENTAL

Size	47.5 x 70 x 14.9 mm 1.87 x 2.75 x 0.58 in
-------------	----------------------------------------------

Weight

GNSS OEM board	28 g / 0.987 oz
UAS interface board	10 g / 0.352 oz

Input voltage

	5 V or 6–30 VDC
--	-----------------

Power consumption

GPS/GLO L1/L2	930 mW
All signals all GNSS constellations	1.1 W
All signals all constellations + L-Band	1.2 W

Antenna

Connectors ¹²	2 x U,FL
Antenna supply voltage	3-5.5 VDC
Maximum antenna current	200 mA
Antenna gain range	passive 0 -50 dB active

I/O connectors

COM1	6 pins DF13-6P- 1.25DSA (plug compatible with Pixhawk and ArduPilot)
COM2	6 pins DF13-6P-1.25DSA
COM3	4 pins DF13-4P-1.25DSA
Event-maker	2 pins header
PPS-Out	3 pins header

Environment

Operating temperature	-40° C to +85° C -40° F to +185° F
Storage temperature	-55° C to +85° C -67° F to +185° F
Humidity	5% to 95% (non-condensing)
Vibration	MIL-STD-810G

Certification

RoHS, WEEE



¹ Optional feature

² Service subscription required

³ Output rate 20 Hz

⁴ Open sky conditions

⁵ RMS level

⁶ After convergence

⁷ Baseline < 40 Km

⁸ 99.9%

⁹ Including software compensation of sawtooth effect

¹⁰ No information available (no almanac, no approximate position)

¹¹ Ephemeris and approximate position known

¹² Second connector for alternative external antenna

EMEA (HQ)

Greenhill Campus
Interleuvenlaan 15i
3001 Leuven, Belgium

+32 16 30 08 00

septentrio.com

Americas

Suite 200
23848 Hawthorne Blvd
Torrance, CA 90505, USA

+1 310 541 8139

sales@septentrio.com

Asia-Pacific

Shanghai, China
Yokohama, Japan

