

acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0
Replaces version of: 2015-09-09 (GHS 3)
revision: 2018-11-02

SECTION 1: Identification

1.1 Product identifier

MIL-W-18723D

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses general use

1.3 Details of the supplier of the safety data sheet

SPECIALITY COATINGS

33835 KELLY

FRAZER, MI, 48026 United State

Telephone: 1.800.875.6320, 1.303.289.6320

Telefax e-mail: info@bbblending.com

Website: bbblending.com

Competent person responsible for the SDS

DAVID REIF

e-mail (competent person)

DREIF@SPECIALTYCOATINGS.COM

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500 24 hour emergency telephone number.

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Annex	 Hazard class and category 	 Hazard statement code(s) 	
B.6	flammable liquid	Cat. 4 (Flam. Liq. 4)	H227
A.5	germ cell mutagenicity	Cat. 1B (Muta. 1B)	H340
A.6	carcinogenicity	Cat. 1B (Carc. 1B)	H350
A.7	reproductive toxicity	Cat. 2 (Repr. 2)	H361f
A.10	aspiration hazard	Cat. 1 (Asp. Tox. 1)	H304

Remarks

For full text of H-phrases: see SECTION 16.

Hazards not otherwise classified

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and chronic).

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Signal word danger



acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0 revision: 2018-11-02 Replaces version of: 2015-09-09 (GHS 3)

Pictograms

GHS08



Hazard statements

H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

H340 May cause genetic defects.

H350 May cause cancer.

H361f Suspected of damaging fertility.

Precautionary statements

Precautionary statements - prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Wear protective gloves/eye protection/face protection.

Precautionary statements - response

IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.

IF exposed or concerned: Get medical advice/attention.

Do NOT induce vomiting.

In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

Precautionary statements - storage

Store in a well-ventilated place. Keep cool.

Store locked up.

Precautionary statements - disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous ingredients for labelling

Stoddard Solvent, octamethylcyclotetrasiloxane, Distillates (petroleum), hydrotreated light, odorless mineral spirits

2.3 Other hazards

This material is combustible, but will not ignite readily. Special danger of slipping by leaking/spilling product.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Hazard o	class and category	Hazard state- ment
Distillates (petroleum), hydrotreated light	CAS No 64742-47-8	5 - < 10	B.6 A.10	Flam. Liq. 4 Asp. Tox. 1	H227 H304
odorless mineral spirits	CAS No 64742-48-9	5 - < 10	B.6 A.2 A.8D A.10	Flam. Liq. 3 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1	H226 H315 H336 H304



Safety Data Sheet acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0 Replaces version of: 2015-09-09 (GHS 3) revision: 2018-11-02

Name of substance	Identifier	Wt%	Hazard o	lass and category	Hazard state- ment
octamethylcyclotetrasiloxane	CAS No 556-67-2	5 - < 10	B.6 A.7	Flam. Liq. 3 Repr. 2	H226 H361f
decamethylcyclopentasiloxane	CAS No 541-02-6	1 - < 5	B.6	Flam. Liq. 4	H227
Stoddard Solvent	CAS No 8052-41-3	1 - < 5	B.6 A.5 A.6 A.9 A.10	Flam. Liq. 3 Muta. 1B Carc. 1B STOT RE 1 Asp. Tox. 1	H226 H340 H350 H372 H304
aminofunctional silicone fluid	CAS No 69430-37-1	< 1	B.6	Flam. Liq. 2	H225
Propan-2-ol	CAS No 67-63-0	<1	B.6 A.3 A.8D	Flam. Liq. 2 Eye Irrit. 2A STOT SE 3	H225 H319 H336
ethyl alcohol	CAS No 64-17-5	<1	B.6 A.1D A.2 A.3 A.8	Flam. Liq. 2 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2A STOT SE 1	H225 H312 H315 H319 H370
methanol	CAS No 67-56-1	<1	B.6 A.1O A.1D A.11 A.8	Flam. Liq. 2 Acute Tox. 3 Acute Tox. 3 Acute Tox. 3 STOT SE 1	H225 H301 H311 H331 H370
ethylbenzene	CAS No 100-41-4	<1	B.6 A.11 A.9 A.10	Flam. Liq. 3 Acute Tox. 4 STOT RE 2 Asp. Tox. 1	H226 H332 H373 H304
xylene	CAS No 1330-20-7	<1	B.6 A.1D A.1I A.2 A.3 A.8R A.10	Flam. Liq. 3 Acute Tox. 4 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2A STOT SE 3 Asp. Tox. 1	H226 H312 H332 H315 H319 H335 H304
cumene	CAS No 98-82-8	<1	B.6 A.8R A.10	Flam. Liq. 3 STOT SE 3 Asp. Tox. 1	H226 H335 H304
1,2-benzisothiazol-3(2H)-one	CAS No 2634-33-5	<1	A.10 A.2 A.3 A.4S	Acute Tox. 4 Skin Irrit. 2 Eye Dam. 1 Skin Sens. 1	H302 H315 H318 H317



acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0
Replaces version of: 2015-09-09 (GHS 3)
revision: 2018-11-02

Name of substance	Identifier	Wt%	Hazard (class and category	Hazard state- ment
4-methylpentan-2-one	CAS No 108-10-1	<1	B.6 A.11 A.3 A.8R	Flam. Liq. 2 Acute Tox. 4 Eye Irrit. 2A STOT SE 3	H225 H332 H319 H335
sodium hydroxide	CAS No 1310-73-2	<1	B.16 A.2 A.3	Met. Corr. 1 Skin Corr. 1A Eye Dam. 1	H290 H314 H318

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

SECTION 4: First-aid measures

4.1

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

Provide fresh air.

Following skin contact

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

water spray, BC-powder, carbon dioxide (CO2)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

SPECIALTY COATINGS INC.

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0 Replaces version of: 2015-09-09 (GHS 3) revision: 2018-11-02

Hazardous combustion products

nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains.

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools.



acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0 revision: 2018-11-02 Replaces version of: 2015-09-09 (GHS 3)

Warning

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Incompatible substances or mixtures

Observe compatible storage of chemicals.

Control of the effects

Protect against external exposure, such as

frost

Consideration of other advice

Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Source
US	hexone (methyl isobutyl ketone)	108-10-1	PEL	100	410			29 CFR OSHA
US	sodium hydroxide	1310-73-2	PEL		2			29 CFR OSHA
US	ethyl alcohol (ethanol)	64-17-5	PEL	1000	1900			29 CFR OSHA
US	petroleum distillates (naphtha) (rubber solvent)	64742-48-9	PEL	500	2000			29 CFR OSHA
US	methyl alcohol	67-56-1	PEL	200	260			29 CFR OSHA
US	isopropyl alcohol	67-63-0	PEL	400	980			29 CFR OSHA
US	stoddard solvent	8052-41-3	PEL	500	2900			29 CFR OSHA

Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless other-

SPECIALTY COATINGS INC.

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0
Replaces version of: 2015-09-09 (GHS 3)
revision: 2018-11-02

Notation

wise specified.

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted av-

erage.

Relevant DNELs/DMELs/PNECs and other threshold levels

No data available.

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state liquid (viscous)
Color off-white
Odor characteristic

Other physical and chemical parameters

pH (value) 7.9 (25 °C)
Melting point/freezing point not determined
Initial boiling point and boiling range >65 °C at 1 atm

Flash point 61 °C at 101.3 kPa 142 °F at 1 atm (closed cup)

Evaporation rate not determined Flammability (solid, gas) not relevant (fluid)



acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0 revision: 2018-11-02 Replaces version of: 2015-09-09 (GHS 3)

Explosive limits

lower explosion limit (LEL)
 upper explosion limit (UEL)
 5.4 vol%

Vapor pressure 132 Pa at 25 °C

Density not determined

Relative density 0.99 (water = 1)

Solubility(ies) not determined

Partition coefficient

n-octanol/water (log KOW) this information is not available

Auto-ignition temperature 343 °C

Viscosity not determined

Explosive properties none Oxidizing properties none

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

· if heated

risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Physical stresses which might result in a hazardous situation and have to be avoided strong shocks

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.



acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0 revision: 2018-11-02 Replaces version of: 2015-09-09 (GHS 3)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	ATE
ethyl alcohol	64-17-5	dermal	1100 ^{mg} / _{kg}
methanol	67-56-1	oral	100 ^{mg} / _{kg}
methanol	67-56-1	dermal	300 ^{mg} / _{kg}
methanol	67-56-1	inhalation: vapor	3 ^{mg} / _l /4h
ethylbenzene	100-41-4	inhalation: vapor	11 ^{mg} / _/ /4h
xylene	1330-20-7	dermal	1100 ^{mg} / _{kg}
xylene	1330-20-7	inhalation: vapor	11 ^{mg} / _l /4h
1,2-benzisothiazol-3(2H)-one	2634-33-5	oral	500 ^{mg} / _{kg}
4-methylpentan-2-one	108-10-1	inhalation: vapor	11 ^{mg} / _l /4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Summary of evaluation of the CMR properties

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility.

Carcinogenicity

National Toxicology Program (United States):

none of the ingredients are listed

IARC Monographs

none of the ingredients are listed

Name of substance	Name acc. to inventory	CAS No	wt%	Classifica- tion	Remarks	Number
4-methylpentan-2-one	Methyl isobutyl ketone	108-10-1	0.0074	2B		Volume 101
ethyl alcohol	Ethanol	64-17-5	0.6586	1	in alcoholic bever- ages	Volume 96, 100E



acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0 Replaces version of: 2015-09-09 (GHS 3)

Name of substanceName acc. to inventoryCAS Nowt%ClassificationRemarksNumberPropan-2-olIsopropyl alcohol67-63-00.69123Volume 15, Sup 7, 71

Legend

1 Carcinogenic to humans.

2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity in humans.

Specific target organ toxicity (STOT)

Shall not be classified as a specific target organ toxicant.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute)

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
octamethylcyclotetrasilox- ane	556-67-2	LC50	>22 ^{µg} / _I	fish	96 h
octamethylcyclotetrasilox- ane	556-67-2	EC50	>1000 ^{mg} / _I	aquatic invertebrates	96 h
decamethylcyclopentasilox- ane	541-02-6	LC50	>16 ^{µg} / _I	fish	96 h
decamethylcyclopentasilox- ane	541-02-6	EC50	>2.9 ^{µg} / _l	aquatic invertebrates	48 h
Propan-2-ol	67-63-0	LC50	10000 ^{mg} / _l	fish	96 h
ethyl alcohol	64-17-5	LC50	14.2 ^g / _l	fish	96 h
ethyl alcohol	64-17-5	EC50	12.9 ^g / _l	fish	96 h
methanol	67-56-1	LC50	15400 ^{mg} / _l	fish	96 h
methanol	67-56-1	EC50	12700 ^{mg} / _l	fish	96 h
methanol	67-56-1	ErC50	22000 ^{mg} / _l	algae	96 h
ethylbenzene	100-41-4	LC50	6.4 ^{mg} / _l	fish	48 h
ethylbenzene	100-41-4	EC50	2.4 ^{mg} / _l	aquatic invertebrates	48 h
cumene	98-82-8	LC50	4.8 ^{mg} / _I	fish	96 h



acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0 Replaces version of: 2015-09-09 (GHS 3)

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
cumene	98-82-8	EC50	2.14 ^{mg} / _l	aquatic invertebrates	48 h
cumene	98-82-8	ErC50	2.01 ^{mg} / _l	algae	72 h
4-methylpentan-2-one	108-10-1	LC50	>179 ^{mg} / _I	fish	96 h
4-methylpentan-2-one	108-10-1	EC50	>200 ^{mg} / _I	aquatic invertebrates	48 h
sodium hydroxide	1310-73-2	EC50	40.4 ^{mg} / _l	aquatic invertebrates	48 h

Aquatic toxicity (chronic)

Aquatic toxicity (chronic) of components of the mixture

aquatic toxicity (cirrollic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
odorless mineral spirits	64742-48-9	EC50	15.41 ^{mg} / _l	microorganisms	40 h
octamethylcyclotetrasilox- ane	556-67-2	LC50	10 ^{µg} / _l	fish	14 d
octamethylcyclotetrasilox- ane	556-67-2	EC50	>500 ^{mg} / _I	aquatic invertebrates	24 h
decamethylcyclopentasilox- ane	541-02-6	LC50	>16 ^{µg} / _I	fish	14 d
decamethylcyclopentasilox- ane	541-02-6	EC50	>15 ^{µg} / _I	aquatic invertebrates	21 d
Propan-2-ol	67-63-0	LC50	>10000 ^{mg} / _l	aquatic invertebrates	24 h
ethyl alcohol	64-17-5	LC50	>0.08 ^{mg} / _I	fish	42 d
ethyl alcohol	64-17-5	EC50	22.6 ^g / _l	algae	10 d
ethyl alcohol	64-17-5	ErC50	675 ^{mg} / _I	algae	4 d
ethylbenzene	100-41-4	LC50	7 ^{mg} / _I	fish	24 h
ethylbenzene	100-41-4	EC50	2.8 ^{mg} / _I	aquatic invertebrates	24 h
cumene	98-82-8	LC50	6.4 ^{mg} / _I	fish	24 h
cumene	98-82-8	EC50	2.45 ^{mg} / _l	aquatic invertebrates	24 h
4-methylpentan-2-one	108-10-1	EC50	3623 ^{mg} / _l	aquatic invertebrates	24 h
4-methylpentan-2-one	108-10-1	ErC50	>146 ^{mg} / _I	algae	7 d

12.2 Persistence and degradability



acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0
Replaces version of: 2015-09-09 (GHS 3)

Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
octamethylcyclotetrasilox- ane	556-67-2	carbon dioxide generation	3.7 %	29 d
decamethylcyclopentas- iloxane	541-02-6	carbon dioxide generation	0.14 %	28 d
Propan-2-ol	67-63-0	oxygen depletion	53 %	5 d
ethyl alcohol	64-17-5	oxygen depletion	74 %	5 d
methanol	67-56-1	oxygen depletion	76 %	5 d
4-methylpentan-2-one	108-10-1	oxygen depletion	83 %	28 d

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
octamethylcyclotetrasilox- ane	556-67-2	12400	4.45	
decamethylcyclopentas- iloxane	541-02-6	7060	4.76 (22.4 °C)	
Stoddard Solvent	8052-41-3		3.16 - 7.15	
ethyl alcohol	64-17-5		-0.35 (pH value: 7.4, 24 °C)	
methanol	67-56-1		-0.77	
ethylbenzene	100-41-4	1	3.6 (pH value: 7.84, 20 °C)	
xylene	1330-20-7	>5.5 - <12.2	3.2 (pH value: 7, 20 °C)	
cumene	98-82-8		3.55 (23 °C)	
4-methylpentan-2-one	108-10-1		1.9 (pH value: 6.7)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

SPECIALTY COATINGS INC.

Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0
Replaces version of: 2015-09-09 (GHS 3)
revision: 2018-11-02

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	(not subject to transport regulations)

14.2 UN proper shipping name not relevant

14.3 Transport hazard class(es)

Class

14.4 Packing group not relevant

14.5 Environmental hazards none (non-environmentally hazardous acc. to the dangerous goods regu-

lations)

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed or exempt from listing

SARA TITLE III (Superfund Amendment and Reauthorization Act)

List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section none of the ingredients are listed

302 and 304)

Specific Toxic Chemical Listings (40 CFR 372) (EPCRA Section 313) none of the ingredients are listed

contains:



acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0 Replaces version of: 2015-09-09 (GHS 3)

> Name of substance CAS No Remarks Effective date 4-methylpentan-2-one 108-10-1 1986-12-31 methanol 67-56-1 1986-12-31 Propan-2-ol 67-63-0 Only persons who 1986-12-31 manufacture by the strong acid process are subject, no supplier notifiction.

Industry or sector specific available guidance(s) NPCA-HMIS® III

Hazardous Materials Identification System (American Coatings Association)

Category	Rating	Description
Chronic	*	Chronic (long-term) health effects may result from repeated overexposure.
Health	0	No significant risk to health.
Flammability	2	Material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.
Physical hazard 0 Material that is normally stable, even under fire conditions, and will not react videcompose, condense, or self-react. Non-explosive.		Material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive.
Personal protective equipment	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)

Category	Degree of hazard	Description	
Flammability	2	Material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.	
Health	0	Material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material.	
Instability	0	Material that is normally stable, even under fire conditions.	
Special hazard			

Right to Know Hazardous Substance List none of the ingredients are listed

Name of substance	CAS No	Remarks	Classifications
4-methylpentan-2-one	108-10-1		F3 R1
sodium hydroxide	1310-73-2		CO R1



acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0 Replaces version of: 2015-09-09 (GHS 3)

Name of substance	CAS No	Remarks	Classifications
ethyl alcohol	64-17-5		CA MU TE F3
methanol	67-56-1		TE F3
Propan-2-ol	67-63-0		F3
Stoddard Solvent	8052-41-3		F2

Legend

CA Carcinogenic.

CO Corrosive.

F2 Flammable - Second Degree.F3 Flammable - Third Degree.

MU Mutagenic.

R1 Reactive - First Degree.

TE Teratogenic.

Proposition 65 List of chemicals

none of the ingredients are listed

Name of substance	CAS No	Remarks	Type of the tox- icity
4-methylpentan-2-one	108-10-1		cancer
4-methylpentan-2-one	108-10-1		developmental
ethyl alcohol	64-17-5	in alcoholic beverages	cancer
ethyl alcohol	64-17-5	in alcoholic beverages	developmental
methanol	67-56-1		developmental

Relevant European Union (EU) safety, health and environmental provisions

Classification according to GHS (1272/2008/EC, CLP)

Hazard class	Category	Hazard class and category
germ cell mutagenicity	1B	(Muta. 1B)
carcinogenicity	1B	(Carc. 1B)
reproductive toxicity	2	(Repr. 2)
aspiration hazard	1	(Asp. Tox. 1)
hazardous to the aquatic environment - chronic hazard	3	(Aquatic Chronic 3)



acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0 revision: 2018-11-02 Replaces version of: 2015-09-09 (GHS 3)

SECTION 16: Other information, including date of preparation or last revision

16.1 Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relevant
1.3	Details of the supplier of the safety data sheet: All Shine 8951 Bonita Beach Road Suite 525-282 Bonita Springs, FL 34135 239-992-2220	Details of the supplier of the safety data sheet: B&B Blending, LLC 10963 Leroy Drive Northglenn CO 80233 United States Telephone: 1.800.875.6320, 1.303.289.6320 Telefax e-mail: info@bbblending.com Website: bbblending.com	yes
1.3		e-mail (competent person):	
1.5		bblahnik@bbblending.com	yes
2.2	Hazardous ingredients for labelling: Stoddard Solvent, dimethylsiloxane cyclic tetramer, Distil- lates (petroleum), hydrotreated light, odorless mineral spirits	Hazardous ingredients for labelling: Stoddard Solvent, octamethylcyclotetrasiloxane, Distillates (petroleum), hydrotreated light, odorless mineral spirits	yes
3.2		Description of the mixture: change in the listing (table)	yes
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic) of components of the mixture: change in the listing (table)	yes
12.2		Degradability of components of the mixture: change in the listing (table)	yes
12.3		Bioaccumulative potential of components of the mixture: change in the listing (table)	yes

16.2 Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR OSHA	29 CFR §1910.1001 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
Acute Tox.	acute toxicity
Asp. Tox.	aspiration hazard
ATE	Acute Toxicity Estimate
BCF	BioConcentration Factor
BOD	Biochemical Oxygen Demand
Carc.	carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	chemical oxygen demand
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level



acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0 Replaces version of: 2015-09-09 (GHS 3)

Descriptions of used abbreviations Abbr. Eye Dam. seriously damaging to the eye Eye Irrit. irritant to the eye Flam. Liq. flammable liquid GHS "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations IARC Monographs IARC Monographs on the Evaluation of Carcinogenic Risks to Humans log KOW n-octanol/water **MARPOL** International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant") Met. Corr. substance or mixture corrosive to metals Muta. germ cell mutagenicity NFPA® 704 National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States) NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition **OSHA** Occupational Safety and Health Administration (United States) **PBT** Persistent. Bioaccumulative and Toxic PEL permissible exposure limit **PNEC** Predicted No-Effect Concentration parts per million ppm Repr. reproductive toxicity Skin Corr. corrosive to skin Skin Irrit. irritant to skin Skin Sens. skin sensitization STEL short-term exposure limit STOT RE specific target organ toxicity - repeated exposure STOT SE specific target organ toxicity - single exposure TWA time-weighted average very Persistent and very Bioaccumulative vPvB

16.3 Key literature references and sources for data

- OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200 49 CFR § 172.101 Hazardous Materials Table (DOT)

16.4 Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).



acc. to OSHA, Appendix D to § 1910.1200

MIL-W-18723D

Version number: GHS 4.0 revision: 2018-11-02 Replaces version of: 2015-09-09 (GHS 3)

16.5

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	highly flammable liquid and vapor
H226	flammable liquid and vapor
H227	combustible liquid
H290	may be corrosive to metals
H301	toxic if swallowed
H302	harmful if swallowed
H304	may be fatal if swallowed and enters airways
H311	toxic in contact with skin
H312	harmful in contact with skin
H314	causes severe skin burns and eye damage
H315	causes skin irritation
H317	may cause an allergic skin reaction
H318	causes serious eye damage
H319	causes serious eye irritation
H331	toxic if inhaled
H332	harmful if inhaled
H335	may cause respiratory irritation
H336	may cause drowsiness or dizziness
H340	may cause genetic defects
H350	may cause cancer
H361f	suspected of damaging fertility
H370	causes damage to organs
H372	causes damage to organs through prolonged or repeated exposure
H373	may cause damage to organs through prolonged or repeated exposure

16.7 Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.