

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Manufacturer Professional Coatings, Inc.,
100 Commerce Park Dr. Cabot, AR 72023

Telephone (501) 843-7509 **Fax** (501) 843-9261

Product Names Aqua-Pro Semi-Gloss

Recommended Use Floor coating

Restrictions on Use For Industrial/Commercial use only

Emergency Contact / Number Chemtrec / (800) 424-9300 (US and Canada) / (703) 527- 3887 (outside US and Canada)

SECTION 2: HAZARD IDENTIFICATION

Hazards

Eye damage/irritation Category 2A, Causes serious eye irritation



Signal Word WARNING

Precautionary Statements

Prevention

Wash hands thoroughly. Wear protective gloves and clothing, eye and face protection.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing. If eye irritation persists get medical advice or attention.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS#	Component Percent
Diethylene glycol monobutyl ether	112-34-5	<5
Triethylamine	121-44-8	<3
Non-hazardous ingredients	Mixture	Balance

SECTION 4: FIRST AID MEASURES

Eye Contact: Flush eyes with clean, lukewarm water for at least 15 minutes while holding eyelids open. Remove contacts. Get medical attention if irritation persists.

Skin Contact: Wash affected area with mild soap and water then rinse with water. Remove any contaminated clothing and wash before reuse. Get medical attention if skin irritation occurs.

Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth and drink 1-2 glasses of water to dilute. Get medical attention.

Inhalation: Remove to fresh air and seek medical attention if adverse effects are observed.

Most Important Symptoms / Effects

May cause eye redness and tearing. Prolonged and repeated skin contact may cause drying. Excessive inhalation of vapors may cause dizziness and headache. Swallowing may cause gastrointestinal irritation and nausea. Effects vary by degree of exposure and individual's susceptibility. See Section 11 for more information.

Indication of Immediate Medical Attention and Special Treatment, If Necessary

Persistent eye or skin irritation, ingestion, gastrointestinal or respiratory distress. See Section 11.

SECTION 5: FIREFIGHTING MEASURES

Suitable and Unsuitable Extinguishing Media

Product will not burn until all water is evaporated. Use fire-fighting techniques suitable to surrounding fire.

Specific Hazards Arising from the Chemical

May produce toxic fumes, gases, and vapors in a fire. Material will not burn until water has been evaporated. Closed containers may rupture or explode when exposed to extreme heat.

Specific Protective Equipment and Precautions for Fire-Fighters

Use a water spray to cool fire-exposed containers, structures and to protect personnel. Do not enter confined fire space without full equipment and a positive pressure NIOSH-approved self-contained breathing apparatus. Closed containers may explode from high heat.

SECTION 6: ACCIDENTAL RELEASE MEASURES

See Section 8 for personal protective gear.

Personal Precautions

Isolate release area and keep unnecessary or untrained people away. Avoid skin or eye contact with spilled material.

Environmental Precautions

Contain spill if it can be done with minimal risk. Prevent liquid from entering drains, sewers or waterways. Advise EPA, state or local agencies as required.

Methods for Cleaning Up

Do not discharge to the environment. Transfer to labeled, sealable containers for product recovery or safe disposal. Small liquid spills can be handled using absorbent material. Larger spills should be diked to prevent runoff to the environment or sewer.

SECTION 7: HANDLING AND STORAGE

See Section 8 for personal protective gear.

Handling and Storage

Use good ventilation and follow all procedures and precautions for handling a possible skin and eye irritant. Best stored at 50 – 90 °F. Reseal lid on container after use. Store only in original or compatible, clearly labeled container.

SECTION 8: EXPOSURE CONTROL AND PERSONAL PROTECTION

Exposure Limits

Component Name	ACGIH TWA	OSHA TWA
Diethylene glycol monobutyl ether	10 ppm	50 ppm

Engineering Controls

Use appropriate ventilation to maintain airborne concentration limits below exposure limits.

Eye and Face Protection

Wear safety glasses or chemical safety goggles; use face shield if splashing is possible e.g. when pouring or working with large amounts.

Skin Protection

Wear protective gloves to avoid repeated or prolonged contact.

Respiratory Protection

Respiratory not normally needed. Maintain good ventilation or air flow. Use a respirator in areas where the exposure is unknown or above OSHA or ACGIH limits.

General Hygiene

Follow accepted work practices for handling an irritant material. Do not eat, drink or smoke in areas where this product is used or stored. Wash thoroughly with soap and water after task or shift, when using the restroom or before eating.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State	White milky liquid	Flash Point (PMCC)	>200 °F
Specific Gravity (Water=1)	1.04 (8.66 lbs/gal)	Upper Flammability Limits	Not Determined
Evaporation Rate (butyl acetate = 1)	<1	Lower Flammability Limits	Not Determined
pH	Not Applicable	Auto-ignition Temperature	Not Determined
Solubility in Water	Miscible	Decomposition Temperature	Not Determined
Odor	Ammonia	Vapor Pressure	Not Determined
Odor Threshold	Not Determined	Vapor Density (Air=1)	>1
Melting/Freezing Point	Not Determined	Partition Coefficient (n-octanol/water)	Not Determined
Boiling Range	>212 °F	Viscosity (mPas, 20 °C)	Not Determined
Initial Boiling Point	Not Determined	Critical Temperature	Not Determined

Note: Physical and chemical properties are provided for safety, health and environmental considerations and do not fully represent product specifications. Those should be requested separately.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Not reactive at normal storage and use conditions

Chemical Stability: Stable at normal storage and use conditions

Possibility of Hazardous Reactions: Will not occur under normal conditions

Conditions to Avoid: Extremely high or low temperatures

Incompatible Materials: Strong oxidizers

Hazardous Decomposition Products: Carbon monoxide and dioxide, other toxic gases or vapors in a fire or at very high temperature.

SECTION 11: TOXICOLOGICAL INFORMATION

Specific toxicity tests have not been conducted on this mixture. In accordance with OSHA's Hazard Communication Standard 1910.1200, this mixture is assumed to have the same health hazards as its significant components.

Acute Toxicity Effects

Likely routes of exposure are skin and eye contact which can cause irritation. Inhalation can cause respiratory irritation. Swallowing material may cause irritation to gastrointestinal tract or nausea depending on individual's sensitivity and amount ingested. Overexposure to vapors and mist may cause dizziness, headache, or nausea. Other components, present at less than 1%, can be damaging to liver, kidneys or central nervous system due to prolonged exposure.

Chronic Toxicity Effects

Long term or repeated exposure may aggravate any acute symptoms. Other components, present at less than 1%, can be damaging to liver, kidneys or central nervous system through repeated exposure.

Carcinogenicity

NTP, OSHA and IARC have not identified any carcinogenic ingredients above the statutory limit.

SECTION 12: ECOLOGICAL INFORMATION

Specific environmental tests have not been conducted on this mixture. The product is not classified as an environmental hazard based on its main components.

SECTION 13: DISPOSAL CONSIDERATIONS

Avoid release to the environment. Dispose of in accordance with local, state/province, and federal environmental regulations.

SECTION 14: TRANSPORT INFORMATION

DOT Information Not Regulated

SECTION 15: REGULATORY INFORMATION

TSCA Status All components are listed in the TSCA inventory
SARA 311/312 Reporting Categories None
SARA 313 Reportable Ingredients Diethylene glycol monobutyl ether (CAS 112-44-5) <5%
Triethylamine (CAS 121-44-8) <3%

SECTION 16: OTHER INFORMATION

Department Issuing SDS Health and Safety

Disclaimer

Important Notice to Purchaser. The information in this publication is based on tests that we believe are reliable. Your results may vary due to differences in test types and conditions. You must evaluate and determine whether the product is suitable for your intended application. **Professional Coatings, Inc.'s** exclusive warranty is as follows: If **Pro-Coat** products are proved defective, the user's exclusive remedy will be, at **Pro-Coat's** option, to replace the defective **Pro-Coat** product or to refund the purchase price for the defective quantity. Except for the replacement or refund remedies, **Pro-Coat** is not liable for direct damages or liable for indirect, incidental or consequential damages, regardless of the legal theory asserted, including negligence and strict liability.

ADDITIONAL COMMENTS

We recommend that containers be either professionally reconditioned for reuse by certified firms or properly disposed of by certified firms to help reduce the possibility of an accident. Disposal of containers should be in accordance with applicable federal, state and local laws and regulations. "EMPTY" drums should not be given to individuals. The conditions of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.