

WHITE WATER SEALER™ WATERBORNE WOOD SEALER

EXCLUSIVELY DESIGNED
TO PROVIDE A TRUE
WHITWASHED
APPEARANCE.



TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

ProCoat® White Water Sealer™ is exclusively designed to provide a whitewashed appearance to any wood species. Its versatility allows you to achieve a variety of looks, from a subtle wash to a bold Scandinavian appearance.

PRODUCT FEATURES

- Two-Component
- White Washed Appearance
- Reduces Tannin Bleed
- Easy Application
- Excellent Abradability
- 2-3 Hour Dry Time
- Environmentally Friendly
- V.O.C Compliant
- Water Clean-Up

PRODUCT USES

- Ideal for wood, parquet, and cork flooring
- Use on newly sanded domestic & exotic woods
- Residential and commercial applications
- Sand & finish applications

TYPICAL PROPERTIES

FINISH TYPE	Ultra-Matte White Waterborne Sealer
COLOR	Milky White (wet)
SOLIDS CONTENT	35% +/- 2%
VOC	<50 g/l
WEIGHT/GALLON	8.70 lbs/gal
TABER CS17 1000G@1000C	45 mg loss
FLASH POINT	>200°F (93°C)
ODOR	Mild, Non-Offensive
CLEAN UP	Water
COVERAGE RATE	350-450 sq ft/gal
APPLICATION	Microfiber Roller
PACK SIZE	3 x 1 Gallon (36 boxes/pallet)
SHELF LIFE	12 months from date of production (unopened)
SHEEN (60°)	Ultra Matte (3)
STORAGE/TRANSPORT	Keep from freezing. Store and transport between 50°F - 90°F
DISPOSAL	Waste & empty containers should be handled in accordance with local regulations
DRYING TIME, UNTIL	Ready for sanding/recoating: 2-4 hours* Light Use: 24 hours* Fully Cured: 5 days* * = under normal climate conditions, 65°F - 80°F /40-60% RH

FOR TECHNICAL ADVICE CONTACT (800) 962-0344



APPLICATION PROCEDURES

Sand and prepare wood surface following NFWA guidelines.

Always prepare a small test area to determine compatibility.

Shake WHITE WATER SEALER™ (Part A) well prior to adding PROCOAT® ISO HARDENER™ (Part B). Mix 1-part hardener to 10-parts WHITE WATER SEALER™. Do not thin or add water. One 12.8 oz. bottle of hardener will activate 1 gallon of finish. Shake mixture vigorously for 30-45 seconds and let sit for 10-15 minutes before applying. POT LIFE: 2 HOURS ONCE MIXED

Roller Application

- The use of 3/8 microfiber rollers are suggested.
- Apply evenly at recommended coverage rate. Avoid streaking, puddles, and lap marks. Do not spread too thin.
- The applicator should evaluate each application and use the appropriate roller material and size determined by the porosity of the substrate being coated.

T-Bar Application

- Pour a 6" to 8" wide line of finish along the starting wall.
- Following the grain of the wood, draw a clean, pre-dampened applicator forward.
- Following the grain of the wood, move the finish toward the opposite wall.
- Hold the applicator at a snowplow angle to maintain a wet edge at all times.
- Maintain at least 3" wide wet edge at all times to ensure proper coverage rate.
- To prevent lapping and dry marks, use recommended coverage of 350-450 square foot per gallon.
- Do not spread too thin.
- When cutting in floor, never work more than five feet ahead of the person applying the finish.
- For smoothest results, before applying final coat, buff with conditioning pad.
- Always vacuum and tack thoroughly with a slightly water-dampened mop or cloth after abrading.

Intercoat Abrasion

It is unnecessary to abrade between ProCoat® Waterborne sealer & finish coats unless more than 24 hours has passed since the previous coat was applied. For smoothest results, abrade between each coat as necessary using 180-240 grit abrasives.

PREVENTION & RESPONSE

Wash hands thoroughly. Wear protective gloves and clothing. Use eye and face protection. In case of eye contact, flush immediately with water for several minutes. Seek medical attention if irritation occurs. If on skin, wash thoroughly with soap and water.

RECOMMENDED SYSTEMS | WOOD

Newly Sanded Floors

Apply 1-2 coats of ProCoat® WHITE WATER SEALER™. Allow to dry overnight. Abrade, vacuum, and tack surface prior to coating.

Sheen Option: Apply 2 coats of ProCoat® WHITE WATER SEALER™ and allow overnight dry. Abrade, vacuum, and tack surface well. Apply 1 coat of ProCoat® Aqua-Pro™ using desired sheen.

Coating over Stains

Allow stain to dry per manufacturer's directions or longer depending on atmospheric conditions. A test area is recommended to ensure compatibility with stain.

MAINTENANCE CARE

Vacuum and mop the floor regularly with ProCare® Citrus Floor Cleaner. This cleaner leaves no film or sticky residue and is safe around kids and pets. Detailed maintenance instructions are available at www.procoatinc.com.



SCAN TO SHOP PROCARE®
CITRUS FLOOR CLEANER

available at
amazon

WARRANTY

If ProCoat® products are proved defective, the user's exclusive remedy will be at ProCoat's® option to replace the defective ProCoat® products or to refund the purchase price for the defective quantity. Except for the replacement or refund remedies, ProCoat® is not liable for direct damages or liable for indirect, incidental or consequential damages, regardless of the legal theory asserted, including negligence and strict liability.

FOLLOW US ON SOCIAL MEDIA @procoat



Email: info1@procoatinc.com
Web: procoatinc.com



Address: 100 Commerce Park Drive
Cabot, Arkansas 72023

PROCOAT
Hardwood Floor Coatings and Specialty Products